TECHNICAL EVALUATION — TABLE CLOCKS

1. Evaluation output

Field	Value
Report	1.Table Clocks.pdf (113 pages)
Standards	IEC 60335-1:2010 (Part 1); IEC 60335-2-26:2002 (Part 2 2-26)
Created	2026-11-03 04:58 UTC

2. Report identity

Field	Value
Report number	(2024)DRI-05273
Laboratory	Fujian Inspection and Research Institute for Product Quality
Report date	14 May 2026
Product declared	Table Clocks
Declared model	2508-01
Standards claimed	US IEC 60335-2-26:2002; IEC 60335-1:2020
Standards evaluated	US IEC 60335-1:2010; US IEC 60335-2-26:2002

3. Summary

Field	Value
Final verdict	REPORT CORRECTION / REPLACEMENT REQUIRED — PRODUCT COMPLIANCE NOT DETERMINED — CERTIFICATION HOLD
Reason	The report contains unresolved model and rating conflicts, incorrectly attributed material, and missing or inconsistent safety-test evidence. The clock’s applicability to the supplied particular standard also requires resolution.
Recommended action	Obtain an authenticated replacement report and supporting construction and test records, then reassess the identified model against the applicable editions before certification.
Conclusion	The submitted report does not provide a reliable basis for a compliance decision for model 2508-01. No product non-conformity is established solely from the documented inconsistencies; the report, test attribution, scope and missing evidence require resolution.
Findings	20 total — Critical 7, High 13, Medium 0, Low 0

4. Findings

Priority	Clause	Normative requirement	Finding reason	Required action	Pages	Evidence
Critical	1	The particular standard excludes battery-operated clocks.	The report claims application of the clock standard while also claiming that the appliance has a rechargeable battery; the construction and supply arrangements are insufficiently established to resolve the scope exclusion.	Establish the clock's construction and supply arrangements and demonstrate the applicability of the claimed standard.	PDF pp.1,70–72	Report: verified p.70 Standard: verified in IEC 60335-2-26:2002 p.11
Critical	7.1	The appliance is to be marked with its model or type reference.	Model 2508-01 is declared on the cover, but the report states that the test data are based on model 504D; their relationship is not established.	Provide traceable identification and evidence linking the tested sample to the declared model.	PDF pp.1,3	Report: verified p.1 Standard: verified in IEC 60335-1:2010 p.29
Critical	10.1	Power input is measured at rated voltage and assessed against the applicable deviation.	The cover declares DC 3 V and 3 W, whereas the power-input table uses 5 V and a 1.0 W rating; the result cannot be attributed to the declared rating.	Resolve the rated voltage and power and provide a valid power-input assessment for the declared model.	PDF pp.1,95	Report: verified p.95 Standard: verified in IEC 60335-1:2010 p.37
Critical	11.5; 11.6	Motor-operated and combined appliances are tested at the most unfavourable voltage between 0.94 and 1.06 times rated voltage.	The heating record states 233.2 V and 253 V, inconsistent with the declared DC 3 V rating; the applicable test supply and attribution are not established.	Provide traceable heating results at the applicable test voltage for the declared construction.	PDF pp.1,12,95	Report: verified p.95 Standard: verified in IEC 60335-1:2010 p.41
Critical	—	The appliance is supplied at rated voltage with continuous battery charging for 168 h.	A pass for the 168 h test is claimed, but the declared test period from 10 to 14 May 2026 spans only four days and cannot accommodate 168 h within that interval.	Provide authenticated test dates and records demonstrating completion of the 168 h test.	PDF pp.1,72	Report: verified p.1 Standard: verified in IEC 60335-1:2010 p.123
Critical	5.2; 6.1; 11	Relevant tests are carried out on the appliance and its classification is verified by inspection and relevant tests.	Pages 108–113 contain sauna-heater and hand-held-appliance material and a class I classification, conflicting with the declared table clock and the class III classification on page 3.	Replace the affected pages with correctly attributed records and verify the integrity of the complete report.	PDF pp.3,108–113	Report: verified p.108 Standard: verified in IEC 60335-1:2010 p.26
Critical	2; 5	The applicable particular part supplements or modifies the corresponding general-part clauses.	The report claims IEC 60335-1:2020, while the supplied general part is US IEC 60335-1:2010; compliance with the supplied edition is not established by the claim alone, and the claimed 2020 edition was not supplied for review.	Provide an edition-specific assessment against the intended general part and supply IEC 60335-1:2020 if its claim is to be reviewed.	PDF p.1	Report: verified p.1 Standard: verified in IEC 60335-2-26:2002 p.8
High	3.1.9; 11.1	Except for spring-driven clocks with electrically operated winding, clocks are operated with the rotor locked for normal operation.	The report gives heating results but does not establish the clock mechanism or whether the applicable locked-rotor condition was used.	Identify the clock mechanism and document the applicable normal-operation test condition.	PDF pp.12,95	Report: verified p.12 Standard: verified in IEC 60335-2-26:2002 p.12
High	13.2; 16.2	Leakage current is checked at operating temperature and following the humidity treatment using the applicable limits.	Both leakage-current tables are marked N/A and contain no measurements, although the report identifies a class III appliance; no adequate justification is recorded.	Provide the applicable leakage-current results or a construction-specific justification for any exclusion.	PDF pp.3,13,16,97–98	Report: verified p.97 Standard: verified in IEC 60335-1:2010 p.45
High	15.3	The humidity treatment is conducted for 48 h at the specified humidity and temperature, followed by the Clause 16 tests.	The report records 93% RH and 48 h but gives no cabinet temperature or initial specimen temperature; the required subsequent leakage-current result is also absent.	Provide the humidity-conditioning temperatures and the applicable post-conditioning test results.	PDF pp.16,98	Report: verified p.16 Standard: verified in IEC 60335-1:2010 p.49
High	19.11; 19.11.1; 19.11.2	Electronic circuits are evaluated against the specified fault conditions unless the stated low-power exemption conditions are satisfied.	A pass is claimed for electronic-circuit evaluation, but the fault-condition entries are N/A and the appended abnormal-operation table is uncompleted; the exemption is not demonstrated.	Document the circuit assessment, applicable faults, test results and any justified exemption.	PDF pp.18, 20–22,99–100	Report: verified p.18 Standard: verified in IEC 60335-1:2010 p.55

Priority	Clause	Normative requirement	Finding reason	Required action	Pages	Evidence
High	20.1	Appliances intended for use on a surface, other than fixed and hand-held appliances, must have adequate stability.	The product is declared as a table clock, but stability is marked N/A without establishing that an exception applies.	Establish the appliance classification and provide the stability test result if applicable.	PDF pp.1,26	Report: verified p.26 Standard: verified in IEC 60335-1:2010 p.60
High	21.1	The particular standard specifies an impact energy of 0.20 J and limits application to dial glasses under the stated condition.	The report records 0.5 J on the plastic enclosure, not the specified 0.20 J, and does not establish the dial-glass assessment.	Document and assess the impact test using the particular-standard conditions.	PDF pp.26,101	Report: verified p.101 Standard: verified in IEC 60335-2-26:2002 p.13
High	22.14	Appliances must not have hazardous ragged or sharp edges in normal use or user maintenance, subject to the stated functional exception.	The inspection is marked N/A without a construction-specific reason.	Inspect and record the assessment of accessible edges and fastener points.	PDF p.30	Report: verified p.30 Standard: verified in IEC 60335-1:2010 p.66
High	24.1	Components must comply with relevant IEC safety requirements as far as reasonably applicable.	The report claims a component-list pass and refers to an appended table, but no component list or supporting component evidence is supplied in the report.	Provide the component list and the applicable component compliance or test evidence.	PDF pp.39,106	Report: verified p.39 Standard: verified in IEC 60335-1:2010 p.75
High	27.1	Class III appliances must have no provision for earthing.	The report classifies the clock as class III but marks the corresponding earthing-provision check N/A without an inspection result.	Inspect and record whether the appliance has any earthing provision.	PDF pp.3,55	Report: verified p.55 Standard: verified in IEC 60335-1:2010 p.89
High	29.1; 29.2	Clearances and creepage distances are assessed against the applicable electrical stresses, working voltage, material group and pollution degree.	Clause 29 is marked N/A solely because the stated working voltage is DC 5 V; the report supplies neither measurements nor a demonstrated applicable exemption.	Identify the relevant insulation paths and provide measurements or a substantiated exemption.	PDF pp.59–63,102–105	Report: verified p.59 Standard: verified in IEC 60335-1:2010 p.97
High	30.1	Relevant external non-metallic parts whose deterioration could impair compliance are subjected to the specified heat-resistance assessment.	The report identifies a plastic enclosure but marks the ball-pressure assessment N/A and supplies no result or exclusion rationale.	Assess the enclosure’s applicability and provide the specified heat-resistance evidence where required.	PDF pp.65, 96,106	Report: verified p.96 Standard: verified in IEC 60335-1:2010 p.102
High	30.2.3.2; 30.2.4	Applicable unattended-appliance connection materials and PCB base materials are assessed by the specified fire-resistance tests or permitted alternatives.	The report claims a pass for 30.2.3.1 but marks 30.2.3.2 and PCB base-material testing N/A without identifying applicable exemptions or material classifications.	Provide the applicable tests or documented exemption and material-classification evidence.	PDF pp.67–69,106–107	Report: verified p.69 Standard: verified in IEC 60335-1:2010 p.106
High	11.7	Charging for the heating test lasts the period stated in the instructions or 24 h, whichever is longer.	The report records only "Period stated in the instructions"; neither that period nor the actual charging duration is given.	Record the specified and actual charging durations and verify the longer-period requirement.	PDF p.72	Report: verified p.72 Standard: verified in IEC 60335-1:2010 p.123