TECHNICAL EVALUATION — SUBMERSIBLE PUMP

1. Evaluation output

Field	Value
Report	2.Submersible pump.pdf (89 pages)
Standards	IEC 60335-2-41:2021 (Part 2 2-41)
Created	2026-11-01 11:38 UTC

2. Report identity

Field	Value
Report number	EN201222034S
Laboratory	EMTEK(NINGBO) CO., LTD.
Report date	Dec 28, 2025
Product declared	Submersible pump
Declared model	SPC55068
Standards claimed	IEC 60335-1:2010+A1:2013+A2:2016; IEC 60335-2-41:2025 in the test specification; IEC 60335-2-41:2012 in the compliance summary
Standards evaluated	ILNAS-EN IEC 60335-2-41:2021, endorsing IEC 60335-2-41:2012, supplied particular part only. IEC 60335-1 and EN IEC 60335-2-41:2021/A11:2021 were not supplied.

3. Summary

Field	Value
Final verdict	REJECT — INSUFFICIENT TECHNICAL EVIDENCE
Reason	The tested model and electrical test basis conflict with the declared product, and several applicable particular-part assessments lack substantiated evidence. The general part and European A11 amendment were not supplied, preventing a complete standards assessment.
Recommended action	Obtain an authenticated, corrected or replacement report for SPC55068 with applicable test evidence and supply the relevant Part 1 and A11 amendment before certification proceeds.
Conclusion	Compliance of SPC55068 cannot be determined from this report. The conflicting sample identity and ratings invalidate reliance on the reported pass results for the declared product; the remaining marking, immersion, cord and fire-resistance evidence must also be resolved.
Findings	19 total — Critical 4, High 14, Medium 1, Low 0

4. Findings

Priority	Clause	Normative requirement	Finding reason	Required action	Pages	Evidence
Critical	—	The supplied particular part specifies safety requirements for pumps.	The declared model is SPC55068, but the testing summary identifies 4TSC4.0-96-110/1000 as the model fully tested; no relationship between the models is established.	Identify the tested sample and provide a report covering SPC55068 or substantiated evidence establishing applicability of the tests.	PDF pp.1,2,3	Report: verified p.3 Standard: verified in IEC 60335-2-41:2021 p.8
Critical	7.1	The applicable rated-voltage marking requirement is in Part 1, which was not supplied.	The declared rating is 220–240 V, whereas the clause 7.1 entry records 96 V; the supply is also identified as DC despite the 50 Hz declared rating.	Correct the product rating and supply identification using verified sample and marking evidence.	PDF pp.2,3,4,6	Report: verified p.6 Standard: requirement not in supplied standards
Critical	10.1	The applicable power-input assessment requirement is in Part 1, which was not supplied.	The declared rated input is 550 W, but the test table uses 1,000 W and reports 995.2 W at 72 V; the result cannot establish compliance for the declared rating.	Provide a valid power-input assessment for the identified 550 W model and its applicable supply.	PDF pp.2,3,79	Report: verified p.79 Standard: requirement not in supplied standards
Critical	11; 13; 16; 19	The supplied particular part applies the corresponding Part 1 safety tests, with its stated modifications.	Heating and leakage-current tables use 76.3 V, and the locked-rotor table uses 116.6 V DC, inconsistent with the declared 220–240 V, 50 Hz rating.	Verify the tested sample and repeat or substantiate the applicable tests at the correct supply conditions.	PDF pp.2,4 ,79,80,81	Report: verified p.81 Standard: verified in IEC 60335-2-41:2021 p.12
High	—	The supplied European particular part endorses IEC 60335-2-41:2012 and is read with its identified European amendment.	The test specification cites IEC 60335-2-41:2025, while the compliance summary cites IEC 60335-2-41:2012; the actual assessment basis is unresolved.	Confirm the edition used and provide the applicable Part 1 and A11 amendment for a complete assessment.	PDF pp.2,3	Report: verified p.2 Standard: verified in IEC 60335-2-41:2021 p.4
High	5.101; 25.14	Pumps are tested as portable unless fixed, and portable pumps other than the stated exceptions undergo the cord-flexing test.	Both provisions are marked N/A without establishing that the pump is fixed; the portable and fixed selections are not identified, although a fixed-appliance cord anchorage test is recorded.	Establish whether the pump is fixed and perform the applicable portable-appliance and cord-flexing assessment.	PDF pp.4,6 ,43,44	Report: verified p.43 Standard: verified in IEC 60335-2-41:2021 p.13
High	7.1	A submersible pump rated above 50 W must be marked with its maximum operating depth, with a minimum of 1 m.	The declared 550 W submersible pump has maximum operating depth recorded as N/A, and the corresponding marking provision is also marked N/A.	Establish and verify the maximum operating depth marking on the tested model.	PDF pp.2,4,7	Report: verified p.7 Standard: verified in IEC 60335-2-41:2021 p.14
High	7.1; 5.7; 11.7	Pumps must be marked with maximum liquid temperature, and the liquid temperature must be maintained as specified during testing.	The report refers to the marking plate and states only a maximum liquid temperature below 45 °C; the reproduced plate does not show an exact temperature and the actual test-liquid temperature is not recorded.	Provide the verified temperature marking and actual liquid temperatures used for the applicable tests.	PDF pp.3,6 ,7,14,79	Report: verified p.3 Standard: verified in IEC 60335-2-41:2021 p.14
High	7.12.1	Installation instructions for pumps rated above 50 W must state the maximum total head in metres.	The report gives a pass and refers to marking detail, but no maximum total-head value or supporting installation instruction is provided.	Provide the installation instructions and verify the maximum total-head value for SPC55068.	PDF pp.3,10	Report: verified p.10 Standard: verified in IEC 60335-2-41:2021 p.14
High	3.1.9; 19.101	The specified normal-operation head must achieve the highest power input, and the dry-running test must use approximately half maximum total head at rated voltage.	The report gives a pass for the dry-running sequence but records neither the actual total head nor the applied voltage for that sequence; normal-operation hydraulic conditions are also not substantiated.	Provide the measured head, supply and operating records for normal operation and the complete dry-running sequence.	PDF pp.13, 25,79,81	Report: verified p.25 Standard: verified in IEC 60335-2-41:2021 p.17
High	15.1.2	Submersible pumps undergo the specified 24 h immersion and depth-dependent water-pressure test.	A pass is recorded without the maximum operating depth, actual pressure, water temperature or salinity; the report also refers to 5 m rather than the supplied standard’s 15 m alternative.	Establish the marked depth and provide or repeat the immersion test with all required conditions recorded.	PDF pp.4,17	Report: verified p.17 Standard: verified in IEC 60335-2-41:2021 p.16

Priority	Clause	Normative requirement	Finding reason	Required action	Pages	Evidence
High	24.1.3	Level switches are subjected to 50,000 operating cycles.	The level-switch test is marked N/A, while the overview image appears to show a float-operated device; the report does not resolve whether it is a level switch fitted to the tested sample.	Identify the device in the overview and provide the applicable level-switch assessment or a substantiated exclusion.	PDF pp.38,88	Report: verified p.38 Standard: verified in IEC 60335-2-41:2021 p.19
High	25.1; 25.3	Submersible pumps other than class III must have a flexible supply cord fitted with a plug.	The particular-part cord and plug provisions are marked N/A for the declared class I submersible pump; the general plug entry is marked pass, leaving the record contradictory.	Verify and document the fitted flexible cord and plug and correct both particular-part verdicts.	PDF pp.4,40,41	Report: verified p.40 Standard: verified in IEC 60335-2-41:2021 p.19
High	25.7	Outdoor pumps other than class III require the specified polychloroprene or equivalent cord, subject to the stated exceptions.	Outdoor use is selected, but the report addresses an indoor-cord provision and provides no cord designation or assessment against the supplied outdoor requirement.	Identify the supply cord and assess it against the applicable outdoor-pump requirement.	PDF pp.4,41,42	Report: verified p.42 Standard: verified in IEC 60335-2-41:2021 p.19
High	25.8	The outdoor submersible pump cord must be at least 10 m or 3 m longer than the marked maximum operating depth, whichever is greater.	The applicable outdoor cord-length provision is marked N/A, with neither cord length nor operating depth recorded.	Measure the cord and establish the marked operating depth before assessing the required minimum length.	PDF pp.4,42	Report: verified p.42 Standard: verified in IEC 60335-2-41:2021 p.19
High	30.2	The specified fire-resistance provision applies according to the pump enclosure and RCD-instruction conditions; otherwise 30.2.3 applies.	All clause 30.2 routes are marked N/A and the fire-test table is empty, although an insulating bushing is listed; the conditions for selecting the applicable route are not established.	Establish the applicable clause 30.2 route and provide the required component or material evidence.	PDF pp.56, 57,82,87	Report: verified p.56 Standard: verified in IEC 60335-2-41:2021 p.20
High	29.1; 29.2	The applicable clearance and creepage requirements are in Part 1, which was not supplied.	The clearance table records a 500 V impulse basis and the basic creepage assessment uses the ≤50 V row, without establishing their applicability to the declared 220–240 V model.	Reassess and document the insulation distances using the verified circuit voltages and applicable Part 1 requirements.	PDF pp.2,5 1,54,83	Report: verified p.83 Standard: requirement not in supplied standards
High	—	A report must provide reliable attribution of its evidence; a specific report-identification requirement is not present in the supplied particular part.	PDF page 86 carries report number EN200622010S rather than EN201222034S, raising uncertainty about attribution of the creepage-table continuation.	Obtain a laboratory-issued corrected report with verified page attribution and complete numbering.	PDF pp.2,5 4,63,81,86	Report: verified p.86 Standard: requirement not in supplied standards
Medium	22.101	Submersible pumps are not subjected to the clause 22.101 static-pressure test.	The report records a pass for the static-pressure test despite identifying the product as submersible and reproducing the exclusion.	Correct the clause disposition and clarify whether the recorded test relates to the declared sample.	PDF pp.2,34	Report: verified p.34 Standard: verified in IEC 60335-2-41:2021 p.18