TECHNICAL EVALUATION — SPEAKER

1. Evaluation output

Field	Value
Report	2 speaker.pdf (36 pages)
Standards	IEC 60065 (Standard)
Created	2026-11-01 13:01 UTC

2. Report identity

Field	Value
Report number	ED253584626L
Laboratory	EMTEK (DONGGUAN) CO., LTD.
Report date	May 20, 2025
Product declared	Speaker, DC 5 V, 1 A
Declared model	2
Standards claimed	IEC 60065-2014
Standards evaluated	IEC 60065:2014, edition 8.0

3. Summary

Field	Value
Final verdict	REPORT CORRECTION / REPLACEMENT REQUIRED — PRODUCT COMPLIANCE NOT DETERMINED — CERTIFICATION HOLD
Reason	The tested sample’s attribution is uncertain and several applicable safety assessments are missing, marked not applicable without justification, or insufficiently documented. No product non-conformity is established solely from the available measurements.
Recommended action	Obtain a correctly attributed, edition-aligned replacement report with the missing assessments and supporting test records before certification proceeds.
Conclusion	The supplied report does not provide a reliable basis for demonstrating compliance of speaker model 2 with IEC 60065:2014. Sample identity, supply and battery configuration, mechanical testing, humidity treatment, fault selection and temperature-limit justification require resolution and reassessment.
Findings	14 total — Critical 1, High 13, Medium 0, Low 0

4. Findings

Priority	Clause	Normative requirement	Finding reason	Required action	Pages	Evidence
Critical	4.1.2	Test samples must be representative of the apparatus supplied to the user or be the actual apparatus ready for shipment.	The particulars record steam discharge and a detachable liquid container for the declared speaker, without explaining their relationship to the photographed sample; attribution of the assessment to model 2 is therefore uncertain.	Verify the tested sample's identity and replace the inconsistent particulars with a traceable product description.	PDF pp.1,3–4,36	Report: verified p.4 Standard: approximate in IEC 60065 p.28
High	4.2.2; 4.2.12	Normal operating tests use the specified supply-voltage variation and, where applicable, a test supply with suitable current capacity and characteristics.	The 5 V rated product was tested for heating at 4.5 V and 5 V; the record does not establish whether 5.5 V was less unfavourable or identify the supply characteristics needed to assess the USB supply arrangement.	Establish the applicable supply arrangement and test or justify the most unfavourable voltage and supply characteristics.	PDF pp.1,33,35	Report: verified p.33 Standard: approximate in IEC 60065 p.30
High	4.1.4; 7.1.1	Temperature measurements must use the specified positioning, and the apparatus must also meet Table 3 when tested on an open bench.	The report refers to the user manual but does not identify the heating-test positioning or record a separate open-bench assessment.	Document the test positioning and provide the required open-bench results.	PDF pp.5,33	Report: verified p.5 Standard: verified in IEC 60065 p.29
High	4.1.6; 4.2.5; 7.1.1	An audio amplifier is operated at one-eighth of non-clipped output power using the specified signal or an allowed alternative.	The table records 0.10 W as one-eighth of maximum output, but does not record the measured non-clipped output power or identify the test signal and its characteristics.	Provide the non-clipped output-power determination and identify the signal used for the heating test.	PDF p.33	Report: verified p.33 Standard: verified in IEC 60065 p.31
High	5.2	Apparatus supplied by d.c. only must be marked with the specified d.c. supply symbol.	The marking-plate copy shows "DC 5V 1A" but does not show the specified d.c. symbol, although the report assigns a pass to the voltage and symbol item.	Provide and verify a corrected marking plate bearing the applicable supply symbol.	PDF pp.2,5	Report: verified p.2 Standard: verified in IEC 60065 p.36
High	7.1.2; 7.1.6	Temperature rises must not exceed the applicable Table 3 values, considering the part and relevant conditions.	The table assigns a 55 K limit to the battery and outside enclosure, but does not identify the battery chemistry, enclosure material or basis for those limits; the measured rises are 5.0 K and 5.3 K respectively.	Identify the materials and battery chemistry and substantiate the applicable temperature-rise limits.	PDF pp.33,35	Report: verified p.33 Standard: verified in IEC 60065 p.44
High	8.12; 8.13; 14.4; 14.11; 19.7	The supplied edition contains specific construction, component and mounting requirements under its own clause numbering.	The report uses a different clause structure: for example, it labels 8.12 void although the supplied standard contains a fastening requirement there, and battery and mounting provisions are also shifted.	Issue a report correctly mapped to IEC 60065:2014 and reassess the applicable requirements.	PDF pp.7–8,11–14,18	Report: verified p.7 Standard: verified in IEC 60065 p.51
High	9.1.7	The enclosure must be sufficiently resistant to external forces and compliance is checked by the specified tests.	The external-force assessment is marked N without a reason or test record.	Perform and record the applicable enclosure force tests or provide a standard-based justification.	PDF pp.8–9	Report: verified p.8 Standard: verified in IEC 60065 p.58
High	10.3; 10.4	Safety must not be impaired by humidity encountered in intended use, with humidity treatment followed by the applicable insulation tests.	Humidity treatment is marked N without explanation, and the insulation resistance and electric strength tables contain no results.	Provide the humidity-treatment assessment and subsequent applicable insulation-test results, or justify each exclusion.	PDF pp.9,34	Report: verified p.9 Standard: verified in IEC 60065 p.60
High	12.1.3; 12.1.5	Portable apparatus is subject to the specified vibration test and, at 7 kg or less, the drop test.	The report identifies the apparatus as portable and below 7 kg, yet marks both vibration and drop tests N without justification.	Conduct and document the vibration and drop tests on the representative apparatus.	PDF pp.3,10,17	Report: verified p.10 Standard: verified in IEC 60065 p.67
High	12.1.6	Moulded or formed thermoplastic enclosures must undergo the specified stress-relief assessment.	The report identifies screws fixing a plastic enclosure but marks the thermoplastic enclosure stress-relief test N without identifying the material or construction.	Identify the enclosure material and perform the stress-relief test if it is moulded or formed thermoplastic.	PDF pp.10,16	Report: verified p.10 Standard: verified in IEC 60065 p.68
High	4.3.1; 4.3.5; 11.2	Relevant fault conditions are applied individually, with consequential faults, to check that hazardous overheating does not occur.	Several fault tests are recorded, but the report provides no circuit-based fault selection or justification for omitting component short-circuit and disconnection conditions.	Provide the circuit analysis and results or justified exclusions for the relevant fault conditions.	PDF pp.9,34–35	Report: verified p.34 Standard: verified in IEC 60065 p.32

Priority	Clause	Normative requirement	Finding reason	Required action	Pages	Evidence
High	14.11.1; 14.11.3	Batteries must be mounted to prevent hazardous gas accumulation and insulation damage, and applicable charging or lithium currents must remain within manufacturer limits.	The report records battery overcharge testing but lists a 1.5 V R03 battery and marks battery mounting and charging-current assessments N; the battery chemistry, rechargeability and current limits are not established.	Identify the installed battery and charging arrangement and provide the applicable mounting and current-limit assessments.	PDF pp.14, 34–35	Report: NOT FOUND Standard: verified in IEC 60065 p.100
High	14.11.4; 14.11.5	Applicable special batteries must withstand the specified mould stress-relief and drop tests without releasing electrolyte.	Battery mould stress relief and drop tests are marked P, but no sample details, conditioning, drop results or evidence establishing applicability are recorded.	Provide the test records and applicability basis for both battery assessments.	PDF pp.14,35	Report: verified p.14 Standard: verified in IEC 60065 p.101