



Customer : SAP	Motor Type : TC22	Output Power [kW] : 1,1	Voltage [V] : 230	Speed [min-1] : 1800
Supply : Monofase	Poles : 4	Frequency : 60Hz	IP : OO	Insulation : F
Test Data : 28/10/2014	Duty Cycle : S3 30%	Temp. [°C]: 22,4	R 1 [Ω]: 1,91	R 2 [Ω]: 3,99
Capacit. [μF] : 30μF			L 1 [mH] : 15,93	L 2 [mH] : 27,34

Prova : H:\Prove\SAP\ 5622684C7M0.TXT

Note: ST.150x90x100 cod.st.A9323161280 cod.mot.19461985684

cod.avv.232316558101A cod.ind.IA1-15G

No Load Test

N.	Iap RPM	Freq Hz	VI Volt	Va Volt	Vc Volt	AI Amp	Am Amp	Aa Amp	Win kW	VA kVA	Cosfi	Capac. mF
1	1785	60,0	206,9	294,2	373,3	2,064	2,058	4,073	0,333	0,427	0,779	30,0
2	1785	60,0	209,9	297,6	377,8	2,104	2,080	4,124	0,348	0,442	0,788	30,0
3	1785	60,0	219,8	309,7	393,6	2,127	2,277	4,308	0,375	0,467	0,802	30,0
4	1786	60,0	229,9	321,5	409,5	2,135	2,523	4,505	0,396	0,491	0,806	30,0
5	1786	60,0	239,8	332,6	424,5	2,155	2,793	4,699	0,420	0,517	0,812	30,0
6	1787	60,0	249,8	343,3	438,8	2,208	3,083	4,892	0,448	0,552	0,812	30,0
7	1787	60,0	252,8	346,9	443,2	2,197	3,201	4,946	0,451	0,556	0,813	30,0

Load Test

N.	Iap RPM	Torque Nm	Wout kW	Eff %	Slip %	Freq Hz	VI Volt	Va Volt	Vc Volt	AI Amp	Am Amp	Aa Amp	Win kW	VA kVA	Cosfi	Capac. mF
1	1603	6,556	1,101	69,7	10,92	60,0	207,1	217,0	288,2	7,839	6,441	3,140	1,579	1,623	0,973	30,0
2	1619	6,492	1,101	71,0	10,06	60,0	210,1	225,9	297,8	7,543	6,022	3,246	1,550	1,585	0,978	30,0
3	1654	6,382	1,105	73,4	8,13	60,0	220,2	250,1	325,1	6,934	5,133	3,551	1,505	1,527	0,986	30,0
4	1675	6,288	1,103	74,1	6,94	60,0	230,3	270,2	349,0	6,542	4,560	3,824	1,488	1,507	0,988	30,0
5	1692	6,218	1,102	74,4	6,02	60,0	240,4	288,4	371,1	6,241	4,151	4,085	1,480	1,500	0,987	30,0
6	1703	6,190	1,104	73,9	5,42	60,0	250,5	304,3	390,8	6,060	3,943	4,323	1,493	1,518	0,984	30,0
7	1705	6,175	1,103	73,7	5,26	60,0	253,5	308,9	396,5	6,011	3,901	4,393	1,497	1,524	0,982	30,0

Starting Test

N.	VI Volt	AI Amp	Torque Nm	Vnom Volt	Anom Ampere	Tnom Nm	Ast Ampere	Tst Nm	Ast/Anom	Tst/Tnom	Capac. mF
1	228,5	18,650	3,104	207,1	7,839	6,556	16,903	2,550	2,156	0,389	30,0
2	228,5	18,650	3,104	210,1	7,543	6,492	17,148	2,624	2,274	0,404	30,0
3	228,5	18,650	3,104	220,2	6,934	6,382	17,979	2,885	2,593	0,452	30,0
4	228,5	18,650	3,104	230,3	6,542	6,288	18,801	3,155	2,874	0,502	30,0
5	228,5	18,650	3,104	240,4	6,241	6,218	19,627	3,438	3,145	0,553	30,0
6	228,5	18,650	3,104	250,5	6,060	6,190	20,445	3,731	3,374	0,603	30,0
7	228,5	18,650	3,104	253,5	6,011	6,175	20,692	3,821	3,442	0,619	30,0

Locked Rotor Test

N.	Freq Hz	VI Volt	Va Volt	Vc Volt	AI Amp	Am Amp	Aa Amp	Win kW	VA kVA	Cosfi	Capac. mF
1	60,0	228,5	59,8	265,8	18,650	20,090	2,930	3,380	4,261	0,793	30,0

