
takeUforward







Striver's DSA

Striver's DSA

System CS

Interview Prep

Striver's CP

Playlists Sheets

Design

Subjects Sheets

Sheet

February 26, 2023 Pattern


Pattern-5: Inverted **Right Pyramid**

Problem Statement: Given an integer N, print

the following pattern:

Here, N = 5.

Examples:





Latest Video on takeUforward



Latest Video on Striver

* * * *

* *

* *



Solution

Disclaimer: Don't jump directly to the solution, try it out yourself first.

Problem Link

Approach:

There are 4 general rules for solving a patternbased question :

- We always use nested loops for printing the patterns. For the outer loop, we count the number of lines/rows and loop for them.
- Next, for the inner loop, we focus on the number of columns and somehow connect them to the rows by forming a logic such that for each row we get the required number of columns to be printed.
- We print the '*' inside the inner loop.
- Observe symmetry in the pattern or check if a pattern is a combination of two or more similar patterns or not.

In this pattern, we run the outer loop for N times as we have to print N rows and since we have to print a right-angled triangle/pyramid

Recent Posts

Top LinkedList
Interview
Questions –
Structured Path
with Video
Solutions

Insert before the node with Value X of the Linked List

Insert before the Kth element of the Linked List

Insert at the head of a Linked List

Delete the node with value X of a Linked List

which must be inverted, the inner loop will run in decreasing order of stars, for eg: Row 1 (i=0) would contain N stars, Row 2 (i=1) would contain (N -1) stars and so on.

Code:

C++ Code

```
#include <bits/stdc++.h>
using namespace std;
void pattern5(int N)
    // This is the outer loop which will 1
    for (int i = 0; i < N; i++)
        // This is the inner loop which lo
       // no. of columns = (N - row index)
        for (int j =N; j>i; j--)
        {
            cout <<"* ";
        }
        // As soon as stars for each itera
        // next row and give a line break
        // would get printed in 1 line.
        cout << endl;</pre>
}
int main()
{
    // Here, we have taken the value of N
    // We can also take input from the use
    int N = 5;
    pattern5(N);
```

```
return 0;
}
```

Output

```
* * * * *
* * * *
* * *
```

Java Code

```
class Main {
   static void pattern5(int N)
{
    // This is the outer loop which will 1
   for (int i = 0; i < N; i++)
        // This is the inner loop which lo
       // no. of columns = (N - row index)
        for (int j = N; j > i; j--)
            System.out.print("* ");
        }
        // As soon as stars for each iter
        // next row and give a line break
        // would get printed in 1 line.
        System.out.println();
    }
}
    public static void main(String[] args)
        // Here, we have taken the value o
        // We can also take input from the
        int N = 5;
        pattern5(N);
```

}

Output

* * * *


* * * *

* * *

* *

*

Special thanks to **Priyanshi Goel** for contributing to this article on takeUforward. If you also wish to share your knowledge with the takeUforward fam, please check out this article. If you want to suggest any improvement/correction in this article please mail us at write4tuf@gmail.com



« Previous Post

Next Post »

Pattern – 6: Inverted Numbered Right Pyramid

Pattern – 4: Right-Angled Number Pyramid – II

Load Comments

takeUforward

The best place to learn data structures, algorithms, most asked coding interview questions, real interview experiences free of cost.

Follow Us













DSA Playlist	DSA Sheets	<u>Contribute</u>
Array Series	Striver's SDE Sheet	Write an Article
Tree Series	Striver's A2Z DSA Sheet	
Graph Series	SDE Core Sheet	
DP Series	Striver's CP Sheet	

Copyright © 2023 takeuforward | All rights reserved