

4K UHD

nextview®
the vision...

Smarter

GOOGLE TV

43"

With
AI
Assistant



Intelligent
Voice Remote



GT2NV43U4K11

Google LED TV

TECHNICAL SPECIFICATIONS

POWER

| | |
|-----------------------------|--|
| Power Requirement | 100-240VAC 50/60Hz |
| Power consumption (Standby) | ≤ 0.5W At 240VAC input & no load condition |
| Maximum Power Consumption | 75 watts |
| Current | ≤ 1.8 Amp |

ACCESSORIES

| | |
|---|-----|
| Remote controller (MAGIC & IR TYPE AS PER CUSTOMER SELECTION) | YES |
| Wall-mount Bracket | YES |
| User manual | YES |
| Stand | YES |

TV MEDIA FORMAT & INTERFACE TECHNOLOGY

| Type | Video Decoder | Resolution | Max fps | Max bitrate Mbps | Bit depth | Support |
|-------------|--|--------------------|---------|---------------------|-----------|---------|
| MPEG1/2/4 | MPEG1 | 1920x1080 | 60 | 50 | 8 | ✓ |
| | MPEG2 MP@HL | 1920x1080 | 60 | 50 | 8 | ✓ |
| | MPEG-4 SP@HL3.0 | 1920x1080 | 60 | 25 | 8 | ✓ |
| | MPEG-4 ASP@HL4.0 | 1920x1080 | 60 | 25 | 8 | ✓ |
| | MPEG-4 version3(MP43) | 1920x1080 | 60 | 25 | 8 | ✓ |
| | Microsoft ISO MPEC-4 version1 (MP4s) | 1920x1080 | 60 | 25 | 8 | ✓ |
| | Microsoft ISO MPEC-4 version1.1 (MPS2) | 1920x1080 | 60 | 25 | 8 | ✓ |
| H.264 | H.264 BP LV 4.0 | 2048x1080 | 60 | 125M | 8 | ✓ |
| | H.264 MP LV 4.0 | 2048x1080 | 60 | 125M | 8 | ✓ |
| | H.264 HP LV 4.0 | 2048x1080 | 60 | 125M | 8 | ✓ |
| | H.264 MP LV 5.1 | 4096x2160 | 30 | 125M | 8 | ✓ |
| | H.264 HP LV 5.1 | 4096X2160 | 30 | 125M | 8 | ✓ |
| | H.264 MVC(VERSION11) | 1920x1080 | 30 | 150M | 8 | ✓ |
| | H.265 Main Profile @ Level 4.1 | 2048x1080 | 60 | 125M | 8 | ✓ |
| H.265 | H.265 Main10 Profile @ Level 4.1 | 2048x1080 | 60 | 125M | 9.8/10 | ✓ |
| | H.265 Main Profile @ Level 5.0 | 4096x2160 | 30 | 125M | 8 | ✓ |
| | H.265 Main10 Profile @ Level 5.0 | 4096x2160 | 30 | 125M | 9.8/10 | ✓ |
| | H.265 Main Profile @ Level 5.1 | 4096X2160 | 60 | 150M | 8 | ✓ |
| | H.265 Main10 Profile @ Level 5.1 | 4096X2160 | 60 | 150M | 9.8/10 | ✓ |
| | H.265 Still Picture Profile | 8192x4096 | NA | NA | 8 | ✓ |
| Generic | Motion jpeg | 1920x1080 | 60 | 25M | 8 | ✓ |
| SHVC | Na | 3840x210+1920x1080 | 60 | 150M | 9.8/10 | ✓ |
| WMV* | Window Media Video v9 | 1920x1080 | 60 | 25M | 8 | ✓ |
| VC1* | VC-1 (SP/MP/AP) | 1920x1080 | 30 | 25M | 8 | ✓ |
| VP8 | VP8 | 1920x1080 | 30 | 25M | 8 | ✓ |
| VP9 | VP9 | 4096X2160 | 60 | 150M | 8/10 | ✓ |
| AVS | AVS jizhun Profile LV6.0 | 1920x1080 | 30 | 25M | 8 | ✓ |
| | AVS Plus | 1920x1080 | 30 | 25M | 8 | ✓ |
| Sorenson | Sorenson H.263 | 1920x1080 | 30 | 25M | 8 | ✓ |
| Motion jpeg | M-JPEG | 1920x1080 | 60 | 25M | 8 | ✓ |
| H.263 | H.263 v_MS/FW/FOUR CC/ H263 | 1920x1080 | 30 | 25M | 8 | ✓ |

AUDIO DECODER LIST

| | | |
|--------------------|---|-----|
| PN | Wav:PCM/ADPCM/A-LAW PCM /U-LAW PCM | YES |
| PCM | ADPCM IMA4 | |
| | WAV (192KHz) | |
| | AMR-NB, AMR-WR/AMR-WB+ | YES |
| AMR | DVD LPCM | YES |
| LPCM | MPEG1 LAYER1/2 | YES |
| MPEG 1/2/3 | MPEG1 LAYER1/2 (MPEG2) | YES |
| MPEG 1/2/3 | MPEG1 LAYER1/2 (MPEG2) | YES |
| | MP3 (MPEG 1 Layer 3) | YES |
| | MPEG-H 3D Audio | YES |
| AAC* | MPEG2 AAC (AAC-LC) | YES |
| | MPEG4 AAC-LC | YES |
| | MPEG4 HE- AAC V1/V2 | YES |
| | MPEG4 AAC-LC (RealAudio9) | YES |
| | MPEG4 HE-AAC-v2 (RealAudio10) | YES |
| Dolby AC3 (DD)* | AC3 | YES |
| | DOLBY Digital EX, DOLBY Digital Plus | YES |
| | dent: AC3 (RealAudio3) | YES |
| Dolby EAC3 (DDCO)* | DOLBY Digital Plus | YES |
| | DOLBY Digital Plus, DOLBY Digital lossless | YES |
| Dolby AC4* | DOLBY AC4 | YES |
| Dolby* | MS10 | YES |
| | MS11 | YES |
| | MS12 | YES |
| | MS12 for Dolby Atmos | YES |
| | MS12 for MAT (Metadata-enhanced Audio Transmission) | YES |
| DRA | DRA (licensee needed) | YES |
| MPEG-H | MPEG-H | YES |
| FLAC | FLAC | YES |
| | FLAC (96HZ) | YES |
| VORBIS | VORBIS | YES |

CONNECTIVITY

| | |
|-----------------|---|
| ETHERNET (RJ45) | 1 |
| YPBPR | 1 |
| AV in | 1 |
| ANTENNA | 1 |
| HDMI | 3 |
| Optical Out | 1 |
| USB | 2 |
| Earphone | 1 |

Image Decoder

| "File Extension" | Container | Data Type | Support |
|------------------|-----------|-------------|---------|
| *.jpg | JPEG | baseline | Yes |
| | | progressive | Yes |
| *.bmp | BMP | | Yes |
| *.png | PNG | | Yes |
| *.gif | GIF | static | Yes |
| | | animation | Yes |
| .mpo | MPO | 3d | Yes |
| .jps | JPEG | 3d baseline | Yes |
| .pns | PNG | 3d | Yes |

GT2NV43U4K11 Google LED TV

SMART TV FEATURES

| | |
|------------------|------------|
| PROCESSOR | A55*4 |
| GPU | G31*2 |
| RAM | 2 GB |
| ROM | 16 GB |
| OPERATING SYSTEM | Android 11 |

Display

| | |
|----------------|-------------------|
| Display size | 43 INCH (109 cm) |
| Aspect ratio | 16:9, Auto |
| Resolution | 3840 x 2160 |
| Contrast | 1200 : 1 |
| Viewing angle | 178°(H) X 178°(V) |
| Maximum colors | 1.07G(8 bit+FRC) |
| Response time | 8 ms |
| Luminance | 250 nits |

CHARACTERISTICS

| | |
|-------------------------|---|
| Dimensions LED Set | 1119X87X650mm |
| (LxWxH) with out Stand | |
| Dimensions LED Set | 1119X220X695mm |
| (LxWxH) with Stand | 1230X190X815mm |
| Box Dimension (LXWXH) | |
| Gross weight of product | 15 kg |
| Net Weight of product | 9 kg |
| PANEL | <p>Type TFT-LCD/LED</p> <p>Interface V-BY-ONE</p> |
| TV | <p>Receiving range 48.25MHz-863.25MHz</p> <p>Input Impedance 75Ω</p> <p>Video System DVB-T2/ATSC/DVB-T</p> <p>Sound System PAL/NTSC</p> |
| AV | <p>Color System PAL/NTSC</p> <p>Video Level 1.0VP-+10%</p> |
| HDMI | Format 480i,480p,576li,576p,720p,1080i,1080p,4k@60hz |
| AUDIO OUTPUT | <p>Max Output Power 2x8w @60hm/2x10w@80hm THD-10%</p> <p>Operating Frequency 2.4/5.0 GHz</p> <p>Communications IEEE 802.11a/b/g/n/ac+</p> <p>Standard</p> <p>Keyboard</p> |

Power,Menu,Source,CH+,CH-,VOL+,VOL-

TOLL FREE NO.
1800 2700 139

f/nextview > /nextview >> @/nextview_official
 support@nexttechgroup.com
 www.nexttechgroup.com



SCAN HERE FOR DETAILS & SOLUTIONS