
## Lab 20 cron job



apiVersion: argoproj.io/v1alpha1 kind: CronWorkflow metadata: name: test-cron-wf spec: schedule: "\* \* \* \* \*" concurrencyPolicy: "Replace" startingDeadlineSeconds: 0 workflowSpec: entrypoint: whalesay serviceAccountName: training shutdown: Terminate timezone: Asia/Kolkata templates: - name: whalesay container: image: alpine:3.6 command: ["sh", "-c"]

## Lab 2:

```
argo cron create argo-cronjob.yaml
argo cron list-n argo
argo cron get test-cron-wf-1-n argo
argo cron suspend test-cron-wf-1-n argo
argo cron list-n argo
```

## yaml file

```
apiVersion: argoproj.io/v1alpha1
kind: CronWorkflow
metadata:
name: test-cron-wf-1
namespace: argo
spec:
 schedule: "* * * * *"
 suspend: false
 concurrencyPolicy: Allow
 startingDeadlineSeconds: 0
 successfulJobsHistoryLimit: 3
 failedJobsHistoryLimit: 1
 workflowSpec:
  entrypoint: whalesay
  serviceAccountName: training
  shutdown: Terminate
  templates:
 - name: whalesay
   container:
    image: alpine:3.6
```

command: ["sh", "-c"]

args: ["date; sleep 90"]