



KALASALINGAM
ACADEMY OF RESEARCH AND EDUCATION
(DEEMED TO BE UNIVERSITY)

Under sec. 3 of UGC Act 1956. Accredited by NAAC with "A" Grade



JAVA PROGRAMMING

BY

DR. R. RAMALAKSHMI

DR. K. MURUGESWARI

MR. M. K. NAGARAJAN

MRS. A. M. GURUSIGAAMANI

Course Outline



CO 1. Understand the object oriented concepts using java



CO2. Apply fundamental programming concepts of Java to develop stand alone applications



CO 3. Solve Real World Problem through reusable and error free code.



CO 4. Design and develop distributed applications.



CO 5. Implement window based applications using event handling mechanisms

Course description

Java still has its importance and popularity in the software industry, in spite of recent development of several high level languages. It has an excellent support of high-level as well as low-level functionality, which makes it suitable for many applications. This course provides students with a comprehensive study of the Java programming language. Instead of Classroom lectures, practical classes stress the strengths of Java, which provide the students with the means of writing efficient, maintainable, and portable code. A course with mini project is one of the great learning opportunities to develop students in various aspects. This course will also help the students during their placement sittings, as most of the companies test proficiency in programming using Java.

UNIT I OOP IN JAVA & INHERITANCE

Object Oriented Programming Concepts - OOP in Java – Characteristics of Java – Fundamental Programming Structures in Java – Defining classes in Java – Comments, Data Types, Variables, Operators, Control Flow, Arrays - constructors, methods -access specifiers - static members – Packages- Inheritance – Super classes- sub classes –Protected members – constructors in sub classes- Strings.

UNIT II EXCEPTION HANDLING AND I/O

Exceptions - exception hierarchy - throwing and catching exceptions – built-in exceptions, creating own exceptions, Stack Trace Elements-Input / Output Basics – Streams – Byte streams and Character streams – Reading and Writing Console – Reading and Writing Files - abstract classes and methods - final methods and classes

UNIT III INTERFACES AND MULTITHREADING

Interfaces – defining an interface, implementing interface, differences between classes and interfaces - extending interfaces - Object cloning -inner classes- Differences between multi-threading and multitasking, thread life cycle, creating threads, synchronizing threads, Inter-thread communication, daemon threads - Generic Programming.

UNIT IV AWT AND EVENT DRIVEN PROGRAMMING

AWT Event Hierarchy- Components - Graphics programming – Applets-Frame – working with 2D shapes - Using color, fonts, and images - Basics of event handling - event handlers - adapter classes - actions - mouse events - Introduction to Swing – layout management - Swing Components – Windows – Menus – Dialog Boxes.

UNIT V NETWORKING AND JDBC

Networking Basics - The Networking Classes and Interfaces -TCP/IP Client Sockets URL TCP/IP Server Sockets – **Datagrams** - A Relational Database Overview - JDBC Introduction - JDBC Product Components - JDBC Architecture - Case studies.



Unit 1

Outcomes

Define classes.

Create objects using default and parameterized constructors.

Run stand alone applications using programming constructs of Java

Inherit the properties of an existing classes.

Hide the members of a class using access specifiers

Use predefined packages and create own package to group related classes.

Unit 1 Outline



Lesson 1. Object Oriented programming Concepts



Lesson 2. Fundamental programming Constructs in Java



Lesson 3. Access Specifiers



Lesson 4. Constructors



Lesson 5. Inheritance



Lesson 6. Packages

Briefs about OOP concepts, Characteristics of Java , Fundamental Programming Structures in Java , Defining classes in Java, Comments, Data Types, Variables, Operators, Control Flow, Arrays, constructors, methods, access specifiers, static members, Packages, Inheritance, Super classes, sub classes, Protected members, constructors in sub classes, Strings.

Course Progress (use before starting new lesson)

Lesson 1. Object Oriented programming Concepts

Lesson 2. Fundamental programming Constructs

Lesson 3. Access Specifiers

Lesson 4. Constructors

Lesson 5. Inheritance



Introduction

- Object-Oriented Programming is a programming paradigm that uses “Objects” and their interactions to design applications.
- It simplifies the software development and maintenance by providing some concepts.



Object Oriented Programming Concepts

- . Object
- . Class
- . Abstraction
- . Encapsulation
- . Inheritance
- . Polymorphism



Object

- . An object is defined as the Realworld Entity.
- . It consists of properties, tasks performed by objects.
- . It also defined as instance of a Class

Ex: Human

Properties ☐ Name, Colour, Height

Tasks Performed ☐ Walk(), Run(), Work(), Read()

Creating an object

Creating an object of the class is also called as instantiating an object. Here, we create an object called “s” and print the value of regno.

```
public class student1
{
    int regno=5;
    public static void main(String args[])
    {
        student1 s=new student1();
        System.out.println(s.regno);
    }
}
```

OUTPUT OF OBJECT CREATION

- Output

```
C:\Users\admin\Desktop\dhilipjava>javac student1.java
```

```
C:\Users\admin\Desktop\dhilipjava>java student1  
5
```


```
C:\Users\admin\Desktop\dhilipjava>_
```



Class

- ❖ Class is a collection of data members and member functions.
- ❖ It is called as the blueprint that defines the variables and methods.
- ❖ When creating instance of a class the system allocates enough memory for the object.

Java Class & Objects



source:techvidvan.com

Syntax of Class:

```
class class_name
{
    type instance_variable;
    type methodname1(parameter_list)
    {
        // body of method
    }
}
```

Example of a Class


```
Class Student
{
    int regno,marks;
    char name;
    void totalmarks()
    {
        .....
    }
}
```

Abstraction

It shows only essential things and hides unnecessary information from the user. It helps the user in reducing programming complexity. Two way of abstraction are as follows

- ❖ Data Abstraction
- ❖ Process Abstraction

Abstraction



Source: data-flair.training.com

Example of Abstraction

```
abstract class Bike
{
    abstract void run();
}
class Honda4 extends Bike
{
    void run()
    {
        System.out.println("running safely");
    }
    public static void main(String args[])
    {
        Bike obj = new Honda4();
        obj.run();
    }
}
```

Output of Abstraction

```
C:\Users\admin\Desktop\dhilipjava>javac Honda4.java
```

```
C:\Users\admin\Desktop\dhilipjava>java Honda4  
running safely
```

```
C:\Users\admin\Desktop\dhilipjava>
```



Encapsulation

- ❖ It is a mechanism of wrapping data(variable) and code acting on the data(methods) together as a single unit.
- ❖ It binds together the code and the data it manipulates and keeps both safe from outside.
- ❖ In Java, the **basis of encapsulation is the class.**
- ❖ A **class** defines the structure and behavior (data and code) that will be shared by a set of objects.

Encapsulation Figure




Fig: Encapsulation

Image src:medium.com



Imagesrc:codeeasy.net

Program for Encapsulation

```
public class RunEncap
{
    public static void main(String args[])
    {
        EncapTest encap = new EncapTest();
        encap.setName("James");
        encap.setAge(20);
        encap.setIdNum("12343ms");

        System.out.print("Name : " + encap.getName() + " Age : " + encap.getAge());
    }
}
```

Output of Encapsulation

```
C:\Users\admin\Desktop\dhilipjava>javac EncapTest.java  
C:\Users\admin\Desktop\dhilipjava>javac RunEncap.java  
C:\Users\admin\Desktop\dhilipjava>java RunEncap  
Name : James Age : 20  
C:\Users\admin\Desktop\dhilipjava>
```

Inheritance

- It is the process of deriving a class from the base class.
- For example, one person is getting the behavior of his parent is an example of inheritance.
- If one object acquires the properties of another object.
- This is important because it supports the concept of hierarchical classification.
- Types of inheritance are as follows
 - Single Inheritance
 - Multiple Inheritance
 - Multilevel Inheritance
 - Hierarchal Inheritance
 - Hybrid Inheritance

Program for Inheritance

```
class Doctor
{
    void Doctor_Details()
    {
        System.out.println("Doctor Details...");
    }
}
class Surgeon extends Doctor
{
    void Surgeon_Details()
    {
        System.out.println("Surgen Detail...");
    }
}
```

```
public class Hospital
{
    public static void main(String args[])
    {
        Surgeon s = new Surgeon();
        s.Doctor_Details();
        s.Surgeon_Details();
    }
}
```


Output of Inheritance

```
NAME : DINESH NGC : 20
C:\Users\admin\Desktop\dhilipjava>javac Hospital.java

C:\Users\admin\Desktop\dhilipjava>java Hospital
Doctor Details...
Surgen Detail...

C:\Users\admin\Desktop\dhilipjava>_
```



Polymorphism

- Polymorphism “Poly” means many “morph” means form.
- It is one of the feature in oops that performs single action in different ways. For example class vehicle has method cars().
- In that cars are of different types XUV, ZEDON, HATCHBACK etc
- Two types of polymorphism are there. They are as follows
 - Compile time polymorphism (Static Binding)
 - Run time polymorphism (Dynamic Binding)
- Another one good example is that a person at the same time can have different characteristics. A man act as a father, son, husband and an employee.

Polymorphism



Imagesrc:csharp-station.com

Program for Polymorphism

```
class MultiplyFun
{
    static int Multiply(int a, int b)
    {
        return a * b;
    }
    static double Multiply(double a, double b)
    {
        return a * b;
    }
}
class Main5
{
    public static void main(String[] args)
    {
        System.out.println(MultiplyFun.Multiply(2, 4));
        System.out.println(MultiplyFun.Multiply(5.5, 6.3));
    }
}
```

Output of Polymorphism

```
C:\Users\admin\Desktop\dhilipjava>javac Main5.java  
  
C:\Users\admin\Desktop\dhilipjava>java Main5  
8  
34.65
```



What is JAVA

- ❖ Java is a high level, class-based object-oriented programming language.
- ❖ It is a high-level programming language which right once and run anywhere.
- ❖ When a programmer writes a java application, then compiled code and he can run that on most operating system (OS) like windows, Linux and MAC OS.
- ❖ It is used to build large enterprise class application.
- ❖ It is used for building large scale system. It is a software only platform running on top of hardware-based platform.
 - ❖ Java Virtual Machine (JVM)
 - ❖ Java Application Programming Interface (Java API)



Characteristics of JAVA

SIMPLE

It is easy for specialized programmer to learn and use.

SECURE

It is providing security while creating internet application

PORTABLE

It can be executed in any environment where java should be there

OBJECT ORIENTED

It is clean, usable, pragmatic approach to objects, not restricted by the need for compatibility with other languages.



Characteristics of JAVA

ROBUST

Java encourage error free programming by doing runtime checking

MULTITHREADED

Java support multithreaded programming

ARCHITECTURAL NEUTRAL

It is not knotted to a specific machine or operating system architecture.

INTERPRETED

Using java bytecode, it supports cross platform code



Characteristics of JAVA

- **HIGH PERFORMANCE**

The Java enables high performance using just in time compiler

- **DISTRIBUTED**

Java was designed for distributed environment of the Internet

- **DYNAMIC**

Java is more dynamic than c and c++, as it is designed to adapt the evolving environment.

Java programs carry substantial amounts of run-time type information that is used to verify and resolve accesses to objects at run time.



OOP in JAVA

Java defines eight simple data types:

- 1) byte-8-bit integer type
- 2) short-16-bit integer type
- 3) int-32-bit integer type
- 4) long-64-bit integer type
- 5) float-32-bit floating-point type
- 6) double-64-bit floating-point type
- 7) char-symbols in a character set
- 8) boolean-logical values

Data Types

DATA TYPES	RANGE	EXAMPLE	USAGE
byte-8-bit integer type	-128 TO 127	Byte b=-15	When working with data streams
short-16-bit integer type	-32768 to 32767	short c= 1000	Least used simple type
int-32-bit integer type	-2147486648 to 2147483647	int b=-600000	It is common one, used to control loops and to index array
long:64-bit integer type	-9223372036854775808 to 9223372036854775807.	long d = 506000000000000078;	When int type is not large enough to hold values

Data Types

float-32-bit floating-point type	$1.4e^{-045}$ to $3.4e^{+038}$	Float d=3.5	Fractional part is used and large degree of accuracy is not needed
double-64-bit floating-point type	$4.9e^{-324}$ to $1.8e^{+308}$	double pi=3.14	Handling large valued number
char-symbols in a character set	0 to 65536	Char a='a'	It is used to represent both ASCII and Unicode character set
Boolean-logical values	True or false	boolean b=(2<3)	It returns relational operators such as 1<2



Variables

It uses variable to store data.

TO allocate memory JVM requires to specify the datatype of the variable.

To associate an identifier of the variable.

It is assigned with initial value.

All are processed as a part of variable declaration.

Variables

declaration	It is used to assign the type of variables
initialization	How to give starting value of variable
scope	How the variables are visible to other parts of the program
lifetime	How the variable is created used and destroyed
type conversion	How automatic type conversion is handled in java
type casting	How variable type is narrowed down



Variable Declaration With Example

Syntax

`datatype identifier=value;`

Example

`int a=20;`

`float i=20.5;`

`double pi=3.14;`

Arrays

- ❖ Array is a collection of related data of similar type.
- ❖ The values can be stored in large amount based on the desire of the user.
- ❖ Arrays can be declared, created, initialized and used.
- ❖ Array is of two types as are shown below
 - One dimensional array
 - Multi dimensional array



Array Initialization

Arrays can be initialized when they are declared:

```
int monthDays[] = {31,28,31,30,31,30,31,31,30,31,30,31};
```

Note:

There is no need to use the new operator

There array is created large enough to hold all specified elements

Array Syntax

Two types of declaring array are as follows

```
type array_variable[];
```

```
type [] array_varriable;
```

After creating an array it does not actually exist. In order to create an array “new” operator should be used.

- `array_variable = new type[size]`

This create new variable to hold size elements of type, which reference will be kept in array variable. Here array variable index starts with zero. Java run time system makes sure that all array indexes are in correct range otherwise it leads to runtime error



Single Dimensional array

Example

```
int days[]={1,2,3,4,5,6,};
```

This is direct way of giving values to array variable. And in this no need to specify the size of the array as we will do in c or c++.

In array concept, if more than one set bracket is there we will call it as multidimensional array. It is also called as array of array.



Multidimensional Array

`int array[][]; //Declaration`

`int array=new int[4][5]; //Creation`

This represents 4 rows and 5 columns.

`int array[][]={{2,3,4},{5,6,7}}// initialization`

This array represents 2 rows and 3 columns



Operator Types

Java operators are used to build value expression.

The listed below are some of the operators used in java

- Arithmetic Operator
- Logical Operator
- Assignment Operator
- Relational Operator
- Bitwise Operator

Arithmetic Operator

Operator	Purpose	a=10,b=3	a=12.5,b=2.0	a='P' b='T'
+	Addition	13 (a+b)	14.5	164
-	Subtraction	7 (a-b)	10.5	-4
*	Multiplication	30 (a*b)	25.0	6720
/	Division	3 (a/b)	6.25	0
%	Modulo Division	1 (a%b)	----	80

Example

a=5 and b=-2 then a%b=1

a=-5 and b=2 then a%b=-1



Logical Operators

LOGICAL OPERATORS :(also called logical connectives)

1. && (logical and)
2. || (logical or)

These 2 operators are used to combine the individual logical expressions into more complex conditions

Results of logical and (&&)

- The result of the logical and (&&) operation will be true only if both operands are true.

Expression 1	Expression2	Result
1	1	1
1	0	0
0	1	0
0	0	0

Results of logical or (||)

- The result of the logical or (||) operation will be true if either operand is true.

Expression 1	Expression 2	Result
1	1	1
1	0	1
0	1	1
0	0	0



Logical Not (!)

- The logical not (!) operator requires only one operand which represents a logical value 0 or non zero.
- The **result** of the operation is **non zero** if and only if the operand is zero.
- **Example**
 - $i=7$, and $!(i>6)$ then result is 0.

ASSIGNMENT OPERATORS:

- ✓ Assignment operators are used to assign a value in a particular variable.
- ✓ The most commonly used assignment operator is '='

Assignment operator form

Identifier= expression

- ✓ Identifier may be variable
- ✓ Expression may be constant, variable, or a more complex expression
- ✓ Assignment expressions are referred to as an assignment statement.
- ✓ Ex: a=5;

Multiple assignment

- Multiple assignment of the form:
- **Identifier1 =Identifier2=expression**
- Is equivalent to
- **Identifier1 = (Identifier2=expression)**
- **Example**
- **a=b=5;** It means first 5 is assigned to 'b' and then the value of b (that is 5) is assigned to 'a'.

SHORTHAND ASSIGNMENT

SHORTHAND ASSIGNMENT OPERATORS:

Syntax:

Var operator=exp;

1) += 2) -= 3) *=, 4) /=, 5) %= these are the shorthand operators.

Example

var +=exp is equivalent to var=var+exp

var-=exp is equivalent to var=var-exp

For Ex:

If i=5,j=7

j*=(i-3)

j=j*(i-3) then j=7*(5-3) then j=7*2 finally j=14.

i%=j

i=i%j then i=5%7 then i=5



RELATIONAL OPERATOR:

There are 4 relational operators

- ❖ $<$ (Less than)
- ❖ $>$ (Greater than)
- ❖ $<=$ (Less than or equal to)
- ❖ $>=$ (Greater than or equal to)

There are 2 Equality operators

- ❖ $==$ (equal to)
- ❖ $!=$ (not equal to)

➤ These 6 operators are used to form logical expressions, which represent conditions that are either true or false.

RELATIONAL OPERATOR:

- The resulting expressions will be of type integer, since true is represented by integer value 1 and false is represented by the value 0.

Example

$i=1, j=2, k=3$

Expression	Result
$i < j$	1
$(i+j) \geq k$	1
$k \neq 3$	0

BITWISE OPERATORS:

Bitwise operator used for manipulation of data at bit level.

OPERATOR	MEANING
&	Bitwise AND
	Bitwise OR
^	Bitwise Exclusive OR
<<	Shift left
>>	Shift Right
~	One's complement

Expression

The data type of the value returned by an expression depends on the elements used in the expression. The expression

- `number = 0;`

which returns an int because the assignment operator returns a value of the same data type as its left-hand operand; in this case, number is an int.

In Java, compound expressions also be used. The data type required by one part of the expression matches the data type of the other. The example of a compound expression is as follows

- `1 * 2 * 3`

Control statements

- ❖ A program is a sequence of instructions.
- ❖ Java control statements cause the flow of execution to advance and branch based on the changes to the state of the program.
- ❖ Each instruction is executed only once in the order it appears.
- ❖ Control statements are divided into three groups:
 1. Selection statements
 2. Iteration statements
 3. Jump statements



Selection Statements

One of the several possible branches will then be carried out, depending on the outcome of the logical test. This is known as selection statement

- if
- if-else
- nested if-else
- switch

if Statement

- In if statement, only one condition is checked.
- If the condition is true the statement is executed. If the condition is false it will exit out of the loop

```
class IfStatement
{
    public static void main(String[] args)
    {
        int number = 10;
        // checks if number is greater than 0
        if (number > 0)
        {
            System.out.println("The number is positive.");
        }
        System.out.println("Statement outside if block");
    }
}
```

Output

```
C:\Users\admin\Desktop\dhilipjava>javac IfStatement.java
```

```
C:\Users\admin\Desktop\dhilipjava>java IfStatement
```

```
The number is positive.
```

```
Statement outside if block
```

If else Statement

- In this if else statement, if the condition is true then, the true statement was executed or else the else part is executed.
- Or else the statement outside the block was executed.

```
class ifelsestmt
{
    public static void main(String[] args)
    {
        int number = 10;
        // checks if number is greater than 0
        if (number > 0)
        {
            System.out.println("The number is positive.");
        }
        // execute this block
        // if number is not greater than 0
        else
        {
            System.out.println("The number is not positive.");
        }
        System.out.println("Statement outside if...else block");
    }
}
```

Output

```
C:\Users\admin\Desktop\dhilipjava>javac ifelsestmt.java  
  
C:\Users\admin\Desktop\dhilipjava>java ifelsestmt  
The number is positive.  
Statement outside if...else block
```

Switch Statement

- The switch statement allows us to execute a block of code among many alternatives.

```
class switchdemo
{
    public static void main(String[] args)
    {
        int number = 44;
        String size;
        // switch statement to check size
        switch (number)
        {
            case 29:
                size = "Small";
                break;
            case 42:
                size = "Medium";
                break;
            // match the value of week
            case 44:
                size = "Large";
                break;
            // ...
        }
    }
}
```

```
        case 48:
            size = "Extra Large";
            break;
    }
    System.out.println("Size: " + size);
}
```


Output

```
C:\Users\admin\Desktop\dhilipjava>javac switchdemo.java
```

```
C:\Users\admin\Desktop\dhilipjava>java switchdemo
```

```
Size: Large
```

ITERATION STATEMENT

During looping, a set of statements are executed until some conditions for termination of the loop is encountered.

A program loop therefore consists of two segments one known as body of the loop and other is the control statement.

The control statement tests certain conditions and then directs the repeated execution of the statements contained in the body of the loop.

Java provides three iteration statements

- while
- do -while
- for



Jump statements

It enables transfer of control to other parts of the program. In java we are having three types of jump statements

- break
- continue
- return



TYPE CONVERSION

- Conversion in java is done in two ways
 1. Implicit type conversion- Carried out by compiler automatically
 2. Explicit type conversion- Carried out by program using casting
- Size Direction of Data Type
 - - Widening Type Conversion (Casting down)
Smaller Data Type -> Larger Data Type
 - - Narrowing Type Conversion (Casting up)
Larger Data Type -> Smaller Data Type



TYPE CASTING

It is the of assigning a primitive data type value to another data type value. It is also a casting of a class or interface into another class or interface.

Syntax

(target type) values

Example


- integer value will be reduced module bytes range:
- int a;
- byte a = (byte) i;
- floating-point value will be truncated to integer value:
 - float a;
 - int b = (int) a;



How to download and install Java for 64-bit machine

The following steps can be followed in order to download and install java. All the steps are described below has been performed on the Windows 10 operating system, but the procedure is quite similar to other operating systems as well.

Step 1: Open <https://www.oracle.com/java/technologies/javase-downloads.html> url in the browser and it will navigate to the official Oracle Java downloads page.

The screenshot shows the Oracle Java SE Downloads page. The header includes the Oracle logo, a search bar with the text 'Ask "Financials"', and links for 'View Accounts' and 'Try Oracle Cloud Free Tier'. The main heading is 'Java SE Downloads' with the subtitle 'Java Platform, Standard Edition'. Under 'Java SE 14', it states 'Java SE 14.0.1 is the latest release for the Java SE Platform'. A list of links on the left includes 'Documentation', 'Installation Instructions', 'Release Notes', 'Oracle License' (with sub-links for 'Binary License' and 'Documentation License'), 'Java SE Licensing Information User Manual' (with a sub-link for 'Includes Third Party Licenses'), 'Certified System Configurations', and 'Readme'. On the right, under 'Oracle JDK', there are two download links: 'JDK Download' and 'Documentation Download', each with a download icon. At the bottom, there is a link for 'Looking for Oracle OpenJDK builds?'.

Step 2: Now, scroll to the version of the Java which we want to download and click on **JDK Download** option as shown below:

A screenshot of the Oracle Java SE Downloads page. The page has a dark header with a search bar containing 'Ask "Financials"', a 'View Accounts' button, and a 'Try Oracle Cloud Free Tier' button. The main content area is titled 'Java SE Downloads' and 'Java Platform, Standard Edition'. On the left, there is a list of links for 'Java SE 14', which is highlighted with a red box. Below this list, there is a section for 'Oracle JDK' with two download options: 'JDK Download' and 'Documentation Download', both highlighted with green boxes. At the bottom, there is a link for 'Looking for Oracle OpenJDK builds?'.

Java SE Downloads

Java Platform, Standard Edition

Java SE 14

Java SE 14.0.1 is the latest release for the Java SE Platform

- Documentation
- Installation Instructions
- Release Notes
- Oracle License
 - Binary License
 - Documentation License
- Java SE Licensing Information User Manual
 - Includes Third Party Licenses
- Certified System Configurations
- Readme


Oracle JDK

[JDK Download](#)

[Documentation Download](#)


Looking for Oracle OpenJDK builds?

Step 3: Scroll down to the page and click on the download button option suitable for your computer Operating system. But for a 64-bit machine, choose the software name ending with **x64**.

The screenshot shows the Oracle Java download page. At the top, there is a search bar with the text 'Ask "Can I take advantage of the cloud in my own data center?"', a 'View Accounts' button, and a 'Try Oracle Cloud Free Tier' button. Below this is a table of download links for JDK 8u251. The table has three columns: the operating system and architecture, the file size, and the download link. The 'Windows x64' row is highlighted with a red circle around the OS name and a green circle around the download link. An upward arrow icon is located to the left of the 'Windows x64' row.

macOS x64	254.78 MB	 jdk-8u251-macosx-x64.dmg
Solaris SPARC 64-bit (SVR4 package)	125.19 MB	 jdk-8u251-solaris-sparcv9.tar.Z
Solaris SPARC 64-bit	88.16 MB	 jdk-8u251-solaris-sparcv9.tar.gz
Solaris x64 (SVR4 package)	133.64 MB	 jdk-8u251-solaris-x64.tar.Z
Solaris x64	91.9 MB	 jdk-8u251-solaris-x64.tar.gz
Windows x86	201.17 MB	 jdk-8u251-windows-i586.exe
Windows x64	211.54 MB	 jdk-8u251-windows-x64.exe

After clicking on the download button, a popup will appear which says that we have to accept **Oracle Technology Network License Agreement for Oracle Java SE** in order to download this software. Therefore, click on the checkbox and then proceed to download as shown below:

The screenshot shows the Oracle Java SE download interface. On the left, there is a list of operating systems: Solaris SPARC 64-bit (88.16 MB), Solaris x64 (SVR4 package), Solaris x64, Windows x86, and Windows x64. On the right, there is a list of download links: jdk-8u251-solaris-sparcv9.tar.gz, is-x64.tar.Z, is-x64.tar.gz, ows-i586.exe, and ows-x64.exe. A modal dialog box is centered on the screen, titled 'You must accept the Oracle Technology Network License Agreement for Oracle Java SE to download this software.' It contains a checkbox with a green checkmark, followed by the text 'I reviewed and accept the Oracle Technology Network License Agreement for Oracle Java SE'. Below this, it says 'You will be redirected to the login screen in order to download the file.' At the bottom of the dialog, there is a green button labeled 'Download jdk-8u251-windows-x64.exe' with a download icon. The checkbox and the download button are highlighted with red circles and a red rectangle, respectively.


Step 4: We will now be navigated to **Oracle Login page**. We need to login to the account. As soon we log in, our download will start instantly as shown below:



Step 5: After the downloading procedure is complete, we need to run the installer. Once Java installation wizard opens, click on the **Next** button as shown below:




Step 6: Again click on the **Next** button if we wish to install Java development kit in the default directory(encircled with green color), or we can change this directory by clicking on **Change** button.



Step 7: The installation will begin as shown below:




Step 8: Now, it will ask for the installation directory for **JRE(Java Runtime Environment)**. Again we can continue with the default directory or change it accordingly.



Step 9: The Java installation will be successfully completed as shown below:



Step 10: Finally, we can click on the **Close** button after the confirmation window appears that the Java is installed.



Simple Java Program

```
class myfirstjavapgm
{
    public static void main(String[] args)
    {
        System.out.println("First Java program.");
    }
}
```

Type the above program in notepad and save using the class name.java.This file is saved as MyFirstJavaProgram.java



Compiling and running a java program

- Compiling and running a java program is very easy after JDK installation. Following are the steps
- Open a command prompt window and go to the directory where you saved the java program (myfirstjavapgm.java). Assume it in Desktop:\dhilipjava.
- Next, set path for your jdk file. Ex: C:\Users\admin\Desktop\dhilipjava
- Type 'javac myfirstjavapgm.java' and press enter to compile your code. If there are no errors in your code, the command prompt will take you to the next line (Assumption: The path variable is set).
- Now, type ' java myfirstjavapgm ' to run your program.
- You will be able to see the result printed on the window.

Output Screen

```
C:\Users\admin\Desktop\dhilipjava>javac myfirstjavapgm.java  
  
C:\Users\admin\Desktop\dhilipjava>java myfirstjavapgm  
First Java program.
```



JAVA Working Environment

Three Components

- JDK-Java Development Kit
- JVM-Java Virtual Machine
- JRE-Java Runtime Environment



JDK


The Java Development Kit (JDK) is primary components.

It physically exists.

It is collection of programming tools and JRE, JVM.

Writing Java applets and applications need development tools like JDK.

JDK Architecture



Source:ictacademy.com



JRE

JRE is an acronym for Java Runtime Environment.


It is also written as Java RTE.

The Java Runtime Environment is a set of software tools.

It physically exists.

It contains a set of libraries + other files that JVM uses at runtime.

JRE Architecture



JRE - Java Runtime Environment


Source: studytonight.com



JVM

- JVM is a engine that provides runtime environment to drive the Java Code or Applications.
- It converts Java byte code into machine languages.
- Java compiler produces code for a virtual machine known as Java Virtual Machine.

JVM Architecture



Source:guru99.com



Uses of JDK,JRE,JVM

- The Java Virtual Machine is built right into your Java software download and helps run Java applications.
- The JRE allows applets written in the Java programming language to run inside various browsers.

Difference between JDK,JRE,JVM

JDK	JRE	JVM
It stands for Java Development Kit.	It stands for Java Runtime Environment	It stands for Java Virtual Machine.
It is the tool necessary to compile, document and package java programs	JRE refers to a runtime environment in which Java bytecode can be executed.	It is an abstract machine. It is a specification that provides a runtime environment in which Java bytecode can be executed.
It contains JRE+development tools.	It's an implementation of the JVM which physical exists.	JVM follow three notations: Specification, Implementation and Runtime Instance

Topic 1

OOP Concepts

Topic 2

Characteristics of JAVA

Topic 3

OOP in JAVA

Topic 4

JAVA Working Environment

First Lesson Summary

Learned about OOP concepts, Characteristics of JAVA, OOP in JAVA, JAVA Working Environment

Fundamental Programming Constructs

Lesson 1. Object Oriented programming Concepts

Lesson 2. Fundamental programming Constructs

Lesson 3. Access Specifiers


Lesson 4. Constructors

Lesson 5. Inheritance

Introduction



- A program is a sequence of instructions that a computer can execute to perform some task. There are two basic blocks of programming: data and instructions and to work with data, you need to understand variable and data types; to work with instructions, you need to understand control structures and subroutines (methods).



Structure of Java Program

Structure of Java Program

- Java is called as Platform independent, Object oriented, and secure programming language.
- Using the java programming language, we can develop a wide variety of applications. So we want to understand the basic structure of java program in detail.

package details	→	<code>import java.io.*</code>
<code>class className</code>	→	<code>class Sum</code>
{		
Data members;	→	<code>int a, b, c;</code>
user_defined method;	→	<code>void display();</code>
<code>public static void main(String args[])</code>		
{		
Block of Statements;	→	<code>System.out.println("Hello Java !");</code>
}		
}		



Structure of Java Program

- . A package is a collection of classes, interfaces and sub-packages. A sub package contains collection of classes, interfaces and sub-sub packages etc. `java.lang.*`; package is imported by default and this package is known as default package.
- . Class is keyword used for developing user defined data type and every java program must start with a concept of class. "ClassName" represent a java valid variable name treated as a name of the class each and every class name in java is treated as user-defined data type.
- . Data member represents either instance or static they will be selected based on the name of the class.


Structure of Java Program

- Each and every java program starts execution from the main() method. And hence main() method is known as program driver.
- Since main() method of java is not returning any value and hence its return type must be void.
- Since main() method of java executes only once throughout the java program execution and hence its nature must be static.
- Since main() method must be accessed by every java programmer and hence whose access specifier must be public.
- Each and every main() method of java must take array of objects of String.
- Block of statements represents set of executable statements which are in term calling user-defined methods are containing business-logic.
- The file naming convention in the java programming is that which-ever class is containing main() method, that class name must be given as a file name with an extension .java.

Structure of Java Program



Java is Compiled and Interpreted



Classes in Java



- . class defines a new data type.
- . Once defined, this new type can be used to create objects of that type.
- . Class is a template for an object, and an object is an instance of a class.
- . A class consists of Data members and methods.
- . The primary purpose of a class is to hold data/information. This is achieved with attributes which are also known as data members.
- . The member functions determine the behavior of the class, i.e. provide a definition for supporting various operations on data held in the form of an object.

Declaring Objects

- When you create a class, you are creating a new data type. You can use this type to declare objects of that type.
- Obtaining objects of a class is a two-step process. First, you must declare a variable of the class type. This variable does not define an object. Instead, it is simply a variable that can refer to an object. Second, you must acquire an actual, physical copy of the object and assign it to that variable. You can do this using the new operator. The new operator dynamically allocates (that is, allocates at run time) memory for an object and returns a reference to it. This reference is, more or less, the address in memory of the object allocated by new. This reference is then stored in the variable. Thus, in Java, all class objects must be dynamically allocated.

```
classname class -var = new classname ( );
```

Java Comments

- . Comments can be used to explain Java code, and to make it more readable. It can also be used to prevent execution when testing alternative code.
- . Single-line comments start with two forward slashes (//).
- . Any text between // and the end of the line is ignored by Java (will not be executed).
- . This example uses a single-line comment before a line of code:

```
// This is a comment  
System.out.println("Hello world")  
/* This is a Simple Java Program  
This is a comment */
```

Data Types



Characters

The char data type is used to store a **single** character. The character must be surrounded by single quotes, like 'A' or 'c'

```
public class Main {  
    public static void main(String[] args) {  
        char myGrade = 'B';  
        System.out.println(myGrade);  
    }  
}
```


Data Types



Strings

- The String data type is used to store a sequence of characters (text). String values must be surrounded by double quotes.

```
public class Main {  
    public static void main(String[] args) {  
        String greeting = "Hello World";  
        System.out.println(greeting);  
    }  
}
```

Variables

- Variables are symbolic names for memory storage.
- Like most compiled languages, variables must be declared before they can be used.
- Variables are a symbolic name given to a memory location.
- All variables have a type which is enforced by the compiler
- The general form of a variable declaration is:


`type variable-name [= value][,variable-name[= value]];`

```
int total;  
float xValue  
= 0.0;  
boolean  
isFinished;
```

`String name;`

Arrays

An *array* is a container object that holds a fixed number of values of a single type. The length of an array is established when the array is created. After creation, its length is fixed. You have seen an example of arrays already, in the main method of the "Hello World!" application.



Each item in an array is called an *element*, and each element is accessed by its numerical *index*. As shown in the preceding illustration, numbering begins with 0. The 9th element, for example, would therefore be accessed at index 8.

Arrays – Example Program

```
class ArrayDemo {  
    public static void main(String[] args) {  
        // declares an array of integers  
  
        int[] anArray; // allocates memory for 10 integers anArray = new int[10]; // initialize first element anArray[0] = 100;  
        // initialize second element anArray[1] = 200; // and so forth  
  
        anArray[2] = 300;  
        anArray[3] = 400;  
        anArray[4] = 500;  
        anArray[5] = 600;  
        anArray[6] = 700;  
        anArray[7] = 800;  
        anArray[8] = 900;  
        anArray[9] = 1000;
```

```
        System.out.println("Element at index 0: " + anArray[0]);
```

Array Declaration & Initialization

The following code snippet shows the two dimensional array declaration in Java Programming Language:

```
Data_Type[][] Array_Name;
```

Data_type: It decides the type of elements it will accept. For example, If we want to store integer values, then the Data Type will be declared as int. If we want to store Float values, then the Data Type will be float.

Array_Name: This is the name to give it to this Java two dimensional array. For example, Car, students, age, marks, department, employees, etc.

```
for ( int i=0; i<n ;i++)  
{  
    for (int j=0; j<n; j++)  
    {  
        a[i][j] = 0;  
    }  
}
```

Array Declaration & Initialization

In the Java programming language, a multidimensional array is an array whose components are themselves arrays. This is unlike arrays in C or Fortran. A consequence of this is that the rows are allowed to vary in length, as shown in the following [MultiDimArrayDemo](#) program:

```
class MultiDimArrayDemo
{
    public static void main(String[] args)
    {
        String[][] names = { {"Mr. ", "Mrs. ", "Ms. "}, {"Smith", "Jones"} };
        // Mr. Smith
        System.out.println(names[0][0] + names[1][0]);
        // Ms. Jones
        System.out.println(names[0][2] + names[1][1]); } }
```

The output from this program is:

Mr. Smith Ms. Jones

Topic 1
Introduction - Structure of Java Program

Topic 2
Defining Class

Topic 2
Data Types

Topic 3
Variables

Topic 4
Operators

Topic 4
Control Flow

Topic 5
Arrays

Summary

LEARN FUNDAMENTAL PROGRAMMING
STRUCTURE FOR WRITING SIMPLE STAND ALONE
APPLICATION USING CONTROL, LOOPING AND
ARRAYS.

Access Specifiers



Lesson 1. Object Oriented programming Concepts

Lesson 2. Fundamental Programming Constructs

Lesson 3: Access Specifiers

Lesson 4. Constructors

Lesson 5. Inheritance

Access Specifiers

There are two types of modifiers in Java:

- access modifiers
- non-access modifiers.

The access modifiers in Java specifies the accessibility or scope of a field, method, constructor, or class. The different types of access specifiers are as follows


private: When a member of a class is specified as private, then that member can only be accessed by other members of its class.

public: When a member of a class is modified by public, then that member can be accessed by any other code.

protected: applies only when inheritance is involved.

default: same as specifying public.

Access Specifiers



Access Specifiers



	default	private	protected	public
Same Class	Yes	Yes	Yes	Yes
Same package subclass	Yes	No	Yes	Yes
Same package non-subclass	Yes	No	Yes	Yes
Different package subclass	No	No	Yes	Yes
Different package non-subclass	No	No	No	Yes

Private



```
class A
{
    private int data=40;
    private void msg()
    {
        System.out.println("Hello java");
    }
}
public class Simple1
{
    public static void main(String args[])
    {
        A obj=new A();
        System.out.println(obj.data); //Compile Time Error
        obj.msg(); //Compile Time Error
    }
}
```

Output



```
C:\Users\admin\Desktop\dhilipjava>javac Simple1.java
Simple1.java:14: error: data has private access in A
        System.out.println(obj.data); //Compile Time Error
                              ^
Simple1.java:15: error: msg() has private access in A
        obj.msg(); //Compile Time Error
              ^
2 errors
```

Public



Public members of any class are accessible anywhere in the program inside the same class and outside of class, within the same package and outside of the package. The other name of public is universal access specifier

```
class Hello
{
    public int a=20;
    public void show()
    {
        System.out.println("Hello java");
    }
}
public class Demo
{
    public static void main(String args[])
    {
        Hello obj=new Hello();
        System.out.println(obj.a);
        obj.show();
    }
}
```

output



```
C:\Users\admin\Desktop\dhilipjava>javac Demo.java
```

```
C:\Users\admin\Desktop\dhilipjava>java Demo
```

```
20
```

```
Hello java
```

Protected:



Protected members of the class are accessible within the same class and another class of the same package and also accessible in inherited class of another package. Protected are also called derived level access modifiers.

```
package pack1;  
public class B1  
{  
    protected void show()  
    {  
        System.out.println("Hello Java");  
    }  
}
```


Protected member Access Example

```
public class Shape
{
    protected double height; // To hold height.    protected double width ; // To hold width or base    public void setValues( double height ,
    double width )
    {

    this. height = height;    this. width = width ;
    } }

public class Rectangle extends Shape
{
    public double getArea ()
    {
    return height * width ; // accessing protected members
    } }

public class TestProgram
{
    public static void main( String [] args)
    {

    Rectangle rectangle = new Rectangle ();    rectangle. setValues (5 ,4);
    System . out. println (" Area of rectangle : " + rectangle. getArea ());
    } }
```

Static Members



- . Static members are those which belongs to the class and you can access these members without instantiating the class.
- . The static keyword can be used with methods, fields, classes (inner/nested), blocks.
- . **Static Methods** – You can create a static method by using the keyword *static*. Static methods can access only static fields, methods. To access static methods there is no need to instantiate the class, you can do it just using the class name as

Static Member



```
public class MyClass
{
    public static void sample()
    {
        System.out.println("Hello");
    } public static
    void main(String args[])
    {
        MyClass.sample();
    }
}
```

Topic 1
Access Specifiers

Topic 2
Static Members

Third Lesson Summary

From this topic we learned the visibility about the classes and data members.

Constructors



Lesson 1. Object Oriented programming Concepts

Lesson 2. Fundamental programming Constructs

Lesson 3. Access Specifiers

Lesson 4. Constructors

Lesson 5. Inheritance

Constructors



In Java, a constructor is a block of codes similar to the method.

It is called when an instance of the class is created.

At the time of calling constructor, memory for the object is allocated in the memory.

It is a special type of method which is used to initialize the object.

Types of Constructors



A constructor having no parameter is known as default constructor and no-arg constructor.

Constructor having parameter is known as parameterized constructor.

```
class Box {  
    double    width ;  
    double    height;  
    double    depth ;  
  
    // default Constructor  
    Box ()  
    {        width =  3;        height =  4;        depth = 2;        }  
    // parameterized Constructor  
    Box( double w, double h, double d)  
    {        width = w;        height = h;        depth = d;        }  
}
```

Example

```
class BoxDemo7 {  
    public static void main( String args [])  
    {  
        Box mybox1 = new Box();  
        Box mybox2 = new Box(3, 6, 9);  
        double vol;  
        // get volume of first box  
        vol = mybox1 . volume ();   System . out .  
        println ("Volume is " + vol);  
        // get volume of second box  
        vol = mybox2 . volume ();   System . out .  
        println ("Volume is " + vol);  
    }  
}
```


this keyword

this can be used inside any method to refer to the current object. That is, this is always a reference to the object on which the method was invoked.

```
Box( double w, double h, double d) {  
    this.width = w;  
    this.height = h;  
    this.depth = d;  
}
```

Stack Implementation

```
class Stack
{
    int stck [] = new int [10];
    int tos;
    Stack ()
    {
        tos = -1;
    }
    void push(int item)
    {
        if (tos == 9)
            System.out.println("Stack is full.");
        else
            stck[++tos] = item;
    }
    int pop()
    {
        if (tos < 0) {
            System.out.println("underflow");
            Stack return 0;
        }
        else
            return stck[tos--];
    }
}
```

```
class TestStack {  
    public static void main( String args []) {  
        Stack mystack1 =new Stack();  
        Stack mystack2 = new Stack();  
        for( int i=0; i <10; i++) mystack1 . push(i);  
        for(int i=10; i <20; i++) mystack2 . push(i);  
        System . out . println("Stack in mystack1:");  
        for( int i=0; i <10; i++)  
            System . out . println( mystack1 . pop());  
        System . out . println("Stack in mystack2  
        :");  for( int i=0; i <10; i++)  
            System . out . println( mystack2 . pop());  
    }  
}
```

Topic 1
Default Constructor

Topic 2
Parameterized Constructor

Third Lesson Summary

Learnt the uses of constructors to assign initial values to the data members through default and parameterized constructors

Inheritance



Lesson 1. Object Oriented programming Concepts

Lesson 2. Fundamental programming Constructs

Lesson 3. Access Specifiers

Lesson 4. Constructors

Lesson 5. Inheritance



Inheritance Introduction

Definition of Inheritance

Inheritance is the mechanism of deriving new class from old one, old class is known as superclass and new class is known as subclass.

The subclass inherits all of its instances variables and methods defined by the superclass and it also adds its own unique elements.


Thus, we can say that subclass is specialized version of superclass.

Syntax


extends is the keyword used to inherit the properties of a class

```
class Super
{ .....
..... }
class Sub extends Super
{ .....
..... }
```


Types of Inheritance



**Single
Inheritance**



**Multilevel
Inheritance**



**Hierarchical
Inheritance**

Single Inheritance

- A class inherits another class
- For example the Dog class inherits the Animal class as shown below

```
class Animal{  
void eat(){System.out.println("eating...");}  
}  
class Dog extends Animal{  
void bark(){System.out.println("barking...");}  
}  
class TestInheritance{  
public static void main(String args[]){  
Dog d=new Dog();  
d.bark();  
d.eat();  
}}}
```

Output
barking...
eating...



Multiple Inheritance

- chain of inheritance
- its like child, parent and grandparent relationship
- for example a BabyDog class inherits the Dog class which again inherits the Animal class

Example Program

```
class Animal{
void eat(){System.out.println("eating...");}
}
class Dog extends Animal{
void bark(){System.out.println("barking...");}
}
class BabyDog extends Dog{
void weep(){System.out.println("weeping...");}
}
class TestInheritance2{
public static void main(String args[]){
BabyDog d=new BabyDog();
d.weep();
d.bark();
d.eat();
}}
```

Output
weeping...
barking...
eating...

Hierarchical Inheritance

- when two or more classes inherits a single class
- for example Dog class and Cat class inherits the Animal class

Example Program

```
class Animal{  
void eat(){System.out.println("eating...");}  
}  
class Dog extends Animal{  
void bark(){System.out.println("barking...");}  
}  
class Cat extends Animal{  
void meow(){System.out.println("meowing...");}  
}  
class TestInheritance3{  
public static void main(String args[]){  
Cat c=new Cat();  
c.meow();  
c.eat();  
//c.bark();//Compile Time Error  
}}
```

Output
meowing...
eating...



INTERFACE

- An **interface in java** is a blueprint of a class.
- It has static constants and abstract methods only.
- The interface in java is a **mechanism to achieve fully abstraction**.
- There can be only abstract methods in the java interface not method body.
- It is used to achieve fully abstraction and multiple inheritance in Java.

Program on Interface

```
interface IntStack
{
    void push(int item);
    int pop();
}
```

```
class FixedStack implements IntStack
{
    private int stack[];
    private int tos;
    FixedStack(int size)
    {
        stack=new int[size];
        tos=-1;
    }
    public void push(int item)
    {
        if(tos==stack.length-1)
            System.out.println("stack is full");
        else
            stack[++tos]=item;
    }
    public int pop()
    {
        if(tos<0)
        {
            System.out.println("stack underflow");
            return 0;
        }
    }
}
```

```
    }
    else
        return stack[tos--];
}
public static void main(String args[])
{
    FixedStack mystack1=new FixedStack(5);
    FixedStack mystack2=new FixedStack(8);
    for(int i=0;i<6;i++) mystack1.push(i);
    for(int i=0;i<9;i++) mystack2.push(i);
    System.out.println("stack in mystack1");
    for(int i=0;i<6;i++)
        System.out.println(mystack1.pop());
    System.out.println("stack in mystack2");
    for(int i=0;i<9;i++)
        System.out.println(mystack2.pop());
}
```

Output

```
C:\Users\admin\Desktop\dhilipjava>java FixedStack
stack is full
stack is full
stack in mystack1
4
3
2
1
0
stack underflow
stack in mystack2
7
6
5
4
3
2
1
0
stack underflow
0
```

Topic 1

Inheritance Introduction

Topic 2

Types of Inheritance

Topic 3

Private Member Access

Topic 4

Usage of Super

Topic 5

Protected Member Access

Topic 6

When constructors are called

Lesson Summary

Understood Inheritance and solve real world problem by implementing different types of inheritance

Packages



Lesson 1. Object Oriented programming Concepts

Lesson 2. Fundamental programming Constructs

Lesson 3. Access Specifiers

Lesson 4. Constructors

Lesson 5 : Inheritance

Lesson 6. Packages

Packages in Java



A **java package** is a group of similar types of classes, interfaces and sub-packages.

Package in java can be categorized in two form, built-in package and user-defined package.

There are many built-in packages such as java, lang, awt, javax, swing, net, io, util, sql etc.

Here, we will have the detailed learning of creating and using user-defined packages.



Packages in Java

Java uses file system directories to store packages. For example, the **.class** files for any classes you declare to be part of **MyPackage** must be stored in a directory called **MyPackage**.

You can create a hierarchy of packages. The general form of a multileveled package statement is shown here: **package pkg1[.pkg2[.pkg3]];**

Example

```
Simple.java - Notepad
File Edit Format View Help

package mypack;
public class Simple{
    public static void main(String args[]){
        System.out.println("Welcome to
package");
    }
}
```

```
Command Prompt
Microsoft Windows [Version 6.3.9600]
(c) 2013 Microsoft Corporation. All rights reserved.

C:\Users\guru>d:
D:\>cd java
D:\Java>set path="C:\Program Files\Java\jdk1.8.0_261\bin"
D:\Java>javac -d . Simple.java
D:\Java>java mypack.Simple
Welcome to package
D:\Java>
```

How to access package from another package?



There are three ways to access the package from outside the package.

- `import package.*;`
- `import package.classname;`
- fully qualified name.

Using packagename.*



Using packagename.*

If you use `package.*` then all the classes and interfaces of this package will be accessible but not sub packages. The `import` keyword is used to make the classes and interface of another package accessible to the current package.

```
package pack;
public class A
{
    public void msg()
    {
        System.out.println("Hello this is using packagename.*");
    }
}
```

```
package mypack;
import pack.*;
class B
{
    public static void main(String args[])
    {
        A obj = new A();
        obj.msg();
    }
}
```

Using packagename.classname



Using packagename.classname

If you import package.classname then only declared class of this package will be accessible.

Sample package created

 mypack	5/21/2020 12:19 PM	File folder
 mypack1	5/21/2020 12:24 PM	File folder
 mypack2	5/21/2020 12:33 PM	File folder
 p1	9/11/2020 10:00 AM	File folder
 pack	5/21/2020 12:19 PM	File folder
 pack1	5/21/2020 12:37 PM	File folder

Using fully qualified name



If you use fully qualified name then only declared class of this package will be accessible.

Now there is no need to import.

But you need to use fully qualified name every time when you are accessing the class or interface.

Topic 1

Packages in Java

Topic 2

Importing Packages

Topic 3

Builtin Packages in Java

Sixth Lesson Summary

Learned about Packages in Java, importing Packages, Builtin Packages in Java, JavaDoc, JavaDoc tags

Thank You!