

class07 (Machine Learning 1)

Amit Subramanian

PCA of UK food data

Read data from website, and try some visualizations


```
url <- "https://tinyurl.com/UK-foods"
x <- read.csv(url, row.names=1)
x
```

	England	Wales	Scotland	N.Ireland
Cheese	105	103	103	66
Carcass_meat	245	227	242	267
Other_meat	685	803	750	586
Fish	147	160	122	93
Fats_and_oils	193	235	184	209
Sugars	156	175	147	139
Fresh_potatoes	720	874	566	1033
Fresh_Veg	253	265	171	143
Other_Veg	488	570	418	355
Processed_potatoes	198	203	220	187
Processed_Veg	360	365	337	334
Fresh_fruit	1102	1137	957	674
Cereals	1472	1582	1462	1494
Beverages	57	73	53	47
Soft_drinks	1374	1256	1572	1506
Alcoholic_drinks	375	475	458	135
Confectionery	54	64	62	41


```
dim(x)
```

```
[1] 17  4
```


```
cols <- rainbow(nrow(x))  
barplot( as.matrix(x), col=cols )
```



```
barplot( as.matrix(x), col=cols, beside=TRUE )
```



```
pairs(x, col=cols)
```



The main base R PCA function is called `prcomp()`, we will need to give it the transpose of our input data.

```
pca <- prcomp( t(x) )
```

```
attributes(pca)
```

```
$names
```


```
[1] "sdev"      "rotation" "center"    "scale"     "x"
```

```
$class
```

```
[1] "prcomp"
```


To make our new PCA plot (a.k.a PCA score plot) we access `pca$x`

```
plot(pca$x[,1], pca$x[,2])  
text(pca$x[,1], pca$x[,2], colnames(x))
```



Now to add some colors

```
country_cols <- c("orange", "red", "blue", "green")
plot(pca$x[,1], pca$x[,2])
text(pca$x[,1], pca$x[,2], colnames(x),
col=country_cols)
```



We can use the square of `pca$sdev` (standard deviation), to calculate the amount of variation in the original data each PC accounts for

```
v <- round( pca$sdev^2/sum(pca$sdev^2) * 100 )
v
```


```
[1] 67 29 4 0
```

```
z <- summary(pca)
z$importance
```

	PC1	PC2	PC3	PC4
Standard deviation	324.15019	212.74780	73.87622	2.921348e-14
Proportion of Variance	0.67444	0.29052	0.03503	0.000000e+00
Cumulative Proportion	0.67444	0.96497	1.00000	1.000000e+00


Let's turn this into a bar plot

```
barplot(v, xlab="Principal Component", ylab="Percent Variation")
```



We can also consider the influence of each original variable

```
par(mar=c(10, 3, 0.35, 0))  
barplot(pca$rotation[,1], las=2)
```




Now to use ggplot for these figures

```
library(ggplot2)


df <- as.data.frame(pca$x)
df_lab <- tibble::rownames_to_column(df, "Country")

# Our first basic plot
ggplot(df_lab) +
  aes(PC1, PC2, col=Country) +
  geom_point()
```



We can also make the plot look much nicer by adding aesthetics and organization


```
ggplot(df_lab) +  
  aes(PC1, PC2, col=Country, label=Country) +  
  geom_hline(yintercept = 0, col="gray") +  
  geom_vline(xintercept = 0, col="gray") +  
  geom_point(show.legend = FALSE) +  
  geom_label(hjust=1, nudge_x = -10, show.legend = FALSE) +  
  expand_limits(x = c(-300,500)) +  
  xlab("PC1 (67.4%)") +  
  ylab("PC2 (28%)") +  
  theme_bw()
```

Now customise the plot with layers


```
ld <- as.data.frame(pca$rotation)
ld_lab <- tibble::rownames_to_column(ld, "Food")

ggplot(ld_lab) +
  aes(PC1, Food) +
  geom_col()
```



Now let's reorder the y-axis by PC1 loadings and add a color scale

```
ggplot(ld_lab) +
  aes(PC1, reorder(Food, PC1), bg=PC1) +
  geom_col() +
  xlab("PC1 Loadings/Contributions") +
  ylab("Food Group") +
  scale_fill_gradient2(low="purple", mid="gray", high="darkgreen", guide=NULL) +
  theme_bw()
```



We can also utilize a biplot to view the data


```
biplot(pca)
```


	PC1	PC2	PC3	PC4	PC5	PC6
Standard deviation	2214.2633	88.9209	84.33908	77.74094	69.66341	67.78516
Proportion of Variance	0.9917	0.0016	0.00144	0.00122	0.00098	0.00093
Cumulative Proportion	0.9917	0.9933	0.99471	0.99593	0.99691	0.99784

	PC7	PC8	PC9	PC10
Standard deviation	65.29428	59.90981	53.20803	2.662e-13
Proportion of Variance	0.00086	0.00073	0.00057	0.000e+00
Cumulative Proportion	0.99870	0.99943	1.00000	1.000e+00


Now to add our PCA plot

```
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2")
```



```
plot(pca, main="Quick scree plot")
```

Quick scree plot



Now to calculate the variation in the original data


```
## Variance captured per PC
pca.var <- pca$sdev^2

## Percent variance is often more informative to look at
pca.var.per <- round(pca.var/sum(pca.var)*100, 1)
pca.var.per
```

```
[1] 99.2  0.2  0.1  0.1  0.1  0.1  0.1  0.1  0.1  0.1  0.0
```

Let's use this to make a bar plot

```
barplot(pca.var.per, main="Scree Plot",
        names.arg = paste0("PC", 1:10),
        xlab="Principal Component", ylab="Percent Variation")
```




Let us add a vector of colors for our samples

```
## A vector of colors for wt and ko samples
colvec <- colnames(rna.data)
colvec[grep("wt", colvec)] <- "red"
colvec[grep("ko", colvec)] <- "blue"

plot(pca$x[,1], pca$x[,2], col=colvec, pch=16,
     xlab=paste0("PC1 (", pca.var.per[1], "%)"),
     ylab=paste0("PC2 (", pca.var.per[2], "%)"))

text(pca$x[,1], pca$x[,2], labels = colnames(rna.data), pos=c(rep(4,5), rep(2,5)))
```




Now to use ggplot

```
library(ggplot2)

df <- as.data.frame(pca$x)

# Our first basic plot
ggplot(df) +
  aes(PC1, PC2) +
  geom_point()
```





Now to add some condition specific colors and aesthetics

```
# Add a 'wt' and 'ko' "condition" column
df$samples <- colnames(rna.data)
df$condition <- substr(colnames(rna.data),1,2)

p <- ggplot(df) +
  aes(PC1, PC2, label=samples, col=condition) +
  geom_label(show.legend = FALSE)

p
```




Now let's polish up the plot

```
p + labs(title="PCA of RNASeq Data",
  subtitle = "PC1 clealy seperates wild-type from knock-out samples",
  x=paste0("PC1 (", pca.var.per[1], "%)"),
  y=paste0("PC2 (", pca.var.per[2], "%)"),
  caption="Class example data") +
  theme_bw()
```

PCA of RNASeq Data

PC1 clearly separates wild-type from knock-out samples



Class example data