API Reference

Amazon Connect Health

API Version 2025-01-29

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Connect Health: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome **1**
Actions **2**
ActivateSubscription 3
Request Syntax 3
URI Request Parameters 3
Request Body 3
Response Syntax 3
Response Elements 4
Errors 4
See Also 5
CreateDomain 6
Request Syntax 6
URI Request Parameters 6
Request Body 6
Response Syntax 7
Response Elements 8
Errors 9
See Also 9
CreateSubscription 11
Request Syntax 11
URI Request Parameters 11
Request Body 11
Response Syntax 11
Response Elements 12
Errors 13
See Also 14
DeactivateSubscription 15
Request Syntax 15
URI Request Parameters 15
Request Body 15
Response Syntax 15
Response Elements 16
Errors 16
See Also 17

DeleteDomain ... 18
Request Syntax ... 18
URI Request Parameters ... 18
Request Body ... 18
Response Syntax ... 18
Response Elements ... 18
Errors ... 19
See Also ... 19
GetDomain ... 21
Request Syntax ... 21
URI Request Parameters ... 21
Request Body ... 21
Response Syntax ... 21
Response Elements ... 22
Errors ... 23
See Also ... 24
GetMedicalScribeListeningSession ... 25
Request Syntax ... 25
URI Request Parameters ... 25
Request Body ... 26
Response Syntax ... 26
Response Elements ... 27
Errors ... 27
See Also ... 28
GetPatientInsightsJob ... 29
Request Syntax ... 29
URI Request Parameters ... 29
Request Body ... 29
Response Syntax ... 29
Response Elements ... 30
Errors ... 32
See Also ... 33
GetSubscription ... 34
Request Syntax ... 34
URI Request Parameters ... 34
Request Body ... 34

Response Syntax ... 34
Response Elements ... 35
Errors ... 35
See Also ... 36
ListDomains ... 37
Request Syntax ... 37
URI Request Parameters ... 37
Request Body ... 37
Response Syntax ... 37
Response Elements ... 38
Errors ... 38
See Also ... 38
ListSubscriptions ... 40
Request Syntax ... 40
URI Request Parameters ... 40
Request Body ... 40
Response Syntax ... 40
Response Elements ... 41
Errors ... 41
See Also ... 42
ListTagsForResource ... 43
Request Syntax ... 43
URI Request Parameters ... 43
Request Body ... 43
Response Syntax ... 43
Response Elements ... 43
Errors ... 44
See Also ... 44
StartMedicalScribeListeningSession ... 45
Request Syntax ... 45
URI Request Parameters ... 46
Request Body ... 47
Response Syntax ... 47
Response Elements ... 48
Errors ... 50
See Also ... 51

StartPatientInsightsJob ... 52
Request Syntax ... 52
URI Request Parameters ... 53
Request Body ... 53
Response Syntax ... 54
Response Elements ... 54
Errors ... 55
See Also ... 56
TagResource ... 57
Request Syntax ... 57
URI Request Parameters ... 57
Request Body ... 57
Response Syntax ... 58
Response Elements ... 58
Errors ... 58
See Also ... 58
UntagResource ... 59
Request Syntax ... 59
URI Request Parameters ... 59
Request Body ... 59
Response Syntax ... 59
Response Elements ... 59
Errors ... 60
See Also ... 60
Data Types ... 61
ArtifactDetails ... 63
Contents ... 63
See Also ... 63
ClinicalNoteGenerationResult ... 65
Contents ... 65
See Also ... 65
ClinicalNoteGenerationSettings ... 66
Contents ... 66
See Also ... 66
ClinicalNoteGenerationSettingsResponse ... 67
Contents ... 67

See Also ... 67
CreateWebAppConfiguration ... 68
Contents ... 68
See Also ... 68
CustomTemplate ... 70
Contents ... 70
See Also ... 70
CustomTemplateResponse ... 71
Contents ... 71
See Also ... 71
DomainSummary ... 72
Contents ... 72
See Also ... 73
EncounterContext ... 74
Contents ... 74
See Also ... 74
EncryptionContext ... 75
Contents ... 75
See Also ... 75
FHIRServer ... 76
Contents ... 76
See Also ... 76
InputDataConfig ... 77
Contents ... 77
See Also ... 77
InsightsContext ... 78
Contents ... 78
See Also ... 78
InsightsOutput ... 79
Contents ... 79
See Also ... 79
ManagedTemplate ... 80
Contents ... 80
See Also ... 80
ManagedTemplateResponse ... 81
Contents ... 81

See Also ... 81
MedicalScribeAudioEvent ... 82
Contents ... 82
See Also ... 82
MedicalScribeChannelDefinition ... 83
Contents ... 83
See Also ... 83
MedicalScribeConfigurationEvent ... 84
Contents ... 84
See Also ... 84
MedicalScribeInputStream ... 85
Contents ... 85
See Also ... 85
MedicalScribeListeningSessionDetails ... 86
Contents ... 86
See Also ... 88
MedicalScribeOutputStream ... 90
Contents ... 90
See Also ... 90
MedicalScribePostStreamActionSettings ... 91
Contents ... 91
See Also ... 91
MedicalScribePostStreamActionSettingsResponse ... 92
Contents ... 92
See Also ... 92
MedicalScribePostStreamActionsResult ... 93
Contents ... 93
See Also ... 93
MedicalScribeSessionControlEvent ... 94
Contents ... 94
See Also ... 94
MedicalScribeTranscriptEvent ... 95
Contents ... 95
See Also ... 95
MedicalScribeTranscriptSegment ... 96
Contents ... 96

See Also ... 97
NoteTemplateSettings ... 98
Contents ... 98
See Also ... 98
NoteTemplateSettingsResponse ... 99
Contents ... 99
See Also ... 99
OutputDataConfig ... 100
Contents ... 100
See Also ... 100
PatientInsightsEncounterContext ... 101
Contents ... 101
See Also ... 101
PatientInsightsPatientContext ... 102
Contents ... 102
See Also ... 102
S3Source ... 104
Contents ... 104
See Also ... 104
SubscriptionDescription ... 105
Contents ... 105
See Also ... 106
TemplateSectionInstruction ... 107
Contents ... 107
See Also ... 107
UserContext ... 108
Contents ... 108
See Also ... 108
WebAppConfiguration ... 110
Contents ... 110
See Also ... 110
Common Parameters ... 112
Common Errors ... 115

Welcome

Health Agent for healthcare providers and patient engagement

This document was last published on March 6, 2026.

Actions

The following actions are supported:

- ActivateSubscription
- CreateDomain
- CreateSubscription
- DeactivateSubscription
- DeleteDomain
- GetDomain
- GetMedicalScribeListeningSession
- GetPatientInsightsJob
- GetSubscription
- ListDomains
- ListSubscriptions
- ListTagsForResource
- StartMedicalScribeListeningSession
- StartPatientInsightsJob
- TagResource
- UntagResource

ActivateSubscription

Activates a Subscription to enable billing for a user.

Request Syntax

```
POST /domains/domainId/subscriptions/subscriptionId/activate HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The unique identifier of the parent Domain.

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

subscriptionId

The unique identifier of the Subscription.

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "subscription": {
      "activatedAt": number,
      "arn": "string",
      "createdAt": number,
      "deactivatedAt": number,
      "domainId": "string",
      "lastUpdatedAt": number,
      "status": "string",
      "subscriptionId": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

subscription

Type: SubscriptionDescription object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateDomain

Creates a new Domain for managing HealthAgent resources.

Request Syntax

```
POST /domain HTTP/1.1
Content-type: application/json

{
   "kmsKeyArn": "string",
   "name": "string",
   "tags": {
      "string" : "string"
   },
   "webAppSetupConfiguration": {
      "ehrRole": "string",
      "idcInstanceId": "string",
      "idcRegion": "string"
   }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

kmsKeyArn

The ARN of the KMS key to use for encrypting data in this Domain.

Type: String

Pattern: `arn:aws:kms:[a-z0-9-]+:[0-9]{12}:key/[a-f0-9-]+`

Required: No

name

The name for the new Domain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

tags

Tags to associate with the Domain.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

webAppSetupConfiguration

Configuration for the Domain web application. Optional, but if provided all fields are required.

Type: CreateWebAppConfiguration object

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
   "arn": "string",
   "createdAt": number,
   "domainId": "string",
   "encryptionContext": {
      "encryptionType": "string",
      "kmsKeyArn": "string"
   },
   "kmsKeyArn": "string",
   "name": "string",
   "status": "string",
   "webAppConfiguration": {
      "ehrRole": "string",
```

```
        "idcApplicationId": "string",
        "idcRegion": "string"
    },
    "webAppUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

arn

Type: String

Pattern: `arn:aws:health-agent:[a-z0-9-]+:[0-9]{12}:domain/(hai-|dom-)[a-z0-9]+`

createdAt

Type: Timestamp

domainId

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

encryptionContext

Type: EncryptionContext object

kmsKeyArn

Type: String

Pattern: `arn:aws:kms:[a-z0-9-]+:[0-9]{12}:key/[a-f0-9-]+`

name

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

status

Type: String

Valid Values: `ACTIVE | DELETING | DELETED`

webAppConfiguration

Type: WebAppConfiguration object

webAppUrl

Type: String

Errors

For information about the errors that are common to all actions, see Common Errors.

ServiceQuotaExceededException

The request exceeds a service quota.

HTTP Status Code: 402

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateSubscription

Creates a new Subscription within a Domain for billing and user management.

Request Syntax

```
POST /domains/domainId/subscriptions HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The unique identifier of the parent Domain.

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
   "activatedAt": number,
   "arn": "string",
   "createdAt": number,
   "deactivatedAt": number,
   "domainId": "string",
   "lastUpdatedAt": number,
   "status": "string",
   "subscriptionId": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

activatedAt

Type: Timestamp

arn

Type: String

Pattern: `arn:aws:health-agent:[a-z0-9-]+:[0-9]{12}:domain/(hai-|dom-)[a-z0-9]+/subscription/sub-[a-zA-Z0-9]{21}`

createdAt

Type: Timestamp

deactivatedAt

Type: Timestamp

domainId

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

lastUpdatedAt

Type: Timestamp

status

Type: String

Valid Values: `ACTIVE | INACTIVE | DELETED`

subscriptionId

Type: String

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeds a service quota.

HTTP Status Code: 402

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeactivateSubscription

Deactivates a Subscription to stop billing for a user.

Request Syntax

```
POST /domains/domainId/subscriptions/subscriptionId/deactivate HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The unique identifier of the parent Domain.

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

subscriptionId

The unique identifier of the Subscription.

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "subscription": {
      "activatedAt": number,
      "arn": "string",
      "createdAt": number,
      "deactivatedAt": number,
      "domainId": "string",
      "lastUpdatedAt": number,
      "status": "string",
      "subscriptionId": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

subscription

Type: SubscriptionDescription object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteDomain

Deletes a Domain and all associated resources.

Request Syntax

```
DELETE /domain/domainId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The id of the Domain to delete

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "arn": "string",
   "domainId": "string",
   "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the Domain that was requested for deletion

Type: String

Pattern: `arn:aws:health-agent:[a-z0-9-]+:[0-9]{12}:domain/(hai-|dom-)[a-z0-9]+`

domainId

The id of the Domain requested for deletion

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

status

Current status of Domain

Type: String

Valid Values: `ACTIVE | DELETING | DELETED`

Errors

For information about the errors that are common to all actions, see Common Errors.

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetDomain

Retrieves information about a Domain.

Request Syntax

```
GET /domain/domainId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The id of the Domain to get

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "arn": "string",
   "createdAt": number,
   "domainId": "string",
   "encryptionContext": {
      "encryptionType": "string",
      "kmsKeyArn": "string"
   },
   "kmsKeyArn": "string",
```

```
    "name": "string",
    "status": "string",
    "tags": {
       "string" : "string"
    },
    "webAppConfiguration": {
       "ehrRole": "string",
       "idcApplicationId": "string",
       "idcRegion": "string"
    },
    "webAppUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

Type: String

Pattern: `arn:aws:health-agent:[a-z0-9-]+:[0-9]{12}:domain/(hai-|dom-)[a-z0-9]+`

createdAt

Type: Timestamp

domainId

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

encryptionContext

Type: EncryptionContext object

kmsKeyArn

Type: String

Pattern: `arn:aws:kms:[a-z0-9-]+:[0-9]{12}:key/[a-f0-9-]+`

name

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

status

Type: String

Valid Values: `ACTIVE | DELETING | DELETED`

tags

Tags associated with the Domain

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

webAppConfiguration

Type: WebAppConfiguration object

webAppUrl

Type: String

Errors

For information about the errors that are common to all actions, see Common Errors.

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetMedicalScribeListeningSession

Retrieves details about an existing Medical Scribe listening session

Request Syntax

```
GET /medical-scribe-stream/domain/domainId/subscription/subscriptionId/
session/sessionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The Domain identifier

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

sessionId

The Session identifier

Length Constraints: Fixed length of 36.

Pattern: `.*[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}.*`

Required: Yes

subscriptionId

The Subscription identifier

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "medicalScribeListeningSessionDetails": {
      "channelDefinitions": [
         {
            "channelId": number,
            "participantRole": "string"
         }
      ],
      "domainId": "string",
      "encounterContextProvided": boolean,
      "languageCode": "string",
      "mediaEncoding": "string",
      "mediaSampleRateHertz": number,
      "postStreamActionResult": {
         "clinicalNoteGenerationResult": {
            "afterVisitSummaryResult": {
               "failureReason": "string",
               "outputLocation": "string",
               "status": "string"
            },
            "noteResult": {
               "failureReason": "string",
               "outputLocation": "string",
               "status": "string"
            },
            "transcriptResult": {
               "failureReason": "string",
               "outputLocation": "string",
               "status": "string"
            }
         }
      },
      "postStreamActionSettings": {
         "clinicalNoteGenerationSettings": {
```

```
            "noteTemplateSettings": { ... }
         },
         "outputS3Uri": "string"
      },
      "sessionId": "string",
      "streamCreationTime": number,
      "streamEndTime": number,
      "streamStatus": "string",
      "subscriptionId": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

medicalScribeListeningSessionDetails

Details about the Medical Scribe listening session

Type: MedicalScribeListeningSessionDetails object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeds a service quota.

HTTP Status Code: 402

ThrottlingException

This error is thrown when the client exceeds the allowed request rate.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetPatientInsightsJob

Get details of a started patient insights job.

Request Syntax

```
GET /domain/domainId/patient-insights-job/jobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

jobId

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "creationTime": "string",
   "encounterContext": {
      "encounterReason": "string"
```

```
    },
    "inputDataConfig": {
       "fhirServer": {
          "fhirEndpoint": "string",
          "oauthToken": "string"
       },
       "s3Sources": [
          {
             "uri": "string"
          }
       ]
    },
    "insightsContext": {
       "insightsType": "string"
    },
    "insightsOutput": {
       "uri": "string"
    },
    "jobArn": "string",
    "jobId": "string",
    "jobStatus": "string",
    "outputDataConfig": {
       "s3OutputPath": "string"
    },
    "patientContext": {
       "dateOfBirth": "string",
       "patientId": "string",
       "pronouns": "string"
    },
    "statusDetails": "string",
    "updatedTime": "string",
    "userContext": {
       "role": "string",
       "specialty": "string",
       "userId": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationTime

Date and time the patient insights job was submitted.

Type: Timestamp

encounterContext

Type: PatientInsightsEncounterContext object

inputDataConfig

Type: InputDataConfig object

insightsContext

Type: InsightsContext object

insightsOutput

Type: InsightsOutput object

jobArn

Type: String

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:aws[-a-z]*:health-agent:[-a-z0-9]+:[0-9]{12}:domain/[-a-zA-Z0-9-]+/patient-insights-job/[-a-zA-Z0-9_/.]+`

jobId

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

jobStatus

Type: String

Valid Values: `SUBMITTED | IN_PROGRESS | FAILED | SUCCEEDED`

outputDataConfig

Type: OutputDataConfig object

patientContext

Type: PatientInsightsPatientContext object

statusDetails

Contains information about the status of a job.

Type: String

Pattern: `.*[\s\S]*\S[\s\S]*.*`

updatedTime

Date and time the patient insights job was last updated.

Type: Timestamp

userContext

Type: UserContext object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ThrottlingException

This error is thrown when the client exceeds the allowed request rate.

HTTP Status Code: 429

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetSubscription

Retrieves information about a Subscription.

Request Syntax

```
GET /domains/domainId/subscriptions/subscriptionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The unique identifier of the parent Domain.

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

subscriptionId

The unique identifier of the Subscription.

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "subscription": {
      "activatedAt": number,
      "arn": "string",
      "createdAt": number,
      "deactivatedAt": number,
      "domainId": "string",
      "lastUpdatedAt": number,
      "status": "string",
      "subscriptionId": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

subscription

Type: SubscriptionDescription object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListDomains

Lists Domains for a given account.

Request Syntax

```
GET /domain?maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Token for pagination.

status

Filter by Domain status.

Valid Values: `ACTIVE | DELETING | DELETED`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "domains": [
      {
         "arn": "string",
         "createdAt": number,
```

```
            "domainId": "string",
            "name": "string",
            "status": "string"
        }
    ],
    "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

domains

List of Domains.

Type: Array of DomainSummary objects

nextToken

Token for the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Errors.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListSubscriptions

Lists all Subscriptions within a Domain.

Request Syntax

```
GET /domains/domainId/subscriptions?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The unique identifier of the parent Domain.

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

maxResults

Maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Token for pagination.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "nextToken": "string",
   "subscriptions": [
      {
         "activatedAt": number,
         "arn": "string",
         "createdAt": number,
         "deactivatedAt": number,
         "domainId": "string",
         "lastUpdatedAt": number,
         "status": "string",
         "subscriptionId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Token for the next page of results.

Type: String

subscriptions

List of Subscriptions.

Type: Array of SubscriptionDescription objects

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListTagsForResource

Lists the tags associated with the specified resource

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource to list tags for

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "tags": {
      "string" : "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags associated with the resource

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see Common Errors.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartMedicalScribeListeningSession

Starts a new Medical Scribe listening session for real-time audio transcription

Request Syntax

```
POST /medical-scribe-stream/ HTTP/1.1
x-amzn-medscribe-session-id: sessionId
x-amzn-medscribe-domain-id: domainId
x-amzn-medscribe-subscription-id: subscriptionId
x-amzn-medscribe-language-code: languageCode
x-amzn-medscribe-sample-rate: mediaSampleRateHertz
x-amzn-medscribe-media-encoding: mediaEncoding
Content-type: application/json

{
   "audioEvent": {
      "audioChunk": blob
   },
   "configurationEvent": {
      "channelDefinitions": [
         {
            "channelId": number,
            "participantRole": "string"
         }
      ],
      "encounterContext": {
         "unstructuredContext": "string"
      },
      "postStreamActionSettings": {
         "clinicalNoteGenerationSettings": {
            "noteTemplateSettings": { ... }
         },
         "outputS3Uri": "string"
      }
   },
   "sessionControlEvent": {
      "type": "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

domainId

The Domain identifier

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

languageCode

The Language Code for the audio in the session

Valid Values: `en-US`

Required: Yes

mediaEncoding

The encoding for the input audio

Valid Values: `pcm | flac`

Required: Yes

mediaSampleRateHertz

The sample rate of the input audio

Valid Range: Minimum value of 8000. Maximum value of 48000.

Required: Yes

sessionId

The Session identifier

Length Constraints: Fixed length of 36.

Pattern: `.*[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}.*`

Required: Yes

subscriptionId

The Subscription identifier

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

audioEvent

Type: MedicalScribeAudioEvent object

Required: No

configurationEvent

Type: MedicalScribeConfigurationEvent object

Required: No

sessionControlEvent

Type: MedicalScribeSessionControlEvent object

Required: No

Response Syntax

```
HTTP/1.1 200
x-amzn-medscribe-session-id: sessionId
x-amzn-medscribe-domain-id: domainId
x-amzn-medscribe-subscription-id: subscriptionId
x-amzn-request-id: requestId
```

```
x-amzn-medscribe-language-code: languageCode
x-amzn-medscribe-sample-rate: mediaSampleRateHertz
x-amzn-medscribe-media-encoding: mediaEncoding
Content-type: application/json

{
   "internalFailureException": {
   },
   "transcriptEvent": {
      "transcriptSegment": {
         "audioBeginOffset": number,
         "audioEndOffset": number,
         "channelId": "string",
         "content": "string",
         "isPartial": boolean,
         "segmentId": "string"
      }
   },
   "validationException": {
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

domainId

The Domain identifier

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

languageCode

The Language Code for the audio in the session

Valid Values: `en-US`

mediaEncoding

The encoding for the input audio

Valid Values: `pcm | flac`

mediaSampleRateHertz

The sample rate of the input audio

Valid Range: Minimum value of 8000. Maximum value of 48000.

requestId

The Request identifier

Length Constraints: Minimum length of 1. Maximum length of 256.

sessionId

The Session identifier

Length Constraints: Fixed length of 36.

Pattern: `.*[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}.*`

subscriptionId

The Subscription identifier

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

The following data is returned in JSON format by the service.

internalFailureException

Type: Exception

HTTP Status Code: 500

transcriptEvent

Type: MedicalScribeTranscriptEvent object

validationException

Type: Exception

HTTP Status Code: 400

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeds a service quota.

HTTP Status Code: 402

ThrottlingException

This error is thrown when the client exceeds the allowed request rate.

HTTP Status Code: 429

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartPatientInsightsJob

Starts a new patient insights job.

Request Syntax

```
POST /domain/domainId/patient-insights-job HTTP/1.1
Content-type: application/json

{
   "clientToken": "string",
   "encounterContext": {
      "encounterReason": "string"
   },
   "inputDataConfig": {
      "fhirServer": {
         "fhirEndpoint": "string",
         "oauthToken": "string"
      },
      "s3Sources": [
         {
            "uri": "string"
         }
      ]
   },
   "insightsContext": {
      "insightsType": "string"
   },
   "outputDataConfig": {
      "s3OutputPath": "string"
   },
   "patientContext": {
      "dateOfBirth": "string",
      "patientId": "string",
      "pronouns": "string"
   },
   "userContext": {
      "role": "string",
      "specialty": "string",
      "userId": "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

domainId

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Pattern: `.*[\s\S]*\S[\s\S]*.*`

Required: No

encounterContext

Type: PatientInsightsEncounterContext object

Required: Yes

inputDataConfig

Type: InputDataConfig object

Required: Yes

insightsContext

Type: InsightsContext object

Required: Yes

outputDataConfig

Type: OutputDataConfig object

Required: Yes

patientContext

Type: PatientInsightsPatientContext object

Required: Yes

userContext

Type: UserContext object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "creationTime": "string",
   "jobArn": "string",
   "jobId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationTime

Date and time the patient insights job was submitted.

Type: Timestamp

jobArn

Type: String

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:aws[-a-z]*:health-agent:[-a-z0-9]+:[0-9]{12}:domain/[-a-zA-Z0-9-]+/patient-insights-job/[-a-zA-Z0-9_/.]+`

jobId

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

This error is thrown when the client does not supply proper credentials to the API.

HTTP Status Code: 401

ConflictException

This error is thrown when a resource update is no longer valid due to assumptions about initial state changing.

HTTP Status Code: 409

InternalServerException

This error is thrown when a transient error causes our API to fail.

HTTP Status Code: 500

ResourceNotFoundException

This error is thrown when the requested resource is not found.

HTTP Status Code: 404

ThrottlingException

This error is thrown when the client exceeds the allowed request rate.

HTTP Status Code: 429

ValidationException

This error is thrown when the client supplies invalid input to the API.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

TagResource

Associates the specified tags with the specified resource

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource to tag

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags to add to the resource

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UntagResource

Removes the specified tags from the specified resource

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource to untag

Required: Yes

tagKeys

The tag keys to remove from the resource

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

Data Types

The Connect Health API contains several data types that various actions use. This section describes each data type in detail.

> **Note**
>
> The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- ArtifactDetails
- ClinicalNoteGenerationResult
- ClinicalNoteGenerationSettings
- ClinicalNoteGenerationSettingsResponse
- CreateWebAppConfiguration
- CustomTemplate
- CustomTemplateResponse
- DomainSummary
- EncounterContext
- EncryptionContext
- FHIRServer
- InputDataConfig
- InsightsContext
- InsightsOutput
- ManagedTemplate
- ManagedTemplateResponse
- MedicalScribeAudioEvent
- MedicalScribeChannelDefinition
- MedicalScribeConfigurationEvent
- MedicalScribeInputStream

- MedicalScribeListeningSessionDetails
- MedicalScribeOutputStream
- MedicalScribePostStreamActionSettings
- MedicalScribePostStreamActionSettingsResponse
- MedicalScribePostStreamActionsResult
- MedicalScribeSessionControlEvent
- MedicalScribeTranscriptEvent
- MedicalScribeTranscriptSegment
- NoteTemplateSettings
- NoteTemplateSettingsResponse
- OutputDataConfig
- PatientInsightsEncounterContext
- PatientInsightsPatientContext
- S3Source
- SubscriptionDescription
- TemplateSectionInstruction
- UserContext
- WebAppConfiguration

ArtifactDetails

Details about a generated artifact including location and status

Contents

failureReason

The reason for failure if the artifact generation failed

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\s\S]*`

Required: No

outputLocation

Type: String

Length Constraints: Minimum length of 1.

Pattern: `.*(s3://|http(s*)://).+.*`

Required: No

status

The generation status of the artifact

Type: String

Valid Values: `IN_PROGRESS | FAILED | COMPLETED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ClinicalNoteGenerationResult

Results of clinical note generation including note, transcript, and summary

Contents

afterVisitSummaryResult

Details about the generated after visit summary

Type: ArtifactDetails object

Required: No

noteResult

Details about the generated clinical note

Type: ArtifactDetails object

Required: No

transcriptResult

Details about the generated transcript

Type: ArtifactDetails object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ClinicalNoteGenerationSettings

Settings for generating clinical notes from the audio stream

Contents

noteTemplateSettings

Settings for the note template to use

Type: NoteTemplateSettings object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ClinicalNoteGenerationSettingsResponse

Response containing settings for clinical note generation

Contents

noteTemplateSettings

Settings for the note template used

Type: NoteTemplateSettingsResponse object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CreateWebAppConfiguration

Input configuration for creating a Pulse web application. Used only in CreateDomain operation input.

Contents

ehrRole

ARN of the IAM role used for EHR operations.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws:iam::[0-9]{12}:role/.+`

Required: Yes

idcInstanceId

The Identity Center instance ID to use for creating the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

idcRegion

The AWS region where Identity Center is configured.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CustomTemplate

Configuration for using a custom note template with specific instructions

Contents

templateInstructions

Custom instructions for each section of the template

Type: Array of TemplateSectionInstruction objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: Yes

templateType

The base template type to customize

Type: String

Valid Values: `HISTORY_AND_PHYSICAL | GIRPP | DAP | SIRP | BIRP | BEHAVIORAL_SOAP`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CustomTemplateResponse

Response containing custom template information

Contents

templateType

The base template type that was customized

Type: String

Valid Values: `HISTORY_AND_PHYSICAL | GIRPP | DAP | SIRP | BIRP | BEHAVIORAL_SOAP`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DomainSummary

Summary information about a Domain.

Contents

arn

Type: String

Pattern: `arn:aws:health-agent:[a-z0-9-]+:[0-9]{12}:domain/(hai-|dom-)[a-z0-9]+`

Required: Yes

createdAt

The timestamp when the Domain was created.

Type: Timestamp

Required: Yes

domainId

The unique identifier of the Domain.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

name

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

status

Type: String

Valid Values: `ACTIVE | DELETING | DELETED`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EncounterContext

Context information about the clinical encounter

Contents

unstructuredContext

Unstructured context information in markdown format

Type: String

Pattern: `[a-zA-Z0-9\s\*_\-#\[\]\(\)\.,:;!?'"`<>~]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EncryptionContext

Encryption context for a Domain.

Contents

encryptionType

The type of encryption key used.

Type: String

Valid Values: `AWS_OWNED_KEY | CUSTOMER_MANAGED_KEY`

Required: Yes

kmsKeyArn

The ARN of the KMS key. Only present when encryptionType is CUSTOMER_MANAGED_KEY.

Type: String

Pattern: `arn:aws:kms:[a-z0-9-]+:[0-9]{12}:key/[a-f0-9-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

FHIRServer

FHIR server configuration for input data source

Contents

fhirEndpoint

FHIR server endpoint URL for accessing patient data.

Type: String

Pattern: `https?://[a-zA-Z0-9\-._~:/?#\[\]@!$&'()*+,;=%]+`

Required: Yes

oauthToken

OAuth token for authenticating with the FHIR server.

Type: String

Pattern: `.*[\s\S]*\S[\s\S]*.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputDataConfig

Configuration details for input patient data

Contents

fhirServer

FHIR server configuration to retrieve patient data.

Type: FHIRServer object

Required: No

s3Sources

List of S3 sources containing patient data.

Type: Array of S3Source objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InsightsContext

Details for insights that user wants to generate

Contents

insightsType

Type: String

Valid Values: `PRE_VISIT`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InsightsOutput

Output of patient insights job

Contents

uri

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ManagedTemplate

Configuration for using a managed note template

Contents

templateType

The type of managed template to use

Type: String

Valid Values: `HISTORY_AND_PHYSICAL | GIRPP | DAP | SIRP | BIRP | BEHAVIORAL_SOAP | PHYSICAL_SOAP`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ManagedTemplateResponse

Response containing managed template information

Contents

templateType

The type of managed template used

Type: String

Valid Values: `HISTORY_AND_PHYSICAL | GIRPP | DAP | SIRP | BIRP | BEHAVIORAL_SOAP | PHYSICAL_SOAP`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeAudioEvent

An event containing audio data for the Medical Scribe stream

Contents

audioChunk

The audio data chunk

Type: Base64-encoded binary data object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeChannelDefinition

Defines a channel in the audio stream

Contents

channelId

The channel identifier

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1.

Required: Yes

participantRole

The role of the participant on this channel

Type: String

Valid Values: `PATIENT | CLINICIAN`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeConfigurationEvent

An event containing configuration for the Medical Scribe session

Contents

postStreamActionSettings

Settings for actions to perform after the stream ends

Type: MedicalScribePostStreamActionSettings object

Required: Yes

channelDefinitions

Channel definitions for the audio stream

Type: Array of MedicalScribeChannelDefinition objects

Array Members: Fixed number of 2 items.

Required: No

encounterContext

Context information about the clinical encounter

Type: EncounterContext object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeInputStream

Input stream for Medical Scribe containing audio and configuration events

Contents

audioEvent

Type: MedicalScribeAudioEvent object

Required: No

configurationEvent

Type: MedicalScribeConfigurationEvent object

Required: No

sessionControlEvent

Type: MedicalScribeSessionControlEvent object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeListeningSessionDetails

Detailed information about a Medical Scribe listening session

Contents

channelDefinitions

Channel definitions for the audio stream

Type: Array of MedicalScribeChannelDefinition objects

Array Members: Fixed number of 2 items.

Required: No

domainId

The Domain identifier

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: No

encounterContextProvided

Indicates whether encounter context was provided

Type: Boolean

Required: No

languageCode

The Language Code for the audio in the session

Type: String

Valid Values: `en-US`

Required: No

mediaEncoding

The encoding for the input audio

Type: String

Valid Values: `pcm | flac`

Required: No

mediaSampleRateHertz

The sample rate of the input audio

Type: Integer

Valid Range: Minimum value of 8000. Maximum value of 48000.

Required: No

postStreamActionResult

Results of post-stream actions

Type: MedicalScribePostStreamActionsResult object

Required: No

postStreamActionSettings

Settings for post-stream actions

Type: MedicalScribePostStreamActionSettingsResponse object

Required: No

sessionId

The Session identifier

Type: String

Length Constraints: Fixed length of 36.

Pattern: `.*[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}.*`

Required: No

streamCreationTime

The timestamp when the stream was created

Type: Timestamp

Required: No

streamEndTime

The timestamp when the stream ended

Type: Timestamp

Required: No

streamStatus

The current status of the stream

Type: String

Valid Values: `IN_PROGRESS | PAUSED | FAILED | COMPLETED`

Required: No

subscriptionId

The Subscription identifier

Type: String

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeOutputStream

Output stream from Medical Scribe containing transcript events and errors

Contents

internalFailureException

Type: Exception

HTTP Status Code: 500

Required: No

transcriptEvent

Type: MedicalScribeTranscriptEvent object

Required: No

validationException

Type: Exception

HTTP Status Code: 400

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribePostStreamActionSettings

Settings for actions to perform after the audio stream ends

Contents

clinicalNoteGenerationSettings

Settings for clinical note generation

Type: ClinicalNoteGenerationSettings object

Required: Yes

outputS3Uri

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribePostStreamActionSettingsResponse

Response containing settings for post-stream actions

Contents

clinicalNoteGenerationSettings

Settings for clinical note generation

Type: ClinicalNoteGenerationSettingsResponse object

Required: Yes

outputS3Uri

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribePostStreamActionsResult

Results of post-stream actions performed after the audio stream ended

Contents

clinicalNoteGenerationResult

Results of clinical note generation

Type: ClinicalNoteGenerationResult object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeSessionControlEvent

An event for controlling the Medical Scribe session

Contents

type

The type of session control event

Type: String

Valid Values: `END_OF_SESSION`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeTranscriptEvent

An event containing transcript data from the Medical Scribe stream

Contents

transcriptSegment

A segment of the transcript

Type: MedicalScribeTranscriptSegment object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MedicalScribeTranscriptSegment

A segment of transcript text with timing and channel information

Contents

audioBeginOffset

The offset from audio start when the audio for this segment begins

Type: Double

Required: No

audioEndOffset

The offset from audio start when the audio for this segment ends

Type: Double

Required: No

channelId

The channel identifier for this segment

Type: String

Required: No

content

The transcript text content

Type: String

Required: No

isPartial

Indicates whether this is a partial or final transcript

Type: Boolean

Required: No

segmentId

The unique identifier for this segment

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NoteTemplateSettings

Settings for the note template to use for clinical note generation

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

customTemplate

Type: CustomTemplate object

Required: No

managedTemplate

Type: ManagedTemplate object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NoteTemplateSettingsResponse

Response containing note template settings

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

customTemplate

Type: CustomTemplateResponse object

Required: No

managedTemplate

Type: ManagedTemplateResponse object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OutputDataConfig

Configuration details for insights output.

Contents

s3OutputPath

S3 URI where the insights output will be stored.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatientInsightsEncounterContext

Details for an encounter

Contents

encounterReason

Chief complaint for the visit

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9 .,-]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatientInsightsPatientContext

Details for a patient

Contents

patientId

Unique identifier of the patient

Type: String

Pattern: `.*[\s\S]*\S[\s\S]*.*`

Required: Yes

dateOfBirth

Date of birth of the patient.

Type: String

Pattern: `\d{4}-(0[1-9]|1[0-2])-(0[1-9]|[12]\d|3[01])`

Required: No

pronouns

Pronouns preferred by the patient.

Type: String

Valid Values: `HE_HIM | SHE_HER | THEY_THEM`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

S3Source

S3 uri for input data source

Contents

uri

The S3 URI.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SubscriptionDescription

Complete subscription resource data.

Contents

arn

Type: String

Pattern: `arn:aws:health-agent:[a-z0-9-]+:[0-9]{12}:domain/(hai-|dom-)[a-z0-9]+/subscription/sub-[a-zA-Z0-9]{21}`

Required: Yes

createdAt

Type: Timestamp

Required: Yes

domainId

Type: String

Length Constraints: Minimum length of 20. Maximum length of 25.

Pattern: `(hai-|dom-)[a-z0-9]+`

Required: Yes

lastUpdatedAt

Type: Timestamp

Required: Yes

status

Type: String

Valid Values: `ACTIVE | INACTIVE | DELETED`

Required: Yes

subscriptionId

Type: String

Length Constraints: Fixed length of 25.

Pattern: `sub-[a-zA-Z0-9]{21}`

Required: Yes

activatedAt

Type: Timestamp

Required: No

deactivatedAt

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TemplateSectionInstruction

Instructions for generating a specific section of a clinical note

Contents

sectionHeader

The header for this section of the template

Type: String

Pattern: `[a-zA-Z0-9]+`

Required: Yes

sectionInstruction

The instruction for generating this section

Type: String

Pattern: `[a-zA-Z0-9\s\*_\-#\[\]\(\)\.,:;!?'"`<>~]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

UserContext

Details for user initiating insights job

Contents

role

Type: String

Valid Values: `CLINICIAN`

Required: Yes

userId

Unique identifier of the user

Type: String

Pattern: `.*[\s\S]*\S[\s\S]*.*`

Required: Yes

specialty

Type: String

Valid Values: `PRIMARY_CARE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

WebAppConfiguration

Configuration for the Domain web application, including Identity Center settings. If provided, all fields are required.

Contents

ehrRole

ARN of the IAM role used for EHR operations.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws:iam::[0-9]{12}:role/.+`

Required: Yes

idcApplicationId

The Identity Center application ID associated with this Domain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

idcRegion

The AWS region where Identity Center is configured.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see Signing AWS API requests in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key*/*YYYYMMDD*/*region*/*service*/aws4_request.

For more information, see Create a signed AWS API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see Elements of an AWS API request signature in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see AWS services that work with IAM in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see Create a signed AWS API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400