[LOGO AREA]

AMMAR ALZAIEM

CYBERSECURITY | VAPT

SECURITY ASSESSMENT REPORT

Linux Commands

REPORT ID	AZ-EH-2026-001
VERSION	1.0
ASSESSMENT DATE	17/10/2026
REPORT DATE	22/10/2026
PREPARED BY	Ammar Alzaiem
CLASSIFICATION	Public

Linux Command – What It Does – When to Use It

Linux Command	What It Does	When to Use It
`pwd`	Displays the current working directory.	When you need to know where you are in the filesystem.
`ls`	Lists files and directories.	When you want to see the contents of a directory.
`ls -la`	Lists all files, including hidden ones, with detailed information.	When inspecting file permissions, ownership, and hidden files.
`cd`	Changes the current directory.	When navigating between directories.
`mkdir`	Creates a new directory.	When organizing files or creating a project folder.
`touch`	Creates an empty file or updates its timestamp.	When creating a new file quickly.
`cp`	Copies files or directories.	When backing up files or duplicating content.
`mv`	Moves or renames files and directories.	When organizing files or changing filenames.
`rm`	Removes files.	When deleting files that are no longer needed.
`rmdir`	Removes an empty directory.	When cleaning up unused directories.
`cat`	Displays or combines file contents.	When reading short text files or configuration files.
`less`	Displays file contents one screen at a time.	When reading large files or logs.
`head`	Displays the first lines of a file.	When checking the beginning of a file or log.
`tail`	Displays the last lines of a file.	When checking recent log entries.

`tail -f`	Continuously displays new lines added to a file.	When monitoring logs in real time.
`nano`	Opens a simple terminal text editor.	When creating or editing configuration files.
`grep`	Searches text for a specified pattern.	When finding errors, usernames, IP addresses, or keywords in files.
`find`	Searches for files and directories based on specified conditions.	When locating files by name, type, or other attributes.
`which`	Shows the path of an executable found through `PATH`.	When checking which executable will run for a command.
`whoami`	Displays the current effective username.	When verifying which user you are operating as.
`id`	Displays the user's UID, GID, and group memberships.	When checking account identity and group permissions.
`sudo`	Runs a command with elevated privileges when authorized.	When performing administrative tasks that require root privileges.
`chmod`	Changes file or directory permissions.	When controlling who can read, modify, or execute a file.
`chown`	Changes file or directory ownership.	When correcting ownership of files or directories.
`ps`	Displays information about running processes.	When checking which processes are running.
`top`	Shows running processes and resource usage in real time.	When investigating high CPU or memory usage.
`kill`	Sends a signal to a process, usually to request termination.	When stopping an unresponsive or unnecessary process.
`df -h`	Displays filesystem disk space usage in a human-readable format.	When checking available disk space.

`du -sh`	Displays the total disk usage of a file or directory.	When finding how much space a directory occupies.
`free -h`	Displays memory and swap usage.	When checking available RAM and swap space.
`uname -a`	Displays system and kernel information.	When identifying the operating system's kernel and architecture details.
`ip addr`	Displays network interfaces and their IP addresses.	When troubleshooting network configuration.
`ip route`	Displays the system's routing table.	When checking the default gateway or diagnosing routing problems.
`ping`	Sends ICMP echo requests to test network reachability.	When checking whether a host is reachable, subject to network filtering.
`ss -tulpn`	Displays listening TCP/UDP sockets and associated process information where permitted.	When checking which services are listening on local ports.
`curl`	Transfers data to or from a URL.	When testing HTTP endpoints or inspecting web server responses.
`wget`	Downloads files from web servers.	When downloading files from a URL.
`ssh`	Connects securely to a remote system.	When administering a remote Linux server.
`scp`	Copies files securely between systems over SSH.	When transferring files to or from a remote machine.
`apt update`	Refreshes the local package index from configured repositories.	Before installing or upgrading packages on Debian-based systems.
`apt install`	Installs packages and their required dependencies.	When installing tools or software on Ubuntu or Kali Linux.
`systemctl status`	Displays the status of a systemd	When checking whether a service is

	service or unit.	running or has failed.
`journalctl`	Reads logs collected by the systemd journal.	When troubleshooting system or service errors.
`crontab -e`	Opens the current user's cron schedule for editing.	When scheduling recurring tasks.
`tar`	Archives files and directories, optionally with compression.	When creating or extracting backups and archive files.
`history`	Displays commands entered in the current shell's history.	When reviewing previously executed commands.
`man`	Opens the manual page for a command.	When learning command options and usage.
`echo`	Prints text or variable values to standard output.	When displaying messages or checking shell variables.
`sort`	Sorts lines of text.	When organizing command output or text-file contents.
`wc -l`	Counts lines in input or a file.	When counting log entries, records, or lines of text.