[LOGO AREA]

AMMAR ALZAIEM

CYBERSECURITY | VAPT

SECURITY ASSESSMENT REPORT

TryHackMe – Linux Fundamentals Part 1

REPORT ID	AZ-EH-2026-002
VERSION	1.0
ASSESSMENT DATE	17/10/2026
REPORT DATE	22/10/2026
PREPARED BY	Ammar Alzaiem
CLASSIFICATION	Public

Overview

This room introduces the Linux command line and some of the commands used to work with files and directories. It starts with basic commands and gradually moves into searching through files and combining commands.

Since Linux is used extensively in cybersecurity, getting comfortable with the terminal is important. I want to be able to navigate a system and find the information I need without depending on a graphical interface.

1. Basic Linux Commands

The first part introduces commands for interacting with the terminal.

```
whoami
```

Displays the username of the current user.

```
echo "TryHackMe"
```

Prints text to the terminal. It can also be used to write text into a file when combined with output redirection.

2. Navigating the Filesystem

I practised moving between directories and checking the contents of files using a few essential commands.

Command	Purpose
`pwd`	Shows the current working directory
`ls`	Lists files and directories
`cd`	Changes the current directory
`cat`	Displays a file's contents

For example:

```
pwd
```

```
ls
```

```
cd /home/tryhackme
```

One thing to understand is that commands such as `ls` operate on the current directory unless you provide another path.

3. Searching Through Files

Searching manually through a large file isn't practical, especially when dealing with logs. Linux provides commands that make this much easier.

find

`find` searches for files and directories based on criteria such as their names.

```
find -name "access.log"
```

This searches for a file named `access.log` under the current directory and its subdirectories.

grep

`grep` searches file contents for matching text.

```
grep "THM" access.log
```

In the room, this command is used to locate a flag inside a web server log file.

These commands are useful in cybersecurity when searching for specific information in system logs, configuration files, or other collected data.

4. Shell Operators and Redirection

This section introduces operators that control how commands run and where their output goes.

Running commands in sequence

```
command1 && command2
```

The second command runs only if the first command finishes successfully.

Running a command in the background

```
command &
```

The `&` operator starts the command in the background, allowing the shell to accept further input.

Redirecting output

```
echo "TryHackMe" > thm
```

The `>` operator writes the output to a file, replacing its existing contents if the file already exists.

```
echo "Another line" >> thm
```

The `>>` operator appends the output to the end of the file instead of replacing its existing contents.

This distinction is important because using `>` on an existing file can overwrite information.

Conclusion

This room covered some of the basic Linux skills I'll need for more advanced cybersecurity work. The commands themselves aren't complicated, but understanding how they fit together is important.

I also found the shell operators worth paying attention to because they allow commands to be combined and their output to be saved or reused. These basics will be useful when working with logs, running tools, and navigating Linux systems during future labs.

