

[LOGO AREA]

AMMAR ALZAIEM

CYBERSECURITY | VAPT

SECURITY ASSESSMENT REPORT

Task 1 Report

REPORT ID	AZ-VAPT-2026-001
VERSION	1.0
ASSESSMENT DATE	1/9/2026
REPORT DATE	1/9/2026
PREPARED BY	Ammar Alzaiem
CLASSIFICATION	Public

In this task we're not doing anything complex, just running bunch of commands

First

```
(amm@noOne)-[~]
$ hostname
noOne

(amm@noOne)-[~]
$ whoami
amm

(amm@noOne)-[~]
$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
   inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
   inet6 ::1/128 scope host noprefixroute
       valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
   link/ether f8:0d:ac:23:a3:ca brd ff:ff:ff:ff:ff:ff
   inet 192.168.1.114/24 brd 192.168.1.255 scope global dynamic noprefixroute eth0
       valid_lft 81981sec preferred_lft 81981sec
   inet6 fe80::6fca:7e39:6e8:be75/64 scope link noprefixroute
       valid_lft forever preferred_lft forever
3: wlan0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default qlen 1000
   link/ether a4:97:b1:71:00:d3 brd ff:ff:ff:ff:ff:ff
   inet 192.168.1.113/24 brd 192.168.1.255 scope global dynamic noprefixroute wlan0
       valid_lft 82044sec preferred_lft 82044sec
   inet6 fe80::a697:b1ff:fe71:d3/64 scope link noprefixroute
       valid_lft forever preferred_lft forever
4: docker0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default
   link/ether 36:40:24:a9:02:5b brd ff:ff:ff:ff:ff:ff
   inet 172.17.0.1/16 brd 172.17.255.255 scope global docker0
       valid_lft forever preferred_lft forever
   inet6 fe80::3440:24ff:fea9:25b/64 scope link proto kernel_ll
       valid_lft forever preferred_lft forever
5: br-1141a8f6eca3: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc noqueue state DOWN group default
   link/ether a2:f1:5b:26:51:de brd ff:ff:ff:ff:ff:ff
   inet 172.18.0.1/16 brd 172.18.255.255 scope global br-1141a8f6eca3
       valid_lft forever preferred_lft forever
6: veth06aa393qif2: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue master docker0 state UP group default
   link/ether 4a:01:bd:a0:4b:08 brd ff:ff:ff:ff:ff:ff link-netnsid 0
   inet6 fe80::4801:bdff:fea0:4b08/64 scope link proto kernel_ll
       valid_lft forever preferred_lft forever
7: utun420: <POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1420 qdisc noqueue state UNKNOWN group default qlen 1000
   link/none
   inet 100.120.118.161/32 scope global utun420
       valid_lft forever preferred_lft forever

(amm@noOne)-[~]
$ ping -c 4 localhost
PING localhost (127.0.0.1) 56(84) bytes of data:
64 bytes from localhost (127.0.0.1): icmp_seq=1 ttl=64 time=0.079 ms
64 bytes from localhost (127.0.0.1): icmp_seq=2 ttl=64 time=0.056 ms
64 bytes from localhost (127.0.0.1): icmp_seq=3 ttl=64 time=0.095 ms
64 bytes from localhost (127.0.0.1): icmp_seq=4 ttl=64 time=0.098 ms
--- localhost ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3057ms
rtt min/avg/max/mdev = 0.056/0.082/0.098/0.016 ms
```

Commands Explanation:

- **hostname** Displays the system name
- **whoami** Shows the username of the logged in user
- **ip a** Shows IP Addresses and interfaces(can be memorized as IP all)
- **ping -c 4 localhost** Tests connectivity to a host
 - **-c Count**, It determines how many ICMP messages to send, default is infinite

Second

```
(ammar@noOne)-[~]
$ ifconfig
br-1141a8f6eca3: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    inet 172.18.0.1 netmask 255.255.0.0 broadcast 172.18.255.255
    ether 76:0f:87:90:4e:04 txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

docker0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 172.17.0.1 netmask 255.255.0.0 broadcast 172.17.255.255
    inet6 fe80::381c:87ff:fe04:852 prefixlen 64 scopeid 0<link>
    ether 3a:1c:87:04:08:52 txqueuelen 0 (Ethernet)
    RX packets 14 bytes 2241 (2.1 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14 bytes 5007 (4.8 KiB)
    TX errors 0 dropped 2 overruns 0 carrier 0 collisions 0

eth0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    ether f8:0d:ac:23:a3:ca txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 8 bytes 480 (480.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 8 bytes 480 (480.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

veth720d47: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet6 fe80::9403:54ff:fec9:2aab prefixlen 64 scopeid 0<link>
    ether 96:03:54:c9:2a:ab txqueuelen 0 (Ethernet)
    RX packets 14 bytes 2437 (2.3 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 25 bytes 5873 (5.7 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

wlan0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.116 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 fe80::a697:b1ff:fe71:d3 prefixlen 64 scopeid 0<link>
    ether a4:97:b1:71:00:d3 txqueuelen 1000 (Ethernet)
    RX packets 133 bytes 25579 (24.9 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 109 bytes 12898 (12.5 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

(ammar@noOne)-[~]
$ ip route
default via 192.168.1.1 dev wlan0 proto dhcp src 192.168.1.116 metric 600
172.17.0.0/16 dev docker0 proto kernel scope link src 172.17.0.1
172.18.0.0/16 dev br-1141a8f6eca3 proto kernel scope link src 172.18.0.1 linkdown
192.168.1.0/24 dev wlan0 proto kernel scope link src 192.168.1.116 metric 600
```

Commands explanation

- **ifconfig** interface configurations, It shows the current applied configuration and modifications on the attached interfaces.
- **ip route** displays the routing table and gateway
- Gateway IP: **192.168.1.1**

Third

```
(amm@noOne)-[~]
$ sudo netstat -antp
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       PID/Program name
tcp        0      0 0.0.0.0:22             0.0.0.0:*               LISTEN      1313/sshd: /usr/sbi
tcp        0      0 0.0.0.0:3000           0.0.0.0:*               LISTEN      6691/docker-proxy
tcp        0      0 100.120.118.161:51960  142.251.153.119:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:51966  142.251.153.119:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:41390  74.125.29.132:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:58500  104.26.0.151:443      ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:40338  172.217.208.101:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:45844  74.125.11.73:443      ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:45852  74.125.11.73:443      ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:33640  34.160.81.0:443       ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:54724  172.217.115.4:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:54730  172.217.115.4:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:34424  208.103.161.2:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:36110  208.103.161.2:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:41968  173.194.69.188:5228    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:43448  208.103.161.1:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:46132  172.217.208.113:443    ESTABLISHED 8371/chrome --type=
tcp        1      0 100.120.118.161:54682  104.20.2.154:443      CLOSE_WAIT  60263/Windscribe
tcp        0      0 100.120.118.161:35902  173.194.188.7:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:52068  172.217.208.94:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:53232  172.217.118.4:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:58316  172.67.69.61:443      TIME_WAIT   -
tcp        0      0 100.120.118.161:58324  172.67.69.61:443      ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:55796  142.251.151.4:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:42210  142.251.157.119:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:56070  192.178.170.113:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:37674  173.194.164.148:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:43470  74.125.29.101:443     ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:34714  172.217.208.119:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:49742  172.217.208.136:443    ESTABLISHED 8371/chrome --type=
tcp        0      0 100.120.118.161:52164  74.125.162.227:443    ESTABLISHED 8371/chrome --type=
tcp6       0      0 :::22                  :::*                    LISTEN      1313/sshd: /usr/sbi
tcp6       0      0 :::3000                :::*                    LISTEN      6704/docker-proxy

(amm@noOne)-[~]
$ ss -tulpn
Netid State  Recv-Q Send-Q Local Address:Port Peer Address:Port Process
udp UNCONN 0      0 224.0.0.251:5353 0.0.0.0:* users(("chrome",pid=8305,fd=133))
udp UNCONN 0      0 224.0.0.251:5353 0.0.0.0:* users(("chrome",pid=8305,fd=132))
udp UNCONN 0      0 224.0.0.251:5353 0.0.0.0:* users(("chrome",pid=8305,fd=131))
udp UNCONN 0      0 224.0.0.251:5353 0.0.0.0:* users(("chrome",pid=8305,fd=129))
udp UNCONN 0      0 0.0.0.0:51053 0.0.0.0:* 
udp UNCONN 0      0 [fe80::a697:b1ff:fe71:d3]::%wlan0:546 [::]:*
udp UNCONN 0      0 [fe80::6fca:7e39:6e8:be75]::%eth0:546 [::]:*
udp UNCONN 0      0 [::]:51053 [::]:*
tcp LISTEN 0      128 0.0.0.0:22 0.0.0.0:*
tcp LISTEN 0     4096 0.0.0.0:3000 0.0.0.0:*
tcp LISTEN 0      128 [::]:22 [::]:*
tcp LISTEN 0     4096 [::]:3000 [::]:*
```

Commands explanation

- **netstat** Used to display network connections
- **-a** Shows all sockets, **-n** Shows numerical addresses only, **-t** Limit the output to TCP connections, **-p** Shows the PID and name of the owner of the socket.
- **ss** Modern replacement for netstat **-t** Displays TCP sockets, **-u** Displays UDP sockets, **-l** Display only listening sockets, **-p** and **-n** same for netstat