

[LOGO AREA]

AMMAR ALZAIEM

CYBERSECURITY | VAPT

SECURITY ASSESSMENT REPORT

Version detection and mapping – Task 9

REPORT ID	AZ-WEB-2026-009
VERSION	1.0
ASSESSMENT DATE	10/9/2026
REPORT DATE	10/9/2026
PREPARED BY	Ammar Alzaiem
CLASSIFICATION	Public

I ran Nmap service/version detection and safe default scripts to identify services running on the target and compare them with the expected Metasploitable2 services.

Scan Results

Nmap identified 23 open TCP ports:

Port	Service	Version
21	FTP	vsftpd 2.3.4
22	SSH	OpenSSH 4.7p1
23	Telnet	Linux telnetd
25	SMTP	Postfix
53	DNS	BIND 9.4.2
80	HTTP	Apache 2.2.8
111	RPC	rpcbind
139/445	SMB	Samba 3.0.20
512/513/514	rexec/rlogin/rsh	Netkit
1099	Java RMI	GNU Classpath
1524	Bind Shell	Metasploitable root shell
2049	NFS	NFS v2-4
2121	FTP	ProFTPD 1.3.1
3306	MySQL	5.0.51a
5432	PostgreSQL	8.3.x
5900	VNC	Protocol 3.3
6000	X11	X11
6667	IRC	UnrealIRCd
8009	AJP	Apache Jserv
8180	HTTP	Tomcat 5.5

Important Findings

The services found are consistent with the intentionally vulnerable Metasploitable2 environment.

The main security issues identified by the Nmap scripts were:

- **Anonymous FTP login is allowed** on port 21.
- **Telnet, rsh, rlogin and rexec** are exposed and use insecure legacy protocols.
- **SMB signing is disabled.**
- **Multiple outdated services** are running, including Apache, BIND, Samba, MySQL and OpenSSH.
- **Port 1524 exposes a root bind shell**, which is a critical finding in a real environment.
- **MySQL and PostgreSQL** are directly exposed to the network.
- **SSLv2 is supported** by the SMTP service, which is an obsolete protocol.

Comparison with Expected Lab Services

The discovered services match the expected vulnerable services of Metasploitable2. No unexpected host or unrelated system was discovered.

The anomalies are therefore mainly **insecure configurations and intentionally vulnerable/outdated services**, rather than unexpected services.

Conclusion

Nmap successfully identified the open ports, services, and versions on the target. The results confirmed that the machine is the expected Metasploitable2 lab target.

The most important findings were anonymous FTP, insecure legacy services, outdated software, disabled SMB signing, exposed databases, and the root bind shell on port 1524. These findings demonstrate the large attack surface intentionally provided by the lab.