

Task 01: Pointer to 3rd Array Element

```
#include <stdio.h>

int main() {
    int arr[5] = {7, 14, 21, 28, 35};
    int *ptr = &arr[2];

    printf("Value: %d\n", *ptr);
    printf("Address: %p\n", ptr);

    return 0;
}
```

Task 02: Pointer Arithmetic

```
#include <stdio.h>

int main() {
    int arr[5] = {2, 4, 6, 8, 10};
    int *ptr = arr;

    printf("3rd element: %d\n", *(ptr + 2));
    return 0;
}
```

Task 03: Swap Using Pointers

```
#include <stdio.h>

void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

int main() {
    int x = 11, y = 22;
    swap(&x, &y);

    printf("x = %d, y = %d\n", x, y);
    return 0;
}
```

Task 04: Sum of Array

```
#include <stdio.h>

int main() {
    int arr[5] = {3, 6, 9, 12, 15};
    int sum = 0;
    int *ptr = arr;

    for(int i = 0; i < 5; i++) {
        sum += *(ptr + i);
    }

    printf("Sum = %d", sum);
    return 0;
}
```

```
}
```

Task 05: Maximum Value

```
#include <stdio.h>

int main() {
    int arr[5] = {45, 12, 78, 34, 23};
    int *ptr = arr;
    int max = *ptr;

    for(int i = 1; i < 5; i++) {
        if(*(ptr + i) > max)
            max = *(ptr + i);
    }

    printf("Max = %d", max);
    return 0;
}
```

Task 06: Reverse Array

```
#include <stdio.h>

int main() {
    int arr[5] = {1, 3, 5, 7, 9};
    int *ptr = arr;

    for(int i = 4; i >= 0; i--) {
        printf("%d ", *(ptr + i));
    }

    return 0;
}
```

Task 07: Count Even Numbers

```
#include <stdio.h>

int main() {
    int arr[5] = {10, 21, 32, 43, 54};
    int count = 0;

    for(int i = 0; i < 5; i++) {
        if(arr[i] % 2 == 0)
            count++;
    }

    printf("Even numbers = %d", count);
    return 0;
}
```