

CENG 789 – Digital Geometry Processing

05- Mesh Comparison (Distance, Descriptor and Sampling)

Prof. Dr. Yusuf Sahillioğlu

Computer Eng. Dept,  **MIDDLE EAST TECHNICAL UNIVERSITY**, Turkey

Distances

2 / 48

- ✓ **Euclidean** vs. **Geodesic** distances.
- ✓ Euclidean geometry: Distance between 2 points is a line.
- ✓ Non-Euclidean geom: Distance between 2 points is a curvy path along the object surface.
- ✓ Geometry of the objects that we deal with is non-Euclidean.
- ✓ Same intrinsically, different extrinsically:




- ✓ We use intrinsic geometry to compare shapes as the understanding of a finger does not change when you bend your arm.

Geodesic Distance

3 / 48

- ✓ Intrinsic geometry is defined by geodesic distances: length of the shortest (curvy) path (of edges) between two points.



Geodesic Distance

4 / 48

- ✓ Compute with Dijkstra's shortest path algorithm since the mesh is an undirected graph.

DIJKSTRA(G, w, s)

```
1 INITIALIZE-SINGLE-SOURCE( $G, s$ )
2  $S = \emptyset$ 
3  $Q = G.V$ 
4 while  $Q \neq \emptyset$ 
5      $u = \text{EXTRACT-MIN}(Q)$ 
6      $S = S \cup \{u\}$ 
7     for each vertex  $v \in G.Adj[u]$ 
8         RELAX( $u, v, w$ )
```

RELAX(u, v, w)


```
1 if  $v.d > u.d + w(u, v)$ 
2      $v.d = u.d + w(u, v)$ 
3      $v.\pi = u$ 
```

- ✓ $v.d$ is the shortest-path estimate (from source s to v).
- ✓ $v.\pi$ is the predecessor of v .
- ✓ Q is a min-priority queue of vertices, keyed by their d values.
- ✓ S is a set of vertices whose final shortest paths from s is determined.
- ✓ $O(V \log V + E)$ w/ min-heap; $O(V^2 + E)$ w/ array; $E = O(V)$, discard.


Geodesic Distance

5 / 48


- ✓ The execution of Dijkstra's algorithm (on a directed graph):




(a)




(b)




(c)



(d)



(e)



(f)

Geodesic Distance

6 / 48

- ✓ A* search is an interesting alternative to Dijkstra in which shortest-path estimate value + a heuristic value towards the goal is considered.

$$f(n) = g(n) + h(n)$$

$g(n) :=$ cost to get from initial state to n

$h(n) :=$ heuristic estimate of cost to get from n to goal

- ✓ See <https://youtu.be/ySN5Wnu88nE> for a gentle introduction.

Geodesic Distance

7 / 48

- ✓ A* search is an interesting alternative to Dijkstra in which shortest-path estimate value + a heuristic value towards the goal is considered.




- ✓ Heuristic: Euclidean dist to the red target. Start: green. Visited: purple.


Geodesic Distance

8 / 48


- ✓ Does the path really stay on the surface?
- ✓ Yes, but could have been better if it could go through faces.



Euclidean distance



Geodesic distance




Geodesic on high-reso


Geodesic Distance

9 / 48

- ✓ Does the path really stay on the surface?
- ✓ Yes, but could have been better if it could go through faces.



Euclidean distance




Geodesic distance

Geodesic Distance

10 / 48

- ✓ Does the path really stay on the surface?
- ✓ Yes, but could have been better if it could go through faces.




Try to add virtual (blue) edges if the 4 triangles involved are nearly co-planar.

Geodesic Distance

11 / 48

- ✓ Fast marching algorithm for more flexible (and accurate) face travels.
 - ✓ R. Kimmel and J. A. Sethian. Computing geodesic paths on manifolds, 1998.





- ✓ Shortcut edge (blue on prev slide) allows face travel starting from a face vertex.
- ✓ Fast marching allows face travel starting from an arbitrary pnt on the face edge.

Geodesic Distance

12 / 48

- ✓ Exact and approximate algorithms are emerging each year.
- ✓ See Geodesics in Heat, Saddle Vertex Graph, Wavefront Propagation.



Geodesic Distance

13 / 48

- ✓ Main disadvantage: Topological noise changes geodesics drastically.



Diffusion Distance

14 / 48

- ✓ Principle: diffusion of heat after some time t .
 - ✓ Geodesic: length of the shortest path.
 - ✓ Diffusion: average over all paths of length t .



Euclidean



Geodesic




Diffusion

Diffusion Distance

15 / 48

- ✓ Principle: diffusion of heat after some time t .
- ✓ Take a hot needle; touch it to a surface point; watch how heat diffuses out over a time t .



Diffusion Distance

16 / 48

- ✓ Principle: diffusion of heat after some time t .
- ✓ $k_t(x,y)$ = probability of Brownian motion of heat starting at point x to be at point y after some time t .



Diffusion Distance

17 / 48

- ✓ Principle: diffusion of heat after some time t .
- ✓ $k_t(x,y)$ = amount of heat transferred from x to y in time t .



Diffusion Distance

18 / 48

- ✓ Principle: diffusion of heat after some time t .
- ✓ $k_t(x, y)$ = amount of heat transferred from x to y in time t .
- ✓ $k_t(x, x)$ = amount of heat remaining at x after time t .

$$k_t(x, y) = \sum_i \exp(-t\lambda_i) \phi_i(x) \phi_i(y)$$

λ_i, ϕ_i eigenvalues/eigenfunctions of the LB operator.



Diffusion Distance

19 / 48

- ✓ Principle: diffusion of heat after some time t .
- ✓ $k_t(x,y)$ = amount of heat transferred from x to y in time t .
- ✓ Intuitively, $k_t(x,y)$, aka the heat kernel, is a weighted average over all paths between x and y possible in time t , which should not be affected by local perturbations of the surface (small topology noise).



Geodesic Distance


20 / 48

- ✓ What can we do with this geodesic?
- ✓ Descriptor.
- ✓ Sampling.
- ✓ Similarity comparisons.
- ✓ ..

Shape Descriptors

21 / 48

- ✓ Local (vertex-based) vs. Global (shape-based) shape descriptors.




- ✓ Desired properties:
 - ✓ Automatic
 - ✓ Fast to compute and compare
 - ✓ Discriminative
 - ✓ Invariant to transformations (rigid, non-rigid, ..)

Shape Descriptors

22 / 48

- ✓ A toy global descriptor: $F = [x_1, y_1, z_1, x_2, y_2, z_2, \dots, x_n, y_n, z_n]$.






- ✓ Desired properties:
 - ✓ Automatic??
 - ✓ Fast to compute and compare??
 - ✓ Discriminative??
 - ✓ Invariant to transformations (rigid, non-rigid, ..)??

Shape Descriptors

23 / 48

- ✓ A toy global descriptor: $F = [\text{numOfHandles}]$. //computable by Euler's formula.




Shapes	Shape Descriptor
	$F_1 = [f_1, f_2, \dots, f_n]$
	$F_2 = [f_1, f_2, \dots, f_n]$
	$F_3 = [f_1, f_2, \dots, f_n]$
Hopefully $F_2 \neq F_1$ and $F_2 \approx F_3$	

- ✓ Desired properties:
 - ✓ Automatic??
 - ✓ Fast to compute and compare??
 - ✓ Discriminative??
 - ✓ Invariant to transformations (rigid, non-rigid, ..)??


Shape Descriptors

24 / 48

- ✓ Global descriptors.





shape histograms
area/volume intersected
by each region stored in a
histogram indexed by radius




Shape Descriptors

25 / 48

✓ Global descriptors.



shape distributions
distance between 2 random
points on the surface




angle between 3 random
points on the surface

..

Shape Descriptors

26 / 48


- ✓ Yet another global descriptor: LightField Descriptor
- ✓ 10 silhouette images rendered from vertices of a hemisphere.
 - ✓ Rotation-invariant.



Shape Descriptors

27 / 48


- ✓ Yet another global descriptor: LightField Descriptor
- ✓ 10 silhouette images rendered from vertices of a hemisphere.
 - ✓ Rotation-invariant.



Shape Descriptors

28 / 48

- ✓ Yet another global descriptor: LightField Descriptor
- ✓ 10 silhouette images rendered from vertices of a hemisphere.
 - ✓ Rotation-invariant.




- ✓ Dissimilarity b/w two 3D models:
$$D_A = \min_i \sum_{k=1}^{10} d(I_{1k}, I_{2k}) .$$

Shape Descriptors





29 / 48

- ✓ Global descriptor for pairwise sim.: Hausdorff distance b/w 2 models.
- ✓ Find closest pnts of each red (min), and then each blue (min). Pick the max of the most widely separated closest pnts (max).

$$H(P, Q) = \max \left(\max_{p \in P} : \min_{q \in Q} : |pq|, \max_{q \in Q} : \min_{p \in P} : |pq| \right)$$



- ✓ Advantage: considers all boundary points, mutual proximity.
- ✓ Disadv: sensitive to outliers; sometimes unnatural (not rigid invariant).




- ✓ Can be made transf-invariant if minimized through all transformations.

Shape Descriptors

30 / 48

- ✓ Global descriptor for pairwise sim.: Chamfer distance b/w 2 models.
- ✓ Find closest pnts of each red (min), and then each blue (min). Pick the sum of these sums, i.e., replace max of Hausssdorf w/ additions.



a.k.a Chamfer distance (CD)

$$d_{CD}(S_1, S_2) = \sum_{x \in S_1} \min_{y \in S_2} \|x - y\|_2^2 + \sum_{y \in S_2} \min_{x \in S_1} \|x - y\|_2^2$$

- ✓ Intuitively may appear more robust to outliers, still quite sensitive.


Shape Descriptors

31 / 48

- ✓ Global descriptor for pairwise sim.: Earth Mover's dist. b/w 2 models.
- ✓ Cost of changing one shape to another.



- ✓ Measure total length of matched dists, minimized over all bijections.
- ✓ May be more natural than Hausdorff, but harder to compute.
- ✓ Points may have weights.




a.k.a Earth Mover's distance (EMD)

$$d_{EMD}(S_1, S_2) = \min_{\phi: S_1 \rightarrow S_2} \sum_{x \in S_1} \|x - \phi(x)\|_2 \quad \text{where } \phi : S_1 \rightarrow S_2 \text{ is a bijection.}$$


Shape Descriptors

32 / 48

- ✓ Global descriptor to a local descriptor: center it about p .




- ✓ Count points in different sectors of a sphere: shape contexts.



Shape Descriptors

33 / 48

- ✓ Global descriptor to a local descriptor: center it about p .
- ✓ Spin Images: Count 3D points falling inside that solid ring.
 - ✓ Go this far in normal direction, and this far in radial direction.




- ✓ Shape contexts in the following part of this video

Shape Descriptors

34 / 48


- ✓ Local shape descriptors.

Curvature




$$K(v_i) = \left(2\pi - \sum_{j: v_j \in \mathcal{N}_1(v_i)} \theta_j^i \right)$$

Average Geodesic Distance



sum of geodesics from
v to all other vertices.

Shape Diameter (SDF)



sum of ray lengths from v.

Shape Descriptors

35 / 48


- ✓ Local shape descriptors.

Intrinsic Girth Function



Shortest geodesic starts & ends at p .

Combine with SDF to detect plate/tube



IGF



SDF



plate | tube

Big $IGF(p)$, small $SDF(p)$ → plate


Small $IGF(p)$, small $SDF(p)$ → tube

Shape Descriptors

36 / 48

- ✓ Local shape descriptors.

Geodesic Iso-Curve Signature




Shape Descriptors

37 / 48

- ✓ Local shape descriptors.

Bilateral Maps




Sampling

38 / 48

- ✓ Subset of vertices are sampled via


Uniform sampling




Evenly-spaced sampling



Curvature-oriented evenly-spaced sampling



Farthest-point sampling (FPS)




- ✓ Uniform sampling: Pick triangles w/ probabilities proportional to their areas; then put a random sample inside the picks.
- ✓ FPS: Eldar et al., The farthest point strategy for progressive image sampling.

Sampling

39 / 48

- ✓ FPS idea.
 - ✓ You have V vertices and N samples; want to sample the $(N+1)$ st.
 - ✓ $V-N$ candidates.
 - ✓ Each candidate is associated with the closest existing sample.
 - ✓ Remember the distance used in this association.
 - ✓ As your $(N+1)$ st sample, pick the candidate that has the max remembered distance.
-
- ✓ If geodesic distance is in use (more accurate):
 - ✓ $O(NV + NV\log V) = O(NV\log V)$ complexity.
 - ✓ Else if Euclidean distance is in use:
 - ✓ $O(NV)$ complexity.
 - ✓ Cost of finding the max distance for each new sample: $O(NV)$, no additional Dijkstra geodesic computation.



Sampling

40 / 48

- ✓ Can we get this sampling via FPS?




Sampling

41 / 48

- ✓ Can we get this sampling via FPS?




- ✓ No.
- ✓ Use local maxima of Average Geodesic Distance descriptor
- ✓ Use local maxima of heat kernel signature (Slide 16), a multiscale descriptor similar to Geodesic Iso-Curves.



An Application: Shape Correspondence

42 / 48

- ✓ Feature-based and/or distance-based algorithms for shape correspondence, an important problem in computer graphics.



An Application: Shape Correspondence

43 / 48

- ✓ Feature-based: match the points with close feature descriptors.
- ✓ Pointwise term, i.e., involves 1 point at a time.

$$\text{Dis}_l(\varphi) = \sum_{x \in X} d_F(f^X(x), f^Y(\varphi(x)))$$

An Application: Shape Correspondence

44 / 48

- ✓ Distance-based: match 2 points with compatible distances.
- ✓ Pairwise term, i.e., involves 2 points at a time.


$$\text{Dis}_q(\varphi) = \sum_{x, \tilde{x} \in X} |d_X(x, \tilde{x}) - d_Y(\varphi(x), \varphi(\tilde{x}))|$$

An Application: Shape Correspondence

45 / 48

- ✓ Feature- and distance-based: a combination of both.


$$\text{Dis}(\varphi) = \sum_{x \in X} d_F(f^X(x), f^Y(\varphi(x))) + \lambda \cdot \sum_{x, \tilde{x} \in X} |d_X(x, \tilde{x}) - d_Y(\varphi(x), \varphi(\tilde{x}))|$$



An Application: Shape Correspondence

- ✓ Let's see a useful pairwise term in action.
 - ✓ Copied from my paper talk: A Genetic Isometric Shape Correspondence Algorithm with Adaptive Sampling, SIGGRAPH Asia, 2018.

$$\mathcal{D}_{\text{iso}}(\phi) = \frac{1}{|\phi|} \sum_{(s_i, t_j) \in \phi} \frac{1}{|\phi'|} \sum_{(s_l, t_m) \in \phi'} |d_g(s_i, s_l) - d_g(t_j, t_m)|$$




A bad/high-distortion map.

$$|.34 - .98| = .64 \quad \text{☹}$$

An Application: Shape Correspondence

47 / 48

- ✓ Interpolation of a sparse correspondence into a dense one.
- ✓ Compute for each vertex on M1 the geodesic distances to all sparse correspondence points on M1, and then establish a correspondence to the vertex on M2 with the most similar distances to sparse correspondence points on M2.



Potential Project Topics

48 / 48

- ✓ Implement paper: Constant-Time All-Pairs Geodesic Distance Query On Triangle Meshes (Figure in Slide 12).
- ✓ Implement paper: Intrinsic Girth Function for Shape Processing.
- ✓ Given the shape, computing the descriptor is easy. How about the inverse problem: given the descriptor(s), compute the shape?
 - ✓ Inspiration: these slides and/or some Shape Registration slides.