

ME 536 – Design of Intelligent Machines

Term Project - Defect Finder Camera

Presenter: Çağdaş Güven

ID:2738938

Date: 30/01/2025

Github:

https://github.com/amnessa/MECH536/tree/e4cba326a3cc35476c5539c02b752f3d851cce0e/me_term_project

Fall 2024 - METU

Introduction & Problem Statement

- In a production line a camera system detect surface defects
- Technician reports a new defect



How It Meets Project Requirements

- Principal Component Analysis - PCA
- Clustering - (K- means)
- A bit of Image Processing - (histogram equalization and resizing)
- Artificial Neural Networks - ANN (VGG16 fc1 layer)




figure 1 - old data cluster representation





figure 2 - Histogram Equalization to spread intensities and enhance contrast

Data & Generation

- North East University Dataset for Defect Detection - NEU Dataset
- Histogram Equalization
- Resize
- Store



Methods & Network Structure

- VGG16 pretrained on ImageNet
- Filter out features
- PCA 4096 \rightarrow 50 (SVD = Full)
- “Whitening in PCA so each principal component has unit variance, preventing large components from dominating.”
- Result: 5 clusters

```
1 fcl_extractor = layer_extractor()
2 fcl = fcl_extractor.predict(images, verbose=True)
3
4 # save results
5 results = {'filename': files,
6           'features': fcl,
7           'labels': labels,
8           'layer_name': 'fcl'
9           }
10
11 feature_dir = Path('..', 'data', 'features')
12 os.makedirs(feature_dir, exist_ok=True)
13 with open(feature_dir / 'VGG16_fcl_features_std.pickle', 'wb') as f:
14     pickle.dump(results, f)
15
16 print(fcl.shape)
```

figure 3 - code part for feature extraction




figure 4 - t-SNE and scatter plot images for cluster confirmation

Novelty Detection Approach

- New Batch of 40 image
- Same preprocess (ANN fc1-PCA - Kmeans)
- Old cluster centers , New cluster centers
- Automatically detect the novel and cluster it




figure 5 - example new data mixed with old
both are member of the same defect class in
real life

Results & Demo

```

1 #####
2 # MAIN USAGE
3 #####
4
5
6 # (1) Load base data (fc1 => shape(N,4096))
7 from pathlib import Path
8 import pickle
9
10 fc1_path = Path('.', 'data', 'features', 'VGG16_fc1_features_std.pickle')
11 with open(fc1_path, 'rb') as f:
12     base_data = pickle.load(f)
13 fc1 = base_data['features'] # (N,4096)
14 # (Optionally) labels, etc.
15
16 # (2) Build PCA(4096->50) + KMeans(6) on the old data
17 pca, kmeans_50d = build_base_pca_kmeans(fc1, n_components=50, k=6)
18
19 # (3) Construct system
20 system = NoveltyDetectionSystem(pca, kmeans_50d)
21
22 # (4) Load a new batch of images (40)
23 batch_dir = Path("NEU_mixed_batch_40")
24 batch_images = sorted(batch_dir.glob("*.bmp"))
25 if not batch_images:
26     print(f"[WARNING] No images in {batch_dir}!")
27 else:
28     print(f"Found {len(batch_images)} images in new batch.")
29
30     # Extract their fc1
31     new_feats_4096 = system.extract_fc1_batch(batch_images)
32
33     # (5) Find 2 new cluster centers from the new batch (in 50D),
34     #       compare to old 6 centers
35     system.cluster_new_batch_2(new_feats_4096)
36
37     # (Optional) visualize in t-SNE 2D
38     system.visualize_new2_tsne(new_feats_4096)

```

✓ 20.7s

figure 6 - calling system from main

New cluster 0: dist to old center#0 => 3.53 => Crazying
New cluster 1: dist to old center#0 => 7.16 => new class





figure 7 results from testing

Possible Improvements

- Dynamic thresholding
- Dynamic Clustering
- Synthetic generation from dataset
- Sub analysis on clustered new data
- Alternative to Kmeans

Ending & Questions



- Thank you for listening !



References

- 1- Cohn, R., Holm, E. Unsupervised Machine Learning Via Transfer Learning and k-Means Clustering to Classify Materials Image Data. Integr Mater Manuf Innov 10, 231–244 (2021). <https://doi.org/10.1007/s40192-021-00205-8>
- 2- van der Maaten L, Hinton G (2008) Visualizing data using t-SNE. J Mach Learn Res 9:2579–2605. <http://www.jmlr.org/papers/v9/vandermaaten08a.html>
- 3- Pelleg D, Pelleg D, Moore A (2000) X-means: extending K-means with efficient estimation of the number of clusters. In: Proceedings of the 17th international conf. on machine learning, pp 727–734. <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.19.3377>
- 4- Pedregosa F et al. (2011) Scikit-learn: machine learning in python. J Mach Learn Res 12:2825–2830. <http://jmlr.csail.mit.edu/papers/v12/pedregosa11a.html>
- 5- Francois Chollet and Etc. Keras. 2015. <https://keras.io>
- 6- van der Walt S et al (2014) scikit-image: image processing in Python. PeerJ 2, e453. <https://doi.org/10.7717/peerj.453>. <https://peerj.com/articles/453>
- 7- Xiao M et al (2017) An evolutionary classifier for steel surface defects with small sample set. Eurasip J Image Video Process 2017(1):48. <https://doi.org/10.1186/s13640-017-0197-y>
- 8- Gao Y et al (2020) A semi-supervised convolutional neural network-based method for steel surface defect recognition. Robot Comput Int Manuf 61:101825. <https://doi.org/10.1016/j.rcim.2019.101825>
- 9- Metal Surface Defects <https://www.kaggle.com/code/kirollosashraf/metal-surface-defects>
- 10- Zhao, Weidong, Chen, Feng, Huang, Hancheng, Li, Dan, Cheng, Wei, A New Steel Defect Detection Algorithm Based on Deep Learning, Computational Intelligence and Neuroscience, 2021, 5592878, 13 pages, 2021. <https://doi.org/10.1155/2021/5592878>

EXTRAS



variance preserved by 50 components: 0.741

