Quick access tool bar.	(Autosave, Mail box)
Ribbons	Home, Insert.
Features.	Condⁿ form., Bold.
Categories	Number, Font, Style.
Name box	A1
Formula box	live broadcast of Excel.
Cell.	☐
Range.	▦
Sheet Name.	



features :: less time consume, fail at complex sc., not self update
function : more time, complex scenario ✓, self up date

① Flash fill (CTRL+E) : merging or splitting of data.

name	class.	Merge-column.
Aman	2	Aman2
Ajay	4	☐
Diya	3	

☐ ✗ select → home. → Editing → ⊡⊙ flash fill.

or.

☐ ✗ CTRL + E //.

Date Error:

	Date	Month	Year.
19/09/18	19	09 error	
3/11/17	☐	=9	
4/02/18.	function	error.	

→ '09
'11
'02
☐ ← CTRL + E

Flash fill fail : • 19/03/18
14/11/22

March → CTRL + E Con

- Currency
- Calculation not possible. (use Function & formula)

② Remove Duplicates :

Select full data. → Data (Ribbon) → Remove Dup.

Customer ID
eg: Row having same customer id.

single column

multi column → Customer ID | Gender
Remove repeating customer id only if gender also same.

③ Text to Column. → ○ Fix width. → ○ Delimited.

OD
19/09/18
13/03/17

Date Month Year.

• select full data/column. → Data (Ribbon) → text to column → ◉ Fix width → select range.

19 | /09/ | 18
13 | /03/ | 17

→ Select destination → finish,

date	Month	year.
19	/09/	2018
13	/03/	2017.

• Text to column ◉ Delimited.

→ In fix width Range used ⇒ 19 | /09/ | 18
17 | /03/ | 17.

→ In delimited sign = delimiter

Eg: Aman Sharma. Khushi Chaudhary → select → text to column → Delimiter = space. → select destination

Eg: for date : delimiter = /

Fail of Text to column.

• extract of values : apple cost 1.2 USD
42 INR is auto fail.
USD 95 is his fees

• Date Month Date Year.
3/4/15 18
4/12/18 17.

Apply Delimiter → Error (have to replace year or column).

Sheet Management. ①. Right click → Rename.
→ Add sheet
→ hide / unhide
→ move / copy (Duplicate)
→ Delete.

Sheet 1 | Sheet 2 ⊕

② Auto fit column width.

Aman Sin | Khushi C → select column or full data. (CTRL+A)

home → format → auto fit column width.
auto fit Row width.

③ Selecting full Row:



select → CTRL + Shift + →

i. apply desired format like alignment ☰ ☰ B, I

ii. to format all rows → format painter (clipboard)
continue (i) → CTRL + Shift + ↓ (OK).

④ Copy Paste.
Select full data or table by shortcuts.

- Copy + paste → full formats + formula.
- Copy & paste value → only value paste
- Copy as image → for prints also.
- Copy + linked paste → Δ main table = Δ Pasted.
- Copy + paste special (skip blanks)


New
old
New
copy
paste skip
old
update (only some cell)

- Copy and paste by performing operation on them.

old	New
750	750
420	420

but new must be 835, 495.


pasted
old
old
114%

- select cell of 114% → copy.
- select the column where to paste ® paste special.
→ Multiplies.
→ Values.

⑤ Freeze unfreeze

Select any data cell → View → ⊛ freeze top Row
⊛ freeze top Column
⊛ freeze Planes.


fix
all above fix
all left side fixed
selected cell

⑥. Merging.


Cust Info
First N
Last N.

→ select → home → merge & center.


Cust Info
First N
Last N

select → home → merge & centre
alignment → ☰.



OK ← select → format painter
all column
(CTRL+Shift+↓)

Filter ▼

- select all data → home → editing → F&S → Filter.

Name ▼ Gender ▼ class ▼ → such sign appear.

---

* Misaligned : Name Gender class

→ select all data → Apply filter ▼ at Right Place ✓.
→ select any cell of data → Apply filter, ▼ at Right Place.
→ select empty area along with data → ▼ Name not Nec

• Date filtering (before 7 Jan)

apply filter → contact_date ▼ ① → Date filter → before ↓ Enter 01/07/2024

1-Jan-23
2-Jan-23
!

② → Manually choose.

• time filtering (b/w 10:00:00 AM & 12:00:00 PM)

select all data → filter
time_column ▼ → Number filter → between → ≤ 10:00:00 ≥ 12:00:00

Sorting

Way ① Column Date
1-Jan-23
2-Jan-23
→ select → home → F&S → Sort.

Way ② select all data → filter → ▼ ▼ ▼
↓
sort available

Custom Sorting

Multiple sorting : transaction based on agent & Morning to even
select all data → home → F&S → Custom sorting
Add value ⊕
sort by Agent-name order A-Z
sort by contact-time order small to large.

Marks	Name.	type.
4	Aaran.	Python
7	Radhika	ML
8	Kavita	ML
9	!	!
2	!	!

Marks	type
>5	ML.

← criteria.

Advanced filtering ①

Filter on basis of made data.

- Select main data → Data → Adv Filter
↓
● Filter list in Place.
List Range : Main data. (select)
Criteria Range : select criteria data OK.

Advance Filtering ②

Sheet 1
Main data

Sheet 2
Criteria data
A1

- select A1 (Sheet 2)
- adv. filtering
- Copy to another location
- List Range : Select A1 then open sheet 1 → Select all sheet (CTRL A)
- Criteria Range → Criteria Table (sheet 2)
- Copy to : A1 (Sheet 2) ▶ data will come in A1 of Sheet 2.

Sheet 1
Main data

Sheet 2
Criteria data

Sheet 3
A1

- select A1 of Sheet 3
- adv filtering
- Copy to another
- List Range : A1 (Sheet 1) → Main data select all.
- Criteria Range : Criteria table (Sheet 2)
- Copy to A1 of Sheet 3 ▶

Data Validation :

Can enter data in cell of any particular row
if it is valid

① Length.

must ≥ 9

Bank name

select → data (Ribbon) → Data tools (category)

allow [text length] ← DV

≤ 9

make such validation on full Column.
- → make data validation on particular cell.
- → copy (CTRL+C) that cell.
- → select all desired cells / column.
- → CTRL +V.

OR :

apply DV on cell → format painter → select rest cell/col

---

② allow only dates :

[after 20th December] [Before 15 Jan]

Tour start date   Tour end date

select → dV → allow : date
data : greater than
Start date : 20/12/23

Setting   title   Error Message

allow   Input message : title :   Title : Error : Msg

③ allow only time

data validation → allow : time
data : >
Start time : 11:00:00 AM.

④ allow on '%'

dV → allow : decimal.
: greater than
: 0.35

- [0.44] enter → [0.44] valid.
- [44%] enter → [44%] valid.
- [0.44] enter → [44%]

⑤ allow only list ;

Pizza, burger, fries only order item | choose from table H order item.

dV → allow : list
source : pizza, burgers, fries

dV → allow : list
source : select full H table / column.

→ order item 1   order item 2

⑥ Data allow Custom (AI chatgpt).

STU XXXX   Current Date | @gmail.com.

Student ID   Date

F7.

dV → allow : custom.
formula : chatgpt.

Prompt : I need validation formula for excel. for student ID.
Eg : STU4926 → first 3 STU Next numeric.
This is for cell address F7 & will copy for other rows as well → give me custom Rule for this situati

Pivot Table , Data Analysis

Source data → backend (Calculation / Conversion) → front end (Display).

- Select Maindata → Insert → Pivot Table.

Table Range: [Select Main sheet]

● New worksheet
○ Existing
] your choice.

location: Sheet 3 or sheet name.

Pivot Table field

- select column : ☐ Sales ☐ price ☐ xyz.

Drag

Filter. | column
Raw | values.

Drag → Sum Sales' | 502691

Sales ● → Rename: Sum Sa

→ Sum, Product, avg, max, min, Produ, Coun

- select column : ☐ account-name. ☐ sales ☐ price ☐ xyz.

Drag

Filter. | column
Raws | value.

● sales → avg
● price → sum

Account-name	Avg Sale	tot
Aman	2002	924
Khushi	2001	
Total		

- Filling column.

only Raw & value ⇒

Account	Sales
Aman	2002
Khushi	
Total	

Raw & value & column (Course type) →

	Course types		
Account	ML sale	AI course	
Aman			
Khushi			
Total			

- copy column, cell → paste in pivot → not allow
# make change direct in pivot like rename etc.

- Sorting in pivot table.

account ● | Sales
Aman
Khushi

Way 1 → Right click → sort

Way ② → Click → More sort option
○ Ascending A to Z by [Product name.]
● Decending Z to A by [Product name ●] → Sales
OK

- Label filter
* Contains.

Eg: filter out Sharmas from list.

account ● | Sales
Aman Sharma
Khushi Chaudhary

→ Click → Label filter → contains
[contains] [Sharma]
OK

- Value filtering
*

Eg: filter out Sales > 1000

account ● | sales
→ click → value filter → ≥ → [Sales] [≥] [1000]
OK

- Report filtering
- back to filling column table :
Take out only for ML Sales

→ Filter [ ] Course-type →

Course type	ML
Account	sales
Aman	
Khushi	

When Row = date → Row = Day( ) Month( ) } ⇒ New automation

Sale
⊕ Nov
⊕ December → ⊖ Nov 1 2 ⊕ Decem

→ Remove: Day, mon
→ 1- Nov - 20
2- Nov -

Number formatting:

① Product Sales
2.4 → select → Right → No. formatting → Number: Decimal
19.
32.

2.324698 → 2.32
19.624692 → 19.62
32.458674. → 32.45.

② 0.476 → No formatting → percentage → Decimal : 2

Analysis ①.

Row = date
Column = Overall Sale, Avg Rating.
Notice ⇒ ⓐ when sell was more rating was ~~less~~ more
when sell was less Rating was less.

Analysis ②.

Top ③ sales & top ③ Ratings.

Day ⊖ sales Avg Rating → select → Value filter → Top 10
→ Top | 3 | Sales
OK.

copy pivot table → Day ⊖ → select → Value filter → Top 10
Bottom | 3 | Ratings

→ Days Sales Avg Rating

Day Sales Avg Rat

PTA → Pivot Table Analyse (Ribbon)

Δ in Main data.

Δ in Main Data → not change in Pivot.
→ Make Δ in Main Data → open Pivot table → select any cell.
→ Pivot Analyze (Ribbon) → Refresh / Refresh All.

Δ in Main data (Addn of new Row / column)

Select Pivot table any cell → Pivot Table Analyse (Ribbon)
→ change Data Source.
→ ⦿ select a table on Range [Select full table] → ctrl shift → ↓
(OK).
→ Refresh.

~~Ana~~ Analysis ③. (Grouping)

Row = Rating
Column = Sales.

Select 1-2-3 → PTA & → Group Selection
Select 4-5-6 → PTA → Group Selection
Select 7-8-9-10 → PTA → Group Selection

→ Rating Sales
1
2
3
4
5
6
7
8
9
10

→ Rating Sales
⊕ Group①
⊕ Group②
⊖ Group③
7
8
9
10

→ Go in Row = Rating, Rating 2 automatically → Remove Rating & Rename G① G② G③

→ Rating 2 Sales
Poor
Neutral

Table 1 → avg sale account of
Table 2 → model vs Avg price.
Table 3 → type vs sale amount

but wants only detail of these 3 table of specific category or anything.

Male
Female
→ click
↓
now 3 table will give male data only

Slicers (Back to report filter once)

→ this is for one table only
→ for all table in sheet, it fails
→ Slicer.



→ Select → PTA → Insert slicer.
↓
Select for what you want to do. Eg: Country
↓
OK. →



This is only for selected Pivot table.
→ to make it for all

Select Slicer box (already made) on sheet → Slicer (Ribbon) → Report Connection
↓
Select all table

Select → insert Timeline → Contact-date

This will look like

Jan Feb March Ap Ma - - - - Dec Month ∨	#

Click on specific Month for specific month data in these 3 tables.

Conditional Formatting. Home → Conditional Formatting ▾

① Data bars.
- select the value column ▤ → home → CF ▾ → Databars ✓
- " " " → Databars → More Rules → for color, format, & Show bars only.



Show bars only



Customize data bar. (Data bar only for total sale ≥ 25000
- select total sale column ▤ → home → CF ▾ → D Bars
↓
More Rules.

Apply:
⇒ ⦿ all cells showing "Total sales" value for "Product Name"

Minimum : 25000
Value : Number. → OK ⇒



② Color Scales.



Select column data ▤ → home → CF ▾ → Color scale ▾ →
Select req type
or
More Rules

Customize Color scales.
Example: sales data → 3 scale (Color scale) selected
↓
More Rules.

data
20
65
50
74 → Must be white not 50.
90

	Mini	Midpoint	Maximum
Type	Lowest v	Number	highest value.
Value		50✗ 75✓	
Color	Red	White	green.

Page No.

DATE: / /

③ Icon sets

Select column data → home → CF ▾ → Icon sets
↓
Select as per req
or
More Rules



④ high ligh cell Rule.

Example: out of CustomeH ID : highligh Duplicate
: =
: text contain
: ≤ ≥ < > =

• select data column
→ home → CF ▾ → highlight cell Rules
↓
Duplicate ▾ value with Red ▾
OK.

⑤ Top / Bottom Rules.

Select column data → home → CF ▾
↓
Top/Bott ▾

to highlight → top 10 or xy item
bottom 10 or xy item.
top 10% or xy% item
bottom 10% or xy% item
Above Avg
Below Avg
More Rules

Can be applied two or more at one time
→ Top 3 → Red
Bottom 3 → Green

Print & layout.
printing in pdf.

① → Print → Setting
Page orientation → landscape
Type → A4
Margin → Narrow
Scaling → Fit sheet on one Page

② Print Area.


only this part to print

• select Print Area → Page layout (Ribbon) → Print Area ✓
→ Go to Print → apply setting as per req. :)
↓
print selection

③ Just remember. kmy.

xyz xyz ⇒ Merge and centre (demerging)

• Print area → apply page break → print area

Go to print
Page ①] separate page.
Page ②

④ Print titles



→ Print → setting (all orientation check)
→ print title (in Page layout) → Row to repeat at top (select R①)



to apply gridline in printing # → print title
↓
gridelines ✓

⑤ To print full (Condn form applied tables)

headings

• apply print area (dont also include head)
• apply page title : heading = row at top
• → # → vertical centre all print
horiz centre

not to include.

Formula & function.

→ data

Sum

cell (eg: G4)

It will have value of applied func from data (selected Range only)

- Formula
  =A1+A2
- Function
  = SUM (A1, A2)

=sum (A1, B2, C1)

→ here A1, B2, C1
- can be selected cells
- can be Ranges selected
- can be selected cells of diff. sheet
- can be selected ranges of diff sheet

Just =sum (select cell/Range , select next Range - - -).

apply comma

☐ → select cell → Formula (Ribbon) → Insert Fun

→ select Sum → input N1 Cell No. (select)
N2 Cell No (select)
+

OK.

=A1-C2+G4 (cell) OK.

select C2 → =A1-C2+G4
→ F9 press → value of C2 appear.

~~Avg~~

Range / cell of same of diff sheet.

= Average (… , … , …)

Count / Count A

x	y	z
—	2	Amazon
—	4	Microsoft
—	9	Apple
—	6	Google
—	8	Meta

= Count (B2 : B6)
= CountA (C2 : C6)

→ Count (… , … , …) R① R② R③
CountA (… , … , …)



= count (B2 : B6)
→ 4 only.

they ignore Empty cell

eg: # CountA dont ignore column header (eg: account-name) if selected within range. So, select data wisely.

Max. data   max value out of selected values.

= Max (… , … , …)   → Range / cell of same of dif sheets.
= Min (… , … , …)

Absolute or Fixed Referencing

①

A X	B No of order	C Price	Total.
Pizza	2	100	☐ → = B2 * C2 ok.
burger	3	50	
chowmin	4	25	

- Now copy the cell (D2)
- Paste it in all next cells below D2.

→ Total 200 → Paste → 200 150 → Paste 200 150 100

② Absolute & fixed Referencing

Total.
=B2*C2 copying this makes value = B3*C3 , =B4*C4 in pasting.

A Discount X	B D. % order	C Price	Total
P	2	100	☐ → if entered =B3*C3-(B3*C3)*B1
B	3	50	
C	4	25	

while pasting it B1 → B2 that is wrong. to fix B1.

→ =B3*C3 - (B3*C3) * $B$1
B1 fixed.

Named Ranges



- Select full column (header included)
  ↓
  Name box : Enter → xyz-column √Enter

Know unselect that → Name box ▽
↓
xyz-column → select that part now.

=CountA(xyz-column)

another way to make such named Ranges
↓
Select Range → Formulas → Named Manager → New
→ Define name
↓
Name: ∼
OK

to delete it → Named manager
→ select Name → Delete

IF

=IF(Validate logic, what if logic pass, what if logic fails).

Eg:

food quality	company	will I attend?
Good	∼	→ =if(C2="bad","not go","go")
Avg	∼	Enter
Bad	∼	
Good		
⋮		

Copy the cell → Paste in Rest → ok.

And / OR :

Price A	Price B	Price C	xyz
∼	∼	∼	→ =And(B2>C2,C2>A2)
∼	∼	∼	True
			False
			Tr...

↳ if true then True else false.

SumIf.

=SUMIF(Criteria Range, "Criteria", sum Range)

Example

Fruit	Price.	Month
Apple.	∼	Jan
Banana	∼	Feb.
Apple.	∼	⋮
Pineapple	∼	Dec
⋮		

Select cell → (Random)
=Sumif(A2:∼,"Apple",B2:∼)
OK

SUM IF + Wild card

=sumif(A2:∼,"____",B2:∼)

"apple" → fruit must be apple
"*apple*" → must have apple in text (pineapple, apple)
"*apple") → must have apple at end: pineapple or I am apple
"J??" → month starts with
"J*") ↗

Count If

=Sumif(A2:∼,"apple")
↓
3 apple purchase were made)
(3 apple in fruit column

IFS

IFS = IFS(Logic , Value if true , Logic, Value if true..)
output

= IFS(B2 > 6, "Greater than 6", B2 < 3 , "it is less than 3")
↳ check B2 > 6 ? if not, check B2 < 3 .

Sumifs = Sumifs("Select Range", Filter 1 , "filtered 1 object",
Value — Select full column

filter 2 , filtered 2 object)
column

Eq: = Sumifs("B1 : B7", C1 : C7 , "Amazon",
price
D1 : D7 , "March") (# "March" = J7)

• This will give sum of price of all amazon of march.

Eq: = Sumifs(B1 : B7, E1 : E7 , "Kiwi" , F1 : F2,
" ≥ 2022-07-10 ", F1 : F2 ,
" ≤ 2022-07-25 ")

Sum of price of kiwi sold b/w 2022-07-10 & 2022-07-25.

Average IFS

= Averageifs ("Select Range", filter 1 , "filtered 1 object",
Value — column range

filter 2 , "filtered 2 object").

Eq: averageifs (B1 : B7 , K1 : K7 , "*o*").
price — vendor name range — vendor name have o letter.

= MaxIFS (‿ , F1 , FOI , F2 , FO2)
= MIN IFS (~ — —)

= Left = Right = Mid

Aman sharma

Extract first 3 letter : = left(A2 , 3) = Ama.
last 3 letter : = right(A2, 3) = rma.
start at 2 end continue 6 : = mid(A2, 2, 6) = man sh

= Upper (‿) = Lower = Proper.

(A2).
Aman sharma.
= upper (A2) ⇒ AMAN SHARMA.
= lower (A2) = aman sharma.
= proper (A2) = Aman Sharma.

Concat and text Join

Aman | Sharma | Jane street

= concat (A2, B2, C2) ⇒ AmanSharmaJane Street

= concat (A2, "=", B2, "=", C2) ⇒ Aman=Sharma=Jane Street

= text Join ("=", TRUE, A2, B2, C2) ⇒ Aman=Sharma=Jane street

Aman | | Jane Street (Empty cell)

= text Join("=", TRUE, A2, B2, C2) ⇒ Aman=Jane Street

= concat (A2, "=", B2, "=", C2) ⇒ Aman==Jane Street

=today()

Today date | =today() ⇒ 31/12/2024

Day Month Year hour minute second Extract

(A2) 31/12/2024 10:38

=day (A2) → 31

=month (A2) → 12

=Year (A2) → 2024

=hour (A2) → 10

=minute (A2) → 38

=second (A2) → 56

Difference b/w days

Start	End
12/11/24	15/11/24

→ = days (End date, start date)

- if End date = today.

(F2) 31/12/24 ⇒ days ($J$1, A2) (today)

Difference b/w days considering weekend or holidays

= Networkdays (Start, End, [holidays]) → select out of ☐

= Networkdays.intl (Start, End, Weekend predefined no, [holidays]) → ☰

Eg:

Networkdays ("01/01/2024", "10/10/2024",) 08/10/24

→ no. of working days considering holiday at 8/10/24

Networkdays.intl ("01/01/24", "10/10/24", 7,) 8/10/24

→ no of working day considering weekend + holiday both | predefined weekend no. for Friday & sat

VLOOKUP

A First Name	B Price	C Vendor	D Purchase Month
Apple	~		
orange	~		
Kiwi	~		
Apple	~		
Pineapple	~		
Banana			

select all

when all in use & 3 = output

G Vendor	H Fruit Name	I Purchase Month
Amazon	Apple	Jan
Blinkit	orange	
Walmart	Pinapple	
BigBasket	Kiwi	

① = VLOOKUP (A2, G1:H5, 2, FALSE). → Exact value चाहिए?

→ yes → FALSE ③

Apple | G H

G① H②

vendor ~~vendor~~ Fruit

② V-(A3, $G$1:$H$5, 1, False)

For Month

VL (A2, $H$1:$I$5, 2, False

9 (Fill to [illegible] all column

using True.

Person	Date	Money.
	2-7-21	
	19-6-20	
	25-4-18	

G Birth	H P.Money.
1-1-21	400
1-1-20	250
1-1-19	150.

= VLOOKUP (B2, $G$1:$H$4, 2, True)

Approx.

& copy to all

⇒ Money

400 → 2-7-21 come => 1-1-21 (400)

250 → 19-6-20 come => 1-1-20 (250)

N/A → 25-4-18 come => nothing.

Eg.

Numbers.	Cars.
5	[illegible]
10	[illegible]
25	[illegible]
35	[illegible]

Number.	Cars.
8	MO
16	ME
26	ML.

=VLOOKUP (~~~~ True) & copy all

⇒

Number	Cars.
5	N/A
10	MO
25	ME
35	ML.

Eg:



Empty ① & ②

used to fill y (①)

used to fill ② (2)

then Go on

Eg: suppose



in sheet 1



Sheet 2.

=VLOOKUP(A2, Go to sheet 2 → select Range → F4 , 2, False/True)

in sheet 2 formula box only

① index = index(select A1-D4 $, 2, 3) = [~~]

Row of selected

Column of selected.

② match = match (select X in local table, Range of main table, 0)

cell

(column)

give position of selected entry in main table.

Example:



Amazon

tata

ans

Nested function.

④ ≥ 90	"A"
≥ 80	"B"
≥ 70	"C"
< 70	"L"

	A	B	C
1	Name	Mark	GRADE
2		85	
3		74	
4		92	
5		69	
6			

if (C2 >= 90, "A",

else for A

if (C2 ≥ 80, "B",

else for B

if (C2 ≥ 70, "C",

else for C

if ((2 < 70, "L"))))

Eg (R1) = sum(A2:A7)

(R2) ⇒ = sum (B2:B9)

Final R ⇒ = sum(A2:A7) * sum (B2:B9)

or

= product (sum (A2:A7), sum(B2:B9))

CHAT GPT.

text function

→ convert Price column (9.84, 6.85) into Roundoff.

→ Extract Month, Day, AM/PM from Date/Time column

Example: 11/12/24 ⇒ Wednesday / December

16:12 ⇒ PM

→ Make copy of existing column just substitute specific entry

eg:

S M S XL		⇒	XS M XS XL

⇒ Replace Existing

Amazon = Replace (A2, 3, 2, K) ⇒ Amkkon

↳ copy formula paste over full column

→ Switch (formula in main table new update / substitute according to extra table / data)

= switch (A2, J2, K2, A3, J3, K3 - -)

A2 ↓ Main table

J2 ↓ A2 = J2

K2 → New value at A2 (in extra table)

	A
1	~~x~~
2	~~y~~
3	z

J	K
x	u
y	v
z	w

	A
1	u
2	v
3	w

Round off

- Roundoff 7.9 → 8 8.1 → 8
- Roundup 7.9 → 8 8.1 → 9
- Round down 7.9 → 7 8.1 → 8
- Round up to nearest 10 : 492 → 490
  366 → 370

- MROUND (Multiplier)

MROUND without Multip	Multip = 2	= 50.
148.7 → 149	148 (div2)	150
457.2 → 457	458 (div2)	450

- MROUND up = ceiling

148.7	50
	150
457.2	500

- MROUND Down = Floor

Statistical formula. ① Large ② Small.

Value column ⇒ 10, 8, 17, 9 ⇒

highest value = max func

lowest value = min func.

3rd highest = Large (w:w, 3)

3rd lowest = Small (w:w, 3)

③ Rank.

A	B
10	2
8	4
17	1
9	3

B → =Rank (A1, A1:A4)

Page No.
DATE: / /

* **Graphs** :

- Normal
- Clustered
- Stacked

Column



Best

1 Legend

3 Legend

Bar.



1 Legend

3 Legend.



Page No.
DATE: / /

Summary :

① Flash fill Aman Sharma Am
Divya Chomal Di

② Text to column → fix width
→ delimiter (/ or space)

③ Sheet Management. • autofit ▭ width.
• freeze unfreeze.
• copy paste types.
• Merging





④ * Filter : Apply how / dateF / TimeF / Adv.F ① / Adv F ② -
* Sorting , custom sorting (Multiple sorts in one table)

⑤ Data validation. (Length / date (range) / time (range)) / decimal (%) / List / Data custom AI Chat GPT.

Report filter

⑥ Pivot table : Columns, Rows, Values, Filter
Label filter ([illegible]) , Value filter (>1000) , sorting in PT.