

Causal parameter estimation with right-censored data using the state learner


Anders Munch & Thomas Gerdts
Section of Biostatistics, University of Copenhagen



The state learner

The state learner models the observed system as an *artificial* multi-state system where censoring is considered a state. After baseline the observed data can be encoded by the process $\eta(t) \in \{-1, 0, 1, 2\}$ defined as

$$\eta(t) = \mathbb{1}\{T \leq t, D = 1\} + 2 \mathbb{1}\{T \leq t, D = 2\} - \mathbb{1}\{T \leq t, D = 0\}, \quad \text{for } t \in [0, \tau].$$



$$F(t, k, x) = P(\eta(t) = k \mid X = x), \quad \text{for all } t \in [0, \tau], k \in \{-1, 0, 1, 2\}, x \in \mathcal{X}.$$

Performance of a model for F can be estimated directly in the observed data, e.g., using the integrated Brier score,

$$\bar{B}_r(F, O) = \int_0^\tau B_t(F, O) dt, \quad \text{where } B_t(F, O) = \sum_{j=-1}^2 (F(t, j, X) - \mathbb{1}\{\eta(t) = j\})^2.$$

Building a library for state learning




Learners of F are not directly available. However, given libraries of learners of cause-specific cumulative hazard functions Λ_1 and Λ_2 , and a library for learning the cumulative hazard of censoring, denoted by Γ , we can obtain a library of learners for F using the following relations.

$$F(t, 0, x) = P(\bar{T} > t \mid X = x) = \prod_t (1 - [\Lambda_1 + \Lambda_2 + \Gamma](ds \mid x)),$$

$$F(t, j, x) = P(\bar{T} \leq t, \Delta = j \mid X = x) = \int_t^0 F(t-, 0, x) \Lambda_j(ds \mid x), \quad \text{for } j \in \{1, 2\},$$

$$F(t, -1, x) = P(\bar{T} \leq t, \Delta = 0 \mid X = x) = \int_t^0 F(t-, 0, x) \Gamma(ds \mid x),$$

Theoretical and empirical results



Prespecification of estimators for survival and censoring probabilities can be difficult with observational data. Super learning uses the data to decide which estimators best fit the data. Targeted learning can correct the bias stemming from this data-adaptive model selection step, and provide valid post-selection inference for causal parameters.

Motivation

The super learner is a machine learning algorithm which combines a library of prediction models into a meta learner based on cross-validated loss. Unfortunately, the commonly used partial likelihood loss is not suited for super learning, and inverse probability of censoring weighted loss functions require a prespecified estimator of the censoring distribution. To relax this, we introduce the state learner, a new super learner for survival analysis, which evaluates the loss based on the observed data simultaneously using libraries of predictions models for the event(s) of interest and the censoring distribution. We establish an oracle inequality for the state learner and investigate its performance through numerical experiments. We illustrate how the state learner allows us to estimate causal effects in a competing risks setting without having to prespecify models for neither the cause-specific hazards of interest nor the censoring distribution.

not the censoring distribution.

Motivation

Ideal data: $(W, T^0, D^0, T^1, D^1) \sim Q \in \mathcal{Q}$

$W \in \mathcal{W} \subset \mathbb{R}^d$ is a vector of covariates, $T^a \in [0, \tau]$ is a counterfactual time to event variable under treatment a , and $D^a \times \{1, 2\}$ denotes the cause of the event. The maximal length of followup is $\tau < \infty$.


Observed data: $(W, A, \bar{T}, \bar{D}) \sim P \in \mathcal{P}$

$A \in \{0, 1\}$ is a binary treatment administered in observed data. The pair (\bar{T}, \bar{D}) is the censored outcome variable, defined as $\bar{T} = T^a \wedge C^a$ and $\bar{D}^a = \mathbb{1}\{T^a \leq C^a\} D^a$, when $A = a$, for some censoring time C^a .

Problem statement

Targeted estimation of causal effects such as the average treatment effect rely on estimators of the cause-specific cumulative hazard functions,

$$\Lambda_j(t \mid w, a) = \int_t^0 Q(T^a \in ds, D^a = j \mid W = w) \frac{Q(T^a \geq s \mid W = w)}{Q(T^a = w)}, \quad j \in \{1, 2\},$$




and the censoring probability. Assuming coarsening at random [2, 9], the cause-specific hazard functions and the censoring probability can be estimated based on samples from P . Many existing methods are available for this task, including the Nelson-Aalen estimator, Cox models, random survival forests, Poisson regression, neural networks, and many others.

A super learner can be used to data-adaptively select a method from a library of candidates. Super learning uses cross-validation to estimate and evaluate the performance of each learner in the library using a given loss function. Our focus in this work is on how a super learner can assess the performance of a learner in a right-censored validation set.

Existing methods

A commonly used loss function in survival analysis is the negative partial log-likelihood loss. This loss is unsuited for super learner because many common survival estimators will have infinite loss in any hold out sample as illustrated in the figure below to the right. Alternative methods such as inverse probability of censoring weighting [4, 3], pseudo-observations [1, 7], and censoring unbiased transformations [8] rely on a pre-specified estimator of the censoring probability. This can lead to a circular reasoning as illustrated in the figure below to the right. A recent proposal in a context without competing events is based on iterative estimation of the survival and the censoring probabilities in the hope that this is not a vicious circle [10].



[1] Per Kragh Andersen, John P Klein, and Susanne Rosenthal. Generalised linear models for correlated pseudo-observations, with applications to multi-state models. *Biometrika*, 2003.

[2] Richard D Gill, Mark J van der Laan, and James M Robins. Coarsening at random: Characterizations, connections, counter-examples. In *Proceedings of the First Seattle Symposium in Biostatistics*, 1997.

[3] Pablo Gonzalez Ginesier, Alex Kottlik, David M Vock, Julian Wolfson, and Erin E Gabriel. Stacked inverse probability of censoring therapy in prostate cancer. *Journal of clinical oncology*, 2000.

[4] Erika Graf, Claudia Schmoor, Willi Sauerbrei, and Martin Schumacher. Assessment and comparison of prognostic classification schemes for survival data. *Statistics in medicine*, 1999.

[5] Michael W Kattan, Michael J Zelefsky, Patrick A Kupelian, Peter T Scardino, Zvi Fuks, and Steven A Leibel. Pre-treatment nomogram for predicting the outcome of three-dimensional conformal radiotherapy in prostate cancer. *Journal of clinical oncology*, 2000.

[6] Anders Munch and Thomas Gerdts. The state learner—a super learner for right-censored data. *Preprint*, 2024.

[7] Michael C Sachs, Andrea Discacciati, Åsa H Everhov, Ola Olén, and Erni E Gabriel. Ensemble prediction of time-to-event outcomes with competing risks: A case-study of surgical complications in Crohn’s disease. *Journal of the Royal Statistical Society Series C: Applied Statistics*, 2019.

[8] Jon Arni Steingrimsdóttir, Liqun Diao, and Robert L Strawderman. Censoring unbiased regression trees and ensembles. *Journal of the American Statistical Association*, 2023.

[9] Mark J van der Laan and James M Robins. *Unified methods for censored longitudinal data and causality*. Springer Science & Business Media, 2003.

[10] Ted Westling, Alex Luedtke, Peter Gilbert, and Marco Carone. Inference for treatment-specific survival curves using machine learning. *Journal of the American Statistical Association*, 2019.