

EAP Authentication with RADIUS Server

Document ID: 44844

Refer to the Cisco Wireless Downloads in order to get Cisco Aironet drivers, firmware and utility software.

Introduction

Prerequisites

Requirements

Components Used

Conventions

Configure

Network EAP or Open Authentication with EAP

Define Authentication Server

Define Client Authentication Methods

Verify

Troubleshoot

Troubleshoot Procedure

Troubleshoot Commands

NetPro Discussion Forums – Featured Conversations

Related Information

Introduction

This document provides a sample configuration of a Cisco IOS® based access point for Extensible Authentication Protocol (EAP) authentication of wireless users against a database accessed by a RADIUS server.

Due to the passive role that the access point plays in EAP (bridges wireless packets from the client into wired packets destined to the authentication server, and vice versa), this configuration is used with virtually all EAP methods. These methods include (but are not limited to) LEAP, Protected EAP (PEAP)–MS–Challenge Handshake Authentication Protocol (CHAP) version 2, PEAP–Generic Token Card (GTC), EAP–Flexible Authentication via Secure Tunneling (FAST), EAP–Transport Layer Security (TLS), and EAP–Tunneled TLS (TTLS). You must appropriately configure the authentication server for each of these EAP methods.

This document covers how to configure the access point (AP) and the RADIUS server, which is Cisco Secure ACS in the configuration example in this document.

Prerequisites

Requirements

Ensure that you meet these requirements before you attempt this configuration:

- You are familiar with the Cisco IOS GUI or CLI.
- You are familiar with the concepts behind EAP authentication.

Components Used

The information in this document is based on these software and hardware versions:

- Cisco Aironet AP products that run Cisco IOS.
 - Assumption of only one Virtual LAN (VLAN) in the network.
 - A RADIUS authentication server product that successfully integrates into a user database.
 - ◆ These are the supported authentication servers for Cisco LEAP and EAP-FAST:
 - ◇ Cisco Secure Access Control Server (ACS)
 - ◇ Cisco Access Registrar (CAR)
 - ◇ Funk Steel Belted RADIUS
 - ◇ Interlink Merit
 - ◆ These are the supported authentication servers for the Microsoft PEAP-MS-CHAP version 2 and PEAP-GTC:
 - ◇ Microsoft Internet Authentication Service (IAS)
 - ◇ Cisco Secure ACS
 - ◇ Funk Steel Belted RADIUS
 - ◇ Interlink Merit
 - ◇ Any additional authentication server Microsoft can authorize.
- Note:** GTC or One-Time Passwords require additional services which require additional software on both the client and server side, as well as hardware or software token generators.
- ◆ Consult the manufacturer of the client supplicant for details on which authentication servers are supported with their products for EAP-TLS, EAP-TTLS and other EAP methods.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

Refer to the Cisco Technical Tips Conventions for more information on document conventions.

Configure

This configuration describes how to configure EAP authentication on an IOS based AP. In the example in this document, LEAP is used as a method of EAP authentication with RADIUS server.

Note: Use the Command Lookup Tool (registered customers only) to obtain more information on the commands used in this section.

As with most password-based authentication algorithms, Cisco LEAP is vulnerable to dictionary attacks. This is not a new attack or new vulnerability of Cisco LEAP. The creation of a strong password policy is the most effective way to mitigate dictionary attacks. This includes the use of strong passwords and the periodical expiration of passwords. Refer to Dictionary Attack on Cisco LEAP to get more information about dictionary attacks and how to prevent them.

This document uses this configuration for both GUI and CLI:

- IP address of the AP is 10.0.0.106.
- IP address of the RADIUS server (ACS) is 10.0.0.3.

Network EAP or Open Authentication with EAP

In any EAP/802.1x based authentication method, you can question what the differences are between Network EAP and Open authentication with EAP. These items refer to the values in the Authentication Algorithm field in the headers of management and association packets. Most manufacturers of wireless clients set this field at the value 0 (Open authentication), then signal a desire to do EAP authentication later in the association process. Cisco sets the value differently, from the start of association with the Network EAP flag.

If your network has clients that are:

- Cisco clients Use Network–EAP.
- Third party clients (include CCX compliant products) Use Open with EAP.
- A combination of both Cisco and third party clients Choose both Network–EAP and Open with EAP.

Define Authentication Server

The first step in the EAP configuration is to define the authentication server and establish a relationship with it.

1. On the access point Server Manager tab (under the **Security > Server Manager** menu item), complete these steps:
 - a. Enter the IP address of the authentication server in the Server field.
 - b. Specify the Shared Secret and the ports.
 - c. Click **Apply** in order to create the definition and populate the dropdown lists.
 - d. Set the EAP Authentication type Priority 1 field to the server IP address under Default Server Priorities.
 - e. Click **Apply**.

Cisco 1200 Access Point

SERVER MANAGER GLOBAL PROPERTIES

Hostname AP 12:18:46 Mon Sep 20 2004

Security: Server Manager

Backup RADIUS Server

Backup RADIUS Server: (Hostname or IP Address)

Shared Secret:

Apply Delete Cancel

Corporate Servers

Current Server List

RADIUS

< NEW >
10.0.0.3

Delete

Server: 10.0.0.3 (Hostname or IP Address)

Shared Secret:

Authentication Port (optional): 1645 (0-65536)

Accounting Port (optional): 1646 (0-65536)

Apply Cancel

Default Server Priorities

EAP Authentication

Priority 1: 10.0.0.3

Priority 2: < NONE >

Priority 3: < NONE >

MAC Authentication

Priority 1: < NONE >

Priority 2: < NONE >

Priority 3: < NONE >

Accounting

Priority 1: < NONE >

Priority 2: < NONE >

Priority 3: < NONE >

Admin Authentication (RADIUS)

Priority 1: < NONE >

Priority 2: < NONE >

Priority 3: < NONE >

Admin Authentication (TACACS+)

Priority 1: 10.0.0.3

Priority 2: < NONE >

Priority 3: < NONE >

Proxy Mobile IP Authentication

Priority 1: < NONE >

Priority 2: < NONE >

Priority 3: < NONE >

Apply Cancel

Close Window Copyright (c) 1992-2004 by Cisco Systems, Inc.

You can also issue these commands from the CLI:

```
AP#configure terminal
```

Enter configuration commands, one per line. End with CNTL/Z.

```
AP(config)#aaa group server radius rad_eap
```

```
AP(config-sg-radius)#server 10.0.0.3 auth-port 1645 acct-port 1646
```

```
AP(config-sg-radius)#exit
```

```
AP(config)#aaa new-model
```

```
AP(config)#aaa authentication login eap_methods group rad_eap

AP(config)#radius-server host 10.0.0.3 auth-port 1645
acct-port 1646 key labap1200ip102

AP(config)#end

AP#write memory
```

2. The access point must be configured in the authentication server as an AAA client.

For example, in Cisco Secure ACS, this happens on the Network Configuration page where the name of the access point, IP address, shared secret and authentication method (RADIUS Cisco Aironet or RADIUS Cisco IOS/PIX) are defined. Refer to the documentation from the manufacturer for other non-ACS authentication servers.

The screenshot shows the 'Network Configuration' page in the Cisco Systems web interface. The 'AAA Client' section is highlighted with a red box. It contains the following fields and options:

- AAA Client Hostname:
- AAA Client IP Address:
- Key:
- Authenticate Using:

Below these fields are four unchecked checkboxes:

- ☐ Single Connect TACACS+ AAA Client (Record stop in accounting on failure).
- ☐ Log Update/Watchdog Packets from this AAA Client
- ☐ Log RADIUS Tunneling Packets from this AAA Client
- ☐ Replace RADIUS Port info with Username from this AAA Client

At the bottom of the form are three buttons: 'Submit', 'Submit + Restart', and 'Cancel'.

On the right side, there is a 'Help' section with a list of links:

- [AAA Client Hostname](#)
- [AAA Client IP Address](#)
- [Key](#)
- [Network Device Group](#)
- [Authenticate Using](#)
- [Single Connect TACACS+ AAA Client](#)
- [Log Update/Watchdog Packets from this AAA Client](#)
- [Log RADIUS Tunneling Packets from this AAA Client](#)
- [Replace RADIUS Port info with Username from this AAA Client](#)

Below the links, there is a section titled 'AAA Client Hostname' with the text: 'The AAA Client Hostname is the name assigned to the AAA client.' and a link [\[Back to Top\]](#).

Ensure that the authentication server is configured to perform the desired EAP authentication method. For example, for a Cisco Secure ACS that does LEAP, configure LEAP authentication on the System Configuration – Global Authentication Setup page. Click **System Configuration**, then click **Global Authentication Setup**. Refer to the documentation from the manufacturer for other non-ACS authentication servers or other EAP methods.

System Configuration

User Setup

Group Setup

Shared Profile Components

Network Configuration

System Configuration

Interface Configuration

Administration Control

External User Databases

Reports and Activity

Online Documentation

Service Control

Logging

Date Format Control

Local Password Management

CiscoSecure Database Replication

ACS Backup

ACS Restore

ACS Service Management

IP Pools Server

IP Pools Address Recovery

ACS Certificate Setup

Global Authentication Setup

Back to Help

Service Control

Logging

Date Format Control

Local Password Management

CiscoSecure Database Replication

RDBMS Synchronization

ACS Backup

ACS Restore

ACS Service Management

IP Pools Address Recovery

IP Pools Server

VoIP Accounting Configuration

ACS Certificate Setup

Global Authentication Configuration

Service Control

Select to open the page from which you can stop or restart Cisco Secure ACS services.

Back to Top

This image shows Cisco Secure ACS configured for PEAP, EAP-FAST, EAP-TLS, LEAP and EAP-MD5.

System Configuration

Edit

Help

User Setup

Group Setup

Shared Profile Components

Network Configuration

System Configuration

Interface Configuration

Administration Control

External User Databases

Reports and Activity

Online Documentation

Global Authentication Setup

EAP Configuration

PEAP

☒ Allow EAP-MSCHAPv2
 ☒ Allow EAP-GTC

Cisco client initial message:

PEAP session timeout (minutes):

Enable Fast Reconnect: ☒

EAP-FAST

☒ Allow EAP-FAST

Active master key TTL:

Retired master key TTL:

PAC TTL:

Client initial message:

Authority ID Info:

Allow automatic PAC provisioning: ☐

EAP-FAST master server: ☒

Actual EAP-FAST server status: **Master**

EAP-TLS

☒ Allow EAP-TLS

Select one or more of the following options:

☒ Certificate SAN comparison
 ☒ Certificate CN comparison
 ☒ Certificate Binary comparison

EAP-TLS session timeout (minutes):

LEAP

☒ Allow LEAP (For Aironet only)

EAP-MD5

☒ Allow EAP-MD5

AP EAP request timeout (seconds):

MS-CHAP Configuration

☒ Allow MS-CHAP Version 1 Authentication
 ☒ Allow MS-CHAP Version 2 Authentication

Back to Help

Submit

Submit + Restart

Cancel

- PEAP
- EAP-FAST
- EAP-TLS
- LEAP
- EAP-MD5
- AP EAP request timeout
- MS-CHAP Configuration

This page specifies settings for various authentication protocols.

[\[Back to Top\]](#)

PEAP

Note: PEAP is a certificate-based authentication protocol. PEAP authentication can occur only after you have

Define Client Authentication Methods

Once the access point knows where to send client authentication requests, configure it to accept those methods.

Note: These instructions are for a WEP based installation. For WPA (which uses ciphers instead of WEP), refer to WPA Configuration Overview.

1. On the access point Encryption Manager tab (under the **Security > Encryption Manager** menu

item), complete these steps:

- Specify that you want to use **WEP encryption**.
- Specify that WEP is **Mandatory**.
- Verify that the key size is set to **128-bits**.
- Click **Apply**.

The screenshot shows the Cisco 1200 Access Point configuration web interface. The left sidebar contains a navigation menu with options like HOME, EXPRESS SET-UP, EXPRESS SECURITY, NETWORK MAP, ASSOCIATION, NETWORK INTERFACES, SECURITY, and SERVICES. The main content area is titled "Cisco 1200 Access Point" and shows the configuration for "RADIO0-802.11B". The "Security: Encryption Manager - Radio0-802.11B" section is active, displaying "Encryption Modes" where "WEP Encryption" is selected and "Mandatory" is chosen from a dropdown menu. Below this, "Cisco Compliant TKIP Features" are shown with checkboxes for "Enable MIC" and "Enable Per Packet Keying". The "Encryption Keys" section contains a table with four rows for "Encryption Key 1" through "Encryption Key 4", each with a "Transmit Key" radio button, an "Encryption Key (Hexadecimal)" input field, and a "Key Size" dropdown menu set to "128 bit". The "Global Properties" section at the bottom includes "Broadcast Key Rotation Interval" with options to "Disable Rotation" or "Enable Rotation with Interval" (set to "DISABLED"), and "WPA Group Key Update" with checkboxes for "Enable Group Key Update On Membership Termination" and "Enable Group Key Update On Member's Capability Change". At the bottom right, there are buttons for "Apply-Radio0", "Apply-All", and "Cancel".

You can also issue these commands from the CLI:

```
AP#configure terminal
```

Enter configuration commands, one per line. End with CNTL/Z.

```
AP(config)#interface dot11radio 0
```

```
AP(config-if)#encryption mode wep mandatory
```

```
AP(config-if)#end
```


AP#write memory

2. Complete these steps on the access point SSID Manager tab (under the **Security > SSID Manager** menu item):

- Select the desired SSID.
- Under "Authentication Methods Accepted," check the box labelled **Open** and use the dropdown list to choose **With EAP**.
- Check the box labelled **Network-EAP** if you have Cisco client cards. See the discussion in the Network EAP or Open Authentication with EAP section.
- Click **Apply**.

Cisco 1200 Access Point

Radio0-802.11B | Radio1-802.11A

Hostname AP 12:47:46 Mon Sep 20 2004

Security: SSID Manager - Radio0-802.11B

SSID Properties

Current SSID List

< NEW >
labap1200

SSID: labap1200

VLAN: < NONE > Define VLANs

Network ID: (0-4096)

Delete-Radio0 Delete-All

Authentication Settings

Methods Accepted:

☒ Open Authentication: with EAP

☐ Shared Authentication: < NO ADDITION >

☒ Network EAP: < NO ADDITION >

Server Priorities:

EAP Authentication Servers	MAC Authentication Servers
<input checked="" type="radio"/> Use Defaults Define Defaults	<input checked="" type="radio"/> Use Defaults Define Defaults
<input type="radio"/> Customize	<input type="radio"/> Customize
Priority 1: < NONE >	Priority 1: < NONE >
Priority 2: < NONE >	Priority 2: < NONE >
Priority 3: < NONE >	Priority 3: < NONE >

Portions of this image not relevant to the discussion have been edited for clarity

Global Radio0-802.11B SSID Properties

Set Guest Mode SSID: < NONE >

Set Infrastructure SSID: < NONE > ☐ Force Infrastructure Devices to associate only to this SSID

Apply Cancel

Close Window Copyright (c) 1992-2004 by Cisco Systems, Inc.

You can also issue these commands from the CLI:

```
AP#configure terminal

Enter configuration commands, one per line.  End with CNTL/Z.

AP(config)#interface dot11radio 0

AP(config-if)#ssid labap1200

AP(config-if-ssid)#authentication open eap eap_methods

AP(config-if-ssid)#authentication network-eap eap_methods

AP(config-if-ssid)#end

AP#write memory
```

Once you confirm basic functionality with a basic EAP configuration, you can add additional features and key management at a later time. Layer more complex functions on top of functional foundations in order to make troubleshooting easier.

Verify

This section provides information you can use to confirm your configuration works properly.

Certain **show** commands are supported by the Output Interpreter Tool (registered customers only) , which allows you to view an analysis of **show** command output.

- **show radius server-group all** Displays a list of all configured RADIUS server-groups on the AP.

Troubleshoot

Troubleshoot Procedure

Complete these steps in order to troubleshoot your configuration.

1. In the client-side utility or software, create a new profile or connection with the same or similar parameters in order to ensure that nothing has become corrupted in the configuration of the client.
2. In order to eliminate the possibility of RF issues that prevent successful authentication, temporarily disable authentication as shown in these steps:
 - ◆ From the CLI, use the commands **no authentication open eap eap_methods**, **no authentication network-eap eap_methods** and **authentication open**.
 - ◆ From the GUI, on the SSID Manager page, un-check **Network-EAP**, check **Open**, and set the dropdown list back to **No Addition**.If the client successfully associates, then RF does not contribute to the association problem.
3. Verify that shared secret passwords are synchronized between the access point and the authentication server. Otherwise, you can receive this error message:

```
Invalid message authenticator in EAP request
```

- ◆ From the CLI, check the line **radius-server host x.x.x.x auth-port x acct-port x key <shared_secret>**.
- ◆ From the GUI, on the Server Manager page, re-enter the shared secret for the appropriate server in the box labelled "Shared Secret."

4. Remove any user groups from the RADIUS server. Sometimes conflicts can occur between user groups defined by the RADIUS server, and user groups in the underlying domain. Check the logs of the RADIUS server for failed attempts, and the reasons those attempts failed.

Certain **show** commands are supported by the Output Interpreter Tool (registered customers only) , which allows you to view an analysis of **show** command output.

Note: Before you issue **debug** commands, refer to the Important Information on Debug Commands.

- ```
*Mar 1 02:37:46.846: dot11_auth_dot1x_send_id_req_to_client: Sending
identity request to 0040.96ac.dd05
*Mar 1 02:37:46.846: dot11_auth_dot1x_send_id_req_to_client:
0040.96ac.dd05 timer started for 30 seconds
*Mar 1 02:37:46.930: dot11_auth_dot1x_run_rfsm: Executing
Action(CLIENT_WAIT,EAP_START) for 0040.96ac.dd05
*Mar 1 02:37:46.931: dot11_auth_dot1x_send_id_req_to_client:
Sending identity request to 0040.96ac.dd05 (client)
*Mar 1 02:37:46.931: dot11_auth_dot1x_send_id_req_to_client: Client
0040.96ac.dd05 timer started for 30 seconds
*Mar 1 02:37:46.938: dot11_auth_dot1x_run_rfsm: Executing
Action(CLIENT_WAIT,CLIENT_REPLY) for 0040.96ac.dd05
*Mar 1 02:37:46.938: dot11_auth_dot1x_send_response_to_server:
Sending client 0040.96ac.dd05 data (User Name) to server
*Mar 1 02:37:46.938: dot11_auth_dot1x_send_response_to_server:
Started timer server_timeout 60 seconds
*Mar 1 02:37:47.017: dot11_auth_dot1x_run_rfsm: Executing
Action(SERVER_WAIT,SERVER_REPLY) for 0040.96ac.dd05
*Mar 1 02:37:47.017: dot11_auth_dot1x_send_response_to_client:
Forwarding server message(Challenge) to client 0040.96ac.dd05
*Mar 1 02:37:47.018: dot11_auth_dot1x_send_response_to_client:
Started timer client_timeout 20 seconds
*Mar 1 02:37:47.025: dot11_auth_dot1x_run_rfsm: Executing
Action(CLIENT_WAIT,CLIENT_REPLY) for 0040.96ac.dd05
*Mar 1 02:37:47.025: dot11_auth_dot1x_send_response_to_server:
Sending client 0040.96ac.dd05 data(User Credentials) to server
-----Lines Omitted for simplicity-----
*Mar 1 02:37:47.030: dot11_auth_dot1x_send_response_to_client:
Started timer client_timeout 20 seconds
*Mar 1 02:37:47.041: dot11_auth_dot1x_run_rfsm: Executing Action
SE RVERPASSW for 0040.96ac.dd05
*Mar 1 02:37:47.041: dot11_auth_dot1x_send_response_to_client:
Forwarding server message(Pass Message) to client
0040.96ac.dd05
*Mar 1 02:37:47.042: dot11_auth_dot1x_send_response_to_client:
Started timer client_timeout 30 seconds
*Mar 1 02:37:47.043: %DOT11-6-ASSOC: Interface Dot11Radio0,
Station TACWEB 0040 .96ac.dd05 Associated KEY_MGMT[NONE] (Client sta
associated to the access point)
```

**Note:** In Cisco IOS Software releases prior to 12.2(15)JA, the syntax of this **debug** command is **debug dot11 aaa dot1x state-machine**.

- **debug dot11 aaa authenticator process** Displays the individual dialog entries of the negotiation between the client and the authentication server.

**Note:** In Cisco IOS Software releases prior to 12.2(15)JA, the syntax of this debug command is **debug dot11 aaa dot1x process**.

- **debug radius authentication** Displays the RADIUS negotiations between the server and client, both of which, are bridged by the AP. This is an output for **failed** authentication:

```
*Mar 1 02:34:55.086: RADIUS/ENCODE(00000031):Orig. component type = DOT11
*Mar 1 02:34:55.086: RADIUS: AAA Unsupported Attr: ssid [264] 5
*Mar 1 02:34:55.086: RADIUS: 73 73 69 [ssi]
*Mar 1 02:34:55.086: RADIUS: AAA Unsupported Attr: interface [157] 3
*Mar 1 02:34:55.087: RADIUS: 32 [2]
*Mar 1 02:34:55.087: RADIUS(00000031): Config NAS IP: 10.0.0.106
*Mar 1 02:34:55.087: RADIUS/ENCODE(00000031): acct_session_id: 47
*Mar 1 02:34:55.087: RADIUS(00000031): Config NAS IP: 10.0.0.106
*Mar 1 02:34:55.087: RADIUS(00000031): sending
*Mar 1 02:34:55.087: RADIUS(00000031): Send Access-Request
to 10.0.0.3 :164 5 id 1645/61, len 130
*Mar 1 02:34:55.088: RADIUS: authenticator 0F 6D B9 57 4B A3 F2 0E -
56 77 A4 7E D3 C2 26 EB
*Mar 1 02:34:55.088: RADIUS: User-Name [1] 8 "wirels"
*Mar 1 02:34:55.088: RADIUS: Framed-MTU [12] 6 1400
*Mar 1 02:34:55.088: RADIUS: Called-Station-Id [30] 16 "0019.a956.55c0"
*Mar 1 02:34:55.088: RADIUS: Calling-Station-Id [31] 16 "0040.96ac.dd05"
*Mar 1 02:34:55.088: RADIUS: Service-Type [6] 6 Login [1]
*Mar 1 02:34:55.088: RADIUS: Message-Authenticato[80] 18
*Mar 1 02:34:55.089: RADIUS: 73 8C 59 C4 98 51 53 9F 58 4D 1D EB A5
4A AB 88 [s?Y??QS?XM???J??]
*Mar 1 02:34:55.089: RADIUS: EAP-Message [79] 13
*Mar 1 02:34:55.089: RADIUS: NAS-Port-Id [87] 5 "299"
*Mar 1 02:34:55.090: RADIUS: NAS-IP-Address [4] 6 10.0.0.106
*Mar 1 02:34:55.090: RADIUS: Nas-Identifier [32] 4 "ap"
*Mar 1 02:34:55.093: RADIUS: Received from id 1645/61
10.0.0.3 :1645, Access-Challenge, len 79
*Mar 1 02:34:55.093: RADIUS: authenticator 72 FD C6 9F A1 53 8F D2 -
84 87 49 9B B4 77 B8 973
-----Lines Omitted-----
*Mar 1 02:34:55.117: RADIUS(00000031): Config NAS IP: 10.0.0.106
*Mar 1 02:34:55.118: RADIUS/ENCODE(00000031): acct_session_id: 47
*Mar 1 02:34:55.118: RADIUS(00000031): Config NAS IP: 10.0.0.106
*Mar 1 02:34:55.118: RADIUS(00000031): sending
*Mar 1 02:34:55.118: RADIUS(00000031): Send Access-Request to
10.0.0.3 :164 5 id 1645/62, len 168
*Mar 1 02:34:55.118: RADIUS: authenticator 49 AE 42 83 C0 E9 9A A7 -
07 0F 4E 7C F4 C7 1F 24
*Mar 1 02:34:55.118: RADIUS: User-Name [1] 8 "wirels"
*Mar 1 02:34:55.119: RADIUS: Framed-MTU [12] 6 1400
-----Lines Omitted-----
*Mar 1 02:34:55.124: RADIUS: Received from id 1645/62
10.0.0.3 :1645, Access-Reject, len 56
*Mar 1 02:34:55.124: RADIUS: authenticator A6 13 99 32 2A 9D A6 25 -
AD 01 26 11 9A F6 01 37
*Mar 1 02:34:55.125: RADIUS: EAP-Message [79] 6
*Mar 1 02:34:55.125: RADIUS: 04 15 00 04 [????]
*Mar 1 02:34:55.125: RADIUS: Reply-Message [18] 12
*Mar 1 02:34:55.125: RADIUS: 52 65 6A 65 63 74 65 64 0A 0D
[Rejected??]
*Mar 1 02:34:55.125: RADIUS: Message-Authenticato[80] 18
*Mar 1 02:34:55.126: RADIUS(00000031): Received from id 1645/62
*Mar 1 02:34:55.126: RADIUS/DECODE: EAP-Message fragments, 4, total 4 bytes
*Mar 1 02:34:55.126: RADIUS/DECODE: Reply-Message fragments, 10, total 10 bytes
```

\*Mar 1 02:34:55.127: %DOT11-7-AUTH\_FAILED: Station  
0040.96ac.dd05 Authentication failed

- **debug aaa authentication** Displays the AAA negotiations for authentication between the client device and the authentication server.

## NetPro Discussion Forums – Featured Conversations

Networking Professionals Connection is a forum for networking professionals to share questions, suggestions, and information about networking solutions, products, and technologies. The featured links are some of the most recent conversations available in this technology.

|                                                                |
|----------------------------------------------------------------|
| NetPro Discussion Forums – Featured Conversations for Wireless |
| Wireless – Mobility: WLAN Radio Standards                      |
| Wireless – Mobility: Security and Network Management           |
| Wireless – Mobility: Getting Started with Wireless             |
| Wireless – Mobility: General                                   |

## Related Information

- **Debug Authentications**
- **Configuring Authentication Types**
- **LEAP Authentication on a Local RADIUS Server**
- **Configuring RADIUS and TACACS+ Servers**
- **Configuring Cisco Secure ACS for Windows v3.2 With PEAP–MS–CHAPv2 Machine Authentication**
- **Cisco Secure ACS for Windows v3.2 With EAP–TLS Machine Authentication**
- **Configuring PEAP/EAP on Microsoft IAS**
- **Troubleshooting Microsoft IAS as a RADIUS server**
- **Microsoft 802.1X Authentication Client**
- **Technical Support & Documentation – Cisco Systems**

Contacts & Feedback | Help | Site Map

© 2007 – 2008 Cisco Systems, Inc. All rights reserved. Terms & Conditions | Privacy Statement | Cookie Policy | Trademarks of Cisco Systems, Inc.

Updated: Feb 13, 2007

Document ID: 44844