

- [6" Series](#)
- [8" Series](#)
- [Ballast Weight](#)
- [Buoyancy Foam](#)
- [Enclosure Tools and Supplies](#)
- [Educational Books](#)
- [Dings & Dents](#)

**Questions About Ordering?**

Check out our [Order and Shipping Info Page](#) for details on ordering, pre-orders, and shipping.

Parameter	Value	
-----------	-------	--

<b>Performance</b>		
Maximum FWD/REV Thrust @ 10 V	2.95 / 2.3 kg f	6.5 / 5.1 lb f
Maximum FWD/REV Thrust @ 12 V	3.7 / 2.9 kg f	8.2 / 6.4 lb f
Maximum FWD/REV Thrust @ 14 V	4.5 / 3.55 kg f	10.0 / 7.8 lb f
Maximum FWD/REV Thrust @ 16 V	5.25 / 4.1 kg f	11.6 / 9.0 lb f
Maximum FWD/REV Thrust @ 18 V	6.05 / 4.6 kg f	13.3 / 10.1 lb f
Maximum FWD/REV Thrust @ 20 V	6.7 / 5.05 kg f	14.8 / 11.1 lb f
Minimum Thrust	0.02 kg f*	0.05 lb f*

<b>Electrical</b>		
Operating Voltage		7-20 volts
Max Current @16 V		24 Amps
Max Power @ 16 V		390 Watts

<b>Physical</b>		
Length	113 mm	4.45 in
Diameter	100 mm	3.9 in
Weight in Air (with 1m cable)	0.76 lb	344 g