

FCCS002 COE VI Section 3

Meet - vite-rmx-ebh

meet.google.com/vite-rmx-ebh?authuser=0

R

Ritu Sibbal is presenting

L

LEKHA SONI
and 50 more

09:57

4:06 PM

You

Switch

- C has a built-in multiple-branch selection statement, called **switch**,
- Switch statement successively tests the value of an expression against a list of integer or character constants.
- When a match is found, the statements associated with that constant are executed. The general form of the **switch** statement is

You can't remove this participant

You

PUSHP JAIN

A

ANANT

MEGHNA

R

Ritu Sibbal

bcxgzslm1s

Raise hand

Turn on captions

Ritu Sibbal is presenting

FCCS002 CDE VI Section 3Meet - vite-rmx-ebb

meet.google.com/vte-rmx-ebb?authuser=0

SHOBHIT PRAK...and 54 more4:08 PMYou

Ritu Sibbal is presenting

```
void menu(void)
{
    char ch;
    printf("1. Check Spelling\n");
    printf("**2. Correct Spelling Errors\n");
    printf("3. Display Spelling Errors\n");
    printf("Strike Any Other Key to Skip\n");
    printf(" Enter your choice: ");
    ch = getchar(); /* read the selection from the keyboard */
    switch(ch) {
        case '1':
            check_spelling ();
            break;
        case '2':
            correct_errors ();
            break;
        case '3':
            display_errors ();
            break;
        default :
            printf
            ("No option selected");
    }
}
```

You

AMRISHA DAS

ANANT

MEGHNA

R

... Ritu Sibbal

FCCS002 COE VI Section 3

Meet - vite-rmx-ebh

meet.google.com/vite-rmx-ebh?authuser=0

SHUBHAM SHA... and 54 more

4:08 PM

Ritu Sibbal is presenting

- The *expression* must evaluate to an integer type
- . The value of *expression* is tested against the values, one after another, of the constants specified in the **case** statements.
- When a match is found, the statement sequence associated with that **case** is executed until the break statement or the end of the **switch** statement is reached.
- The **default** statement is executed if no matches are found.
- The **default** is optional, and if it is not present, no action takes place if all matches fail

- The **break** statement is one of C's jump statements.
- You can use it in loops as well as in the **switch** statement .
- When **break** is encountered in a **switch**, program execution "jumps" to the line of code following the **switch** statement.

You

A

AMRISHA DAS

A

ANANT

MEGHNA

R

Ritu Sibbal

FCCS002 COE VI Section 3Meet - vite-rmx-ebh

meet.google.com/vite-rmx-ebh?authuser=0

Ritu Sibbal is presentingROHAN GOEL and 56 more4:12 PM

- This example illustrates two aspects of **switch**.
- First, you can have **case** statements that have no statement sequence associated with them. When this occurs, execution simply drops through to the next **case**. In this example, the first three **cases** all execute the same statements, which are
 - `flag = 0;`
 - `break;`
- Second, execution of one statement sequence continues into the next **case** if no **break** statement is present. If `i` matches 4, **flag** is set to 1, and because there is no **break** statement at the end of that **case**, execution continues and the call to **error(flag)** is executed. If `i` had matched 5, **error(flag)** would have been called with a flag value of -1 (rather than 1).
- The fact that **cases** can run together when no **break** is present prevents the unnecessary duplication of statements, resulting in more efficient code.

You

MEGHNA

A

ANANT

A

AMRISHA DAS

R

Ritu Sibbal

Iteration

- The iteration statements are **while**, **for**, and **do-while**.
- These are also called *loop statements*.

Ritu Sibbal is presenting

ARUSHEE VERMA and 59 more

4:19 PM

You

... RITIK YADAV

A

APURVA MISHRA

AKHIL DUBEY

R

Ritu Sibbal

Browser tabs: FCC5002 COE VI Section 3, Meet - vite-rmx-ebh

Address bar: meet.google.com/vte-rmx-ebh?authuser=0

Meeting header: Ritu Sibbal is presenting, ARYAMAN SINGH and 59 more, 4:20 PM

- In C, and all other modern programming languages, iteration statements (also called loops) allow a set of instructions to be repeatedly executed until a certain condition is reached.
- This condition may be predetermined (as in the **for** loop) or open ended (as in the **while** and **do-while** loops).

Participants: You, RITIK YADAV, APURVA MISHRA, ISHAAN KUMAR, Ritu Sibbal

Browser tabs: FCC5002 COE VI Section 3, Meet - vite-rmrx-ebh

Address bar: meet.google.com/vite-rmrx-ebh?authuser=0

Meeting controls: Ritu Sibbal is presenting, DARSH MITTAL and 59 more, 4:20 PM

The for Loop

- The general form of the **for** statement is

for (initialization; condition; increment) statement ;

Participants: You, RITIK YADAV, A, APURVA MISHRA, I, ISHAAN KUMAR, Ritu Sibbal

Browser tabs: FCC5002 COE VI Section 3, Meet - vite-rmx-ebh

Address bar: meet.google.com/vte-rmx-ebh?authuser=0

Header: Ritu Sibbal is presenting, ESHAN MALHO... and 59 more, 4:20 PM

- The **for** works like this:
- The *initialization* is an assignment statement that is used to set the loop control variable. The *condition* is a relational expression that determines when the loop exits.
- The *increment* defines how the loop control variable changes each time the loop is repeated.
- These three major sections are separated by semicolons.
- The **for** loop continues to execute as long as the condition is true. Once the condition becomes false, program execution resumes on the statement following the **for**.

Participants: You, RITIK YADAV, APURVA MISHRA, ISHAAN KUMAR, Ritu Sibbal

FCCS002 CDE VI Section 3

Meet - vite-rmx-ebh

meet.google.com/vte-rmx-ebh?authuser=0

NITASH BISWAS
and 59 more

4:21 PM

R

Ritu Sibbal is presenting

Example

```
#include <stdio.h>
int main(void)
{
    int x;
    for(x=1; x <= 100; x++) printf("%d ", x);
    return 0;
}
```

You

RITIK YADAV

R

RAHUL SHARMA

I

ISHAAN KUMAR

R

Ritu Sibbal

Browser tabs: FCC5002 COE VI Section 3, Meet - vite-rmx-ebb

Address bar: meet.google.com/vte-rmx-ebb?authuser=0

Meeting controls: Ritu Sibbal is presenting, MOKSHI SHAR... and 58 more, 4:26 PM

PowerPoint ribbon: File, Home, Insert, Design, Transitions, Animations, Slide Show, Review, View, Help, Acrobat, Tell me what you want to do

Slide Show tab options: From Beginning, From Current Slide, Present Online, Custom Slide Show, Set Up Slide Show, Hide Slide, Rehearse Timings, Record Slide Show, Keep Slides Updated, Use Timings, Monitor: Automatic, Play Narrations, Show Media Controls, Use Presenter View

Slide 27 content:

- In **for** loops, the conditional test is always performed at the top of the loop. This means that the code inside the loop may not be executed at all if the condition is false to begin with. For example, in

```
x = 10;
for(y=10; y != x; ++y) printf("%d", y);
printf("%d", y); /* this is the only printf()
statement that will execute */
```

- the loop will never execute because **x** and **y** are equal when the loop is entered. Because this causes the conditional expression to evaluate to false, neither the body of the loop nor the increment portion of the loop executes. Thus, **y** still has the value 10, and the only output produced by the fragment is the number 10 printed once on the screen

Slide 27 of 37, English (United States), Uploading to OneDrive, 82%

Participants: You, SHIRISH TI JAIN, SHASHANK MISHRA, MANAN SURJ, Ritu Sibbal

Browser tabs: FCC5002 CDE VI Section 3, Meet - vite-rmx-ebb

Address bar: meet.google.com/vte-rmx-ebb?authuser=0

Google Meet header: Ritu Sibbal is presenting, PUSH P JAIN and 58 more, 4:27 PM

PowerPoint title bar: Lecture's statements.pptx - PowerPoint

PowerPoint ribbon: File, Home, Insert, Design, Transitions, Animations, Slide Show, Review, View, Help, Acrobat, Tell me what you want to do

Slide Show ribbon options:

- From Beginning, From Current Slide, Present Online, Custom Slide Show
- Set Up Slide Show, Hide Slide, Rehearse Timings, Record Slide Show
- Keep Slides Updated, Use Timings, Monitor: Automatic
- Play Narrations, Show Media Controls, Use Presenter View

The For loop Variations

- The previous discussion described the most common form of the **for** loop.
- However, several variations of the **for** are allowed that increase its power, flexibility, and applicability
- A common variations uses the comma operator to allow two or more variables to control the loop.

Slide navigation: 25, 26, 27, 28, 29, 30

Slide 28 content: The For loop variations

Bottom status bar: Slide 28 of 37, English (United States), Uploading to OneDrive, Notes, Comments, 82%

Participants list:

- You
- SHIRISH TI JAIN
- SHASHANK MISHRA
- MANAN SURJ
- Ritu Sibbal

Browser tabs: FCC5002 CDE VI Section 3, Meet - vite-rmxr-ebh

Address bar: meet.google.com/vte-rmxr-ebh?authuser=0

Top bar: Ritu Sibbal is presenting, ROHIT SHARMA and 56 more, 4:27 PM

PowerPoint Title: Lecture8 statements.pptx - PowerPoint

PowerPoint Ribbon: File, Home, Insert, Design, Transitions, Animations, Slide Show, Review, View, Help, Acrobat, Tell me what you want to do

Slide Show Tab Options:

- From Beginning, From Current Slide, Present Online, Custom Slide Show, Start Slide Show
- Set Up Slide Show, Hide Slide, Rehearse Timings, Record Slide Show, Set Up
- Keep Slides Updated, Use Timings, Monitor: Automatic
- Play Narrations, Show Media Controls, Use Presenter View

Slide 25:

```
for (x=0, y=10; x+y < 10; ++x) {
    y = getchar();
    y = y - '0'; /* subtract the ASCII code for 0 from y */
}
```

Slide 26:

Commas separate the two initialization statements. Each time the loop repeats, **x** is incremented and **y**'s value is set by keyboard input.

Slide 27:

Both **x** and **y** must be at the correct value for the loop to terminate. Even though **y**'s value is set by keyboard input, **y** must be initialized to 0 so that its value is defined before the first evaluation of the conditional expression. (If **y**'s value was not set, it could by chance contain the value 10, making the conditional test false and preventing the loop from executing.)

Slide 28:

AKHIL DUBEY has left the meeting

Slide 29 of 37, English (United States), Uploading to OneDrive, 82%

Participants: You, SHIRISH TI JAIN, SHASHANK MISHRA, MANAN SURJ, Ritu Sibbal

Browser tabs: FCC5002 COE VI Section 3, Meet - vite-rmx-ebb

Address bar: meet.google.com/vte-rmx-ebb?authuser=0

Meeting controls: Ritu Sibbal is presenting, AMAN KUMAR J... and 55 more, 4:28 PM

PowerPoint ribbon: File, Home, Insert, Design, Transitions, Animations, Slide Show, Review, View, Help, Acrobat, Tell me what you want to do

Slide Show tab options: From Beginning, From Current Slide, Present Online, Custom Slide Show, Set Up Slide Show, Hide Slide, Rehearse Timings, Record Slide Show, Keep Slides Updated, Use Timings, Monitor: Automatic, Play Narrations, Show Media Controls, Use Presenter View

The While Loop

- The second loop available in C is the **while** loop. Its general form is

```
while(condition) statement;
```

Slide 30 of 37, English (United States), Uploading to OneDrive, 82%

Participants: You, SHIRISH TI JAIN, RITIK YADAV, MANAN SURI, Ritu Sibbal

Browser tabs: FCCS002 COE VI Section 3, Meet - vite-rmxr-ebh

Address bar: meet.google.com/vite-rmxr-ebh?authuser=0

Meeting header: Ritu Sibbal is presenting, AMOGH GARG and 55 more, 4:29 PM

PowerPoint ribbon: File, Home, Insert, Design, Transitions, Animations, Slide Show, Review, View, Help, Acrobat, Tell me what you want to do

Slide Show tab options:

- From Beginning, From Current Slide, Present Online, Custom Slide Show, Start Slide Show
- Set Up Slide Show, Hide Slide, Rehearse Timings, Record Slide Show, Set Up
- ☒ Keep Slides Updated, ☒ Use Timings, Monitor: Automatic
- ☒ Play Narrations, ☒ Show Media Controls, ☒ Use Presenter View

Slide 31 content:

- where *statement* is either an empty statement, a single statement, or a block of statements.
- The *condition* may be any expression, and true is any nonzero value. The loop iterates while the condition is true. When the condition becomes false, program control passes to the line of code immediately following the loop.

Slide navigation: 28, 29, 30, 31 (selected), 32, 33

Footer: Slide 31 of 37, English (United States), Uploading to OneDrive, Notes, Comments, 82%

Participant list:

- You
- S
- SHIRISH TI JAIN
- RITIK YADAV
- M
- MANAN SURJ
- R
- Ritu Sibbal

FFCS002 CDE VI Section 3 Meet - vite-rmx-ebh

meet.google.com/vte-rmx-ebh?authuser=0

Ritu Sibbal is presenting

MEGHNA and 56 more

4:31 PM

Lecture8 statements.pptx - PowerPoint

File Home Insert Design Transitions Animations Slide Show Review View Help Acrobat Tell me what you want to do

From Beginning From Current Slide Present Custom Slide Online Show Start Slide Show Set Up Hide Slide Rehearse Record Slide Timings Show Set Up

Keep Slides Updated Use Timings Monitor: Automatic

Play Narrations Show Media Controls Use Presenter View

30 The following example shows a keyboard input routine that simply loops until the user types

31 • A:

```
char wait_for_char(void)
{
    char ch;
    ch = '\0'; /* initialize ch */
    while(ch != 'A') ch = getchar();
    return ch;
}
```

32

33

34

• First, **ch** is initialized to null. As a local variable, its value is not known when **wait_for_char()** is executed. The **while** loop then checks to see if **ch** is not equal to **A**. Because **ch** was initialized to null, the test is true and the loop begins. Each time you press a key, the condition is tested again.

• Once you enter an **A**, the condition becomes false because **ch** equals **A**, and the loop terminates

bxzgsjmls

Raise hand Turn on captions Ritu Sibbal is presenting

You SHIRISH TI JAIN RITIK YADAV AKHIL DUBEY R

Browser tabs: FCC5002 CDE VI Section 3, Meet - vite-rmx-ebb

Address bar: meet.google.com/vite-rmx-ebb?authuser=0

Meeting controls: Ritu Sibbal is presenting, PIYUSH SINGH and 56 more, 4:31 PM

PowerPoint ribbon: File, Home, Insert, Design, Transitions, Animations, Slide Show, Review, View, Help, Acrobat, Tell me what you want to do

Slide Show tab options: From Beginning, From Current Slide, Present Online, Custom Slide Show, Set Up Slide Show, Hide Slide, Rehearse Timings, Record Slide Show, Keep Slides Updated, Use Timings, Monitor: Automatic, Play Narrations, Show Media Controls, Use Presenter View

Slide 33 content:

- **The do-while Loop**

Unlike **for** and **while** loops, which test the loop condition at the top of the loop, the **do-while** loop checks its condition at the bottom of the loop. This means that a **do-while** loop always executes at least once. The general form of the **do-while** loop is

```
do {  
    statement;  
} while(condition);
```

- The following **do-while** loop will read numbers from the keyboard until it finds a number less than or equal to 100:
- do {
- `scanf("%d", &num);`
- } while (num > 100);

Slide 33 of 37, English (United States), Uploading to OneDrive, 82%

Participants: You, SHIRISH TI JAIN, RITIK YADAV, MANAN SURI, Ritu Sibbal