

FCC5002 CDE VI Section 3

Meet - xbd-ghrf-yes

meet.google.com/xbd-ghrf-yes?authuser=0

A

ARUSHEE VERMA
and 53 more

09:00

1:10 PM

You

R

Ritu Sibbal is presenting

*The & and * Pointer Operators*

- A *pointer* is the memory address of an object.
- A *pointer variable* is a variable that is specifically declared to hold a pointer to an object of its specified type.
- Pointers are one of C's most powerful features, and they are used for a wide variety of purposes.
- For example, they can provide a fast means of referencing array elements.
- They allow functions to modify their calling parameters. They support linked lists, binary trees, and other
- dynamic data structures.
- We now briefly cover the two operators that are used to manipulate pointers.

00:03:39

You

A

AMAN SONI

A

AMOGH GARG

ASHISH KANT

R

... Ritu Sibbal

FCCS002 CDE VI Section 3 x Meet - xbd-ghrf-yes x +

meet.google.com/xbd-ghrf-yes?authuser=0

Ritu Sibbal is presenting

ABHISHEK KUM... and 57 more

1:14 PM

Example

- Assume that the variable **count** is at memory location 2000.
- Also assume that **count** has a value of 100. Then, after the previous assignment, **m** will have the value 2000

You

AMAN SONI

ROHIT SHARMA

MEGHNA

R

Ritu Sibbal

FCCS002 COE VI Section 3

Meet - xbd-ghrf-yes

meet.google.com/xbd-ghrf-yes?authuser=0

SHIRISH TI JAIN and 56 more

1:13 PM

Ritu Sibbal is presenting

- The first pointer operator is **&**, a unary operator that returns the memory address of its operand.

For example,

- `m = &count;`
- places into **m** the memory address of the variable **count**.
- This address is the computer's internal location of the variable. It has nothing to do with the value of **count**.
- You can think of **&** as meaning "the address of." Therefore, the preceding assignment statement means "**m** receives the address of **count**."

You

A

AMAN SONI

ASHISH KANT

A

AMOGH GARG

R

Ritu Sibbal

FCCS002 CDE VI Section 3 x Meet - xbd-ghrf-yes x +

meet.google.com/xbd-ghrf-yes?authuser=0

R Ritu Sibbal is presenting

ANUJ and 57 more 08:44 1:15 PM You

00:08:11

- For example, if **m** contains memory address of the variable **count**,

$$q = *m;$$

- places the value of **count** into **q**. Now **q** has the value 100 because 100 is stored at location 2000, the memory address that was stored in **m**.
- Think of * as meaning "at address."
- In this case, you could read the statement as "**q** receives the value at address **m**."

- Unfortunately, the multiplication symbol and the "at address" symbol are the same, and the symbol
- for the bitwise AND and the "address of" symbol are the same. These operators have no relationship
- to each other. Both **&** and ***** have a higher precedence than all other arithmetic operators except the
- unary minus, with which they share equal precedence.

You

AMAN SONI

ROHIT SHARMA

MEGHNA

R Ritu Sibbal

FCCS002 CDE VI Section 3

Meet - xbd-ghrf-yes

meet.google.com/xbd-ghrf-yes?authuser=0

R Ritu Sibbal is presenting

AMRISHA DAS and 59 more

09:66

1:20 PM

You

00:12:45

You

MEGHNA

A

AMAN SONI

R

RAHUL SHARMA

R

Ritu Sibbal

- Variables that will hold pointers must be declared as such, by putting `*` in front of the variable name.
- This indicates to the compiler that it will hold a pointer to that type of variable. For example, to declare `ch` as a pointer to a character, write

```
char *ch;
```
- It is important to understand that `ch` is not a character but a pointer to a character— there is a big difference. The type of data that a pointer points to, in this case `char`, is called the *base type* of the pointer.
- The pointer variable itself is a variable that holds the address to an object of the base type.
- Thus, a character pointer (or any type of pointer) is of sufficient size to hold an address as defined by the architecture of the host computer. It is the base type that determines what that address contains.

Browser tabs: FCC5002 CDE VI Section 3, Meet - xbd-ghrf-yes

Address bar: meet.google.com/xbd-ghrf-yes?authuser=0

Meeting controls: Ritu Sibbal is presenting, MOKSHI SHAR... and 60 more, 2867, 1:22 PM, You

- You can mix both pointer and nonpointer variables in the same declaration statement. For example,
- `int x, *y, count;`
- declares **x** and **count** as integer types and **y** as a pointer to an integer type.

Participants (00:14:54): You, MEGHNA, A, VISHAL VERMA, R, RAHUL SHARMA, Ritu Sibbal

• The following program uses * and & operators to put the value 10 into a variable called **target**.

```
#include <stdio.h>
int main(void)
{
    int target, source;
    int *m;
    source = 10;
    m = &source;
    target = *m;
    printf("%d", target);
    return 0;
}
```

00:18:07

You

M

MOKSHI SHARMA

V

VISHAL VERMA

ROHIT SHARMA

R

Ritu Sibbal

FCC5002 CDE VI Section 3

Meet - xbd-ghrf-yes

meet.google.com/xbd-ghrf-yes?authuser=0

ISHAAN KUMAR and 60 more

03:67

1:31 PM

You

R Ritu Sibbal is presenting

The Compile-Time Operator sizeof

- sizeof** is a unary compile-time operator that returns the length, in bytes, of the variable or parenthesized type specifier that it precedes. For example, assuming that integers are 4 bytes and **doubles** are 8 bytes, this fragment will display **8 4**.

```
double f;  
printf("%d ", sizeof f);  
printf('%d", sizeof(int));
```

To compute the size of a type, you must enclose the type name in parentheses.

00:00:30

You

R Ritu Sibbal

MEGHNA

A AMAN SONI

ROHIT SHARMA

FCCS002 COE VI Section 3Meet - xbd-ghrf-yesmeet.google.com/xbd-ghrf-yes?authuser=0

Ritu Sibbal is presentingNITASH BISWAS and 60 more1:32 PM

The Comma Operator

- The comma operator strings together several expressions.
- The left side of the comma operator is always evaluated as **void**.
- This means that the expression on the right side becomes the value of the total comma-separated expression. For example,
$$x = (y=3, y+1);$$
- first assigns **y** the value 3 and then assigns **x** the value 4. The parentheses are necessary because the comma operator has a lower precedence than the assignment operator.

You

R

Ritu Sibbal

S

SHASHANK MISHRA

A

AMAN SONI

ROHIT SHARMA

FCCS002 COE VI Section 3 x Meet - xbd-ghrf-yes x +

meet.google.com/xbd-ghrf-yes?authuser=0

Ritu Sibbal is presenting

NITASH BISWAS and 60 more

09:47 1:32 PM You

- The comma causes a sequence of operations. When you use it on the right side of an assignment statement, the value assigned is the value of the last expression of the comma-separated list.
- The comma operator has somewhat the same meaning as the word "and" in English, as used in the phrase "do this and this."

You

R

... Ritu Sibbal

S

... SHASHANK MISHRA

A

AMAN SONI

ROHIT SHARMA