

The screenshot shows a Google Meet window. At the top, the browser address bar displays the URL: `meet.google.com/ztd-wppv-iwi?authuser=0`. The top bar of the Meet interface indicates that 'Ritu Sibbal is presenting'. On the right side of the top bar, there are icons for participants (showing 60), chat, and the time (12:05 PM). Below the top bar, the main area displays a presentation slide with the title 'Global Variables' in a large, bold, black font. On the right side of the screen, a vertical list of participants is visible, including YASH JINDAL, Ritu Sibbal (who is presenting), ISHAAN KUMAR, and SHUBHAM SHARMA. At the bottom of the screen, there are icons for microphone, video, and chat, along with a 'Raise hand' button and a 'Turn on captions' button. The bottom left corner shows the text 'bcxzgslms'.

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

P PIYUSH SINGH and 57 more

03:44

12:05 PM

You

- Unlike local variables, *global variables* are known throughout the program and may be used by any piece of code.
- Also, they will hold their value throughout the program's execution.
- You create global variables by declaring them outside of any function.
- Any expression may access them, regardless of what block of code that expression is in.

Y

YASH JINDAL

R

Ritu Sibbal

🌙

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

S SHASHANK MIS...
and 57 more

03:44

12:06 PM

You

```
• #include <stdio.h>
int count; /* count is global */
void func1(void);
void func2(void);
int main(void)
{
    count = 100;
    func1();
    return 0;
}
void func1(void)
{
    int temp;
    temp = count;
    func2();
    printf("count is %d", count); /* will print 100 */
}
void func2(void)
{
    int count;
    for(count=1; count<10; count++)
        putchar('.');
}
```

Y

YASH JINDAL

R

Ritu Sibbal

🧘

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

+

meet.google.com/ztd-wppv-iwi?authuser=0

SHYAMAL JAIN and 58 more

12:06 PM

You

R Ritu Sibbal is presenting

- Although neither **main()** nor **func1()** has declared the variable **count**, both may use it. **func2()**, however, has declared a local variable called **count**.
- When **func2()** refers to **count**, it refers to only its local variable, not the global one.
- If a global variable and a local variable have the same name, all references to that variable name inside the code block in which the local variable is declared will refer to that local variable and have no effect on the global variable.

Y YASH JINDAL

R Ritu Sibbal

🤔 DHRUV KUMAR

S SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R

Ritu Sibbal is presenting

V

VISHESH NAITH...
and 58 more

03:55

12:07 PM

You

- Storage for global variables is in a fixed region of memory set aside for this purpose by the compiler.
- Global variables are helpful when many functions in your program use the same data.
- You should avoid using unnecessary global variables, however.
 1. They take up memory the entire time your program is executing, not just when they are needed.
 2. Using a global where a local variable will do makes a function less general because it relies on something that must be defined outside itself.
 3. Finally, using a large number of global variables can lead to program errors because of unknown and unwanted side effects. A major problem in developing large programs is the accidental changing of a variable's value because it was used elsewhere in the program. This can happen in C if you use too many global variables in your programs.

VISHAL VERMA has left the meeting

Y

YASH JINDAL

R

Ritu Sibbal

🧘

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream x Meet - ztd-wppv-iwi x +

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

DAKSH CHETIW... and 61 more

12:09 PM

You

Formal Parameters

Y YASH JINDAL

R Ritu Sibbal

🧘 DHRUV KUMAR

S SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

K KATARI PRAJEET YA... and 62 more

12:09 PM

You

- If a function is to use arguments, it must declare variables that will accept the values of the arguments.
- These variables are called the *formal parameters* of the function. They behave like any other local variables inside the function.
- As shown in the following program fragment, their declarations occur after the function name and inside parentheses

Y YASH JINDAL

R Ritu Sibbal

🧘 DHRUV KUMAR

S SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

LEKHA SONI
and 62 more

12:09 PM

You

R

Ritu Sibbal is presenting


```
/* Return 1 if c is part of string s; 0 otherwise */  
int is_in(char *s, char c)  
{  
    while(*s)  
        if(*s==c) return 1;  
    else s++;  
    return 0;  
}
```

Y

YASH JINDAL

R

Ritu Sibbal



DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream x Meet - ztd-wppv-iwi x +

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

M MAJITHIYA RISH... and 62 more

12:10 PM

- If a function is to use arguments, it must declare variables that will accept the values of the arguments.
- These variables are called the *formal parameters* of the function. They behave like any other local variables inside the function.
- As shown in the following program fragment, their declarations occur after the function name and inside parentheses

YASH JINDAL

R Ritu Sibbal

DHRUV KUMAR

S SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R

Ritu Sibbal is presenting

S

SHUBHAM AGGAR...
and 62 more

12:11 PM

You


Operators

A

AMAN SONI

R

Ritu Sibbal



DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream x Meet - ztd-wppv-iwi x +

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

VINIT and 62 more

12:12 PM

You

C is very rich in built-in operators.

There are four main classes of operators:

1. *arithmetic*,
2. *relational* ,
3. *logical*, and
4. *bitwise*.

In addition, there are some special operators, such as the assignment operator, for particular tasks.

AMAN SONI

Ritu Sibbal

DHRUV KUMAR

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

VISHESH NAITH... and 62 more

12:12 PM

The Assignment Operator

- The assignment operator is used within any valid expression. The general form of the assignment operator is
$$\text{variable_name} = \text{expression};$$
- where an expression may be as simple as a single constant or as complex as you require. C uses a single equal sign to indicate assignment .
- The *target*, or left part, of the assignment must be an object, such as a variable, that can receive a value.

A

AMAN SONI

R

Ritu Sibbal

🧘

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

ABHIJEET SHAR... and 62 more

12:12 PM

You

Multiple Assignments

- Many variables can be assigned the same value by using multiple assignments in a single statement.
- For example, this program fragment assigns **x**, **y**, and **z** the value 0:

```
x = y = z = 0;
```

A

AMAN SONI

R

Ritu Sibbal

🧘

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

AKASH SHEKHAR PAUNI... and 63 more

70

12:13 PM

You

Compound Assignments

- For simplifying coding of assignment operation.
$$x = x + 10;$$
can be written as
$$x += 10;$$
- The operator `+=` tells the compiler to assign to `x` the value of `x` plus 10.
- Compound assignment operators exist for all the binary operators (those that require two operands).
- In general, statements like
$$var = var \text{ operator } expression$$
can be rewritten as
$$var \text{ operator } = expression$$
- For another example,
$$x = x - 100;$$
is the same as
$$x -= 100;$$

A

AMAN SONI

R

Ritu Sibbal

🌙

DHRUV KUMAR

🌳

ROHIT SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

A ARUSHEE VERMA and 61 more

12:14 PM

You

Arithmetic Operators


Operator	Action
-	Subtraction, also unary minus
+	Addition
*	Multiplication
/	Division
%	Modulus
--	Decrement
++	Increment

A

AMAN SONI

R

Ritu Sibbal



DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

Ritu Sibbal is presenting

ASHISH KANT and 61 more

12:14 PM

You

The Increment and Decrement Operators

- C includes two useful operators that simplify two common operations. These are the increment and decrement operators, ++ and --. The operator ++ adds 1 to its operand, and -- subtracts 1. In other words:
$$x = x + 1;$$

is the same as
$$++x;$$

and
$$x = x - 1;$$


is the same as
$$x--;$$

A

AMAN SONI

R

Ritu Sibbal



DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

ISHAAN KUMAR and 61 more

12:14 PM

You

Both the increment and decrement operators may either precede (prefix) or follow (postfix) the operand. For example,

$$x = x + 1;$$

can be written

$$++x;$$

or

$$x++;$$

AMAN SONI

R Ritu Sibbal

DHRUV KUMAR

S SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R

Ritu Sibbal is presenting

M

MAHIKA KUSHW...
and 61 more

12:15 PM

- There is, however, a difference between the prefix and postfix forms when you use these operators in a larger expression.
- When an increment or decrement operator precedes its operand, the increment or decrement operation is performed before obtaining the value of the operand for use in the expression.
- If the operator follows its operand, the value of the operand is obtained before incrementing or decrementing it.

A

AMAN SONI

R

Ritu Sibbal

🧘

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R

Ritu Sibbal is presenting

M

MOKSHI SHAR...
and 62 more

12:15 PM

Example

```
x = 10;  
y = ++x;  
sets y to 11. However, if you write the code as  
x = 10;  
y = x++;  
y is set to 10. Either way, x is set to 11; the difference is in when it happens
```

A

AMAN SONI

R

Ritu Sibbal

🧘

DHRUV KUMAR

👤

NITASH BISWAS

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

R Ritu Sibbal is presenting

R RITHIK KUMAR and 62 more

12:16 PM

You

Precedence of Operators

- Here is the precedence of the arithmetic operators:
- Highest**
 - $++$ $--$
 - $-(\text{unary minus})$
 - $*$ $/$ $\%$
- Lowest**
 - $+$ $-$

- Operators on the same level of precedence are evaluated by the compiler from left to right.
- Parentheses may be used to alter the order of evaluation.
- Parentheses force an operation, or set of operations, to have a higher level of precedence.

A

AMAN SONI

R

Ritu Sibbal

DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

+

meet.google.com/ztd-wppv-iwi?authuser=0

VINIT and 62 more

12:17 PM

R Ritu Sibbal is presenting

A

AMAN SONI

R

Ritu Sibbal

DHRUV KUMAR

S

SHUBHAM SHARMA

Relational and Logical operators

- In the term relational operator, *relational* refers to the relationships that values can have with one another. In the term logical operator, *logical* refers to the ways these relationships can be connected.
- The idea of true and false underlies the concepts of relational and logical operators.
- In C, true is any value other than zero. False is zero. Expressions that use relational or logical operators return 0 for false and 1 for true.

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

ABHIJEET SHAR... and 62 more

12:18 PM

R Ritu Sibbal is presenting

p	q	p & q	p q	!p
0	0	0	0	1
0	1	0	1	1
1	1	1	1	0
1	0	0	1	0

A AMAN SONI

R Ritu Sibbal

🧘 DHRUV KUMAR

S SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

ANANT and 62 more

12:18 PM

You

R Ritu Sibbal is presenting

• **Highest**

!

>>=<<=

= = !=

&&

Lowest


||

A

AMAN SONI

R

Ritu Sibbal



DHRUV KUMAR

S

SHUBHAM SHARMA

Course stream

Meet - ztd-wppv-iwi

meet.google.com/ztd-wppv-iwi?authuser=0

70

12:19 PM

You

R Ritu Sibbal is presenting

A ARYAMAN SOOD and 63 more

- As with arithmetic expressions, you can use parentheses to alter the natural order of evaluation in a
- relational and/or logical expression.
- For example,
 !0&&0 || 0
 is false. However, when you add parentheses to the same expression,
 !(0 && 0) || 0
 the result is true.
- Remember, all relational and logical expressions produce a result of either 1 or 0. Therefore, the
- following program fragment is not only correct, but will print the number 1.

```
int x;  
x = 100;  
printf('%d', x>10);
```

A

AMAN SONI

R

Ritu Sibbal

😴

DHRUV KUMAR

S

SHUBHAM SHARMA