

VRC MIX

(LOW & MEDIUM) PRESSURE SPRAY
PAINTING EQUIPMENT



ADVANCED VARIABLE RATIO ELECTRONIC TWO COMPONENT SYSTEM

- ◆ Accurate- Component metering by precision geared flow meters
- ◆ Reliable- Online mixing ratio assurance
- ◆ Ease to use- User friendly touch screen operation interface
- ◆ Multi colour operation- Quick colour change
- ◆ Material usage reporting

TECHNICAL SPECIFICATIONS

COMPARISON	MANUAL	VRC – MIX	FAULTS	ALARM	SYSTEM
Online ratio assurance	NO	YES	Off- mixing ratio	Audio + Visual alarm with text message	Auto shut off
Fresh material mixing on demand	NO	YES	Pot life nearing end	Audio + Visual alarm with text message	
Pot life monitor	NO	YES	Pot life end	Audio + Visual alarm with text message	Auto shut off
Material usage report	NO	YES	Container nearing to empty	Audio + Visual alarm with text message	
Paint / solvent wastage	HIGH	NO	Container empty	Audio + Visual alarm with text message	Auto shut off
Colour change, configuration & setup time	HIGH	VERY LOW	Surpass of set pressure limits	Audio + Visual alarm with text message	Auto shut off
Labour cost	HIGH	LOW	Other system fault & Interlocks	Audio + Visual alarm with text message	

FEATURES	STANDARD	OPTIONAL (ON REQUEST)
Mixing ratio range	Up to 15:0 (in 0.1 increment)	
Accuracy tolerance	Down to 1% users settable	
Flow rate	0.1 to 4 liters per minute	Higher flow rate
Maximum fluid pressure	Air spray system – 30 bars	
Air pressure requirement	0-7 bars	
Electrical power requirement	230 V AC 50 Hz Single phase	As per available power source
Multi colour application (colour change facility)	colour, hardeners, solvents, different recipes can be stored	Modular system. Extra colour and recipe addition
Flushing	Manual as well as inbuilt auto flushing cycle programmable sequential air solvent purge	
Material usage reporting	Reporting of component consumption accumulative + daily consumption	
Pot life monitoring	Pot life monitoring of mixed material	
Pressure monitoring	Online system health checking by pressure monitoring	
Level monitoring		Online container level monitoring based on material consumption
Remote operator panel		Ex- proof remote operator panel
Communication	RS 232 communication port for printer/ network/ PC. Protocol Modbus	SCADA
Operator Interface	Touch screen graphical display with audio visual alarm system	

ACCESSORIES



VR Coatings Pvt.Ltd.

Registered Office:
J-138 MIDC,
Bhosari, Pune 411026
Maharashtra, INDIA

☎ +91 98 2291 29 14
✉ sales@vrcoatings.com
🌐 www.vrcoatings.com

