

HIPPO PUMP

DOUBLE DIAPHRAGM PUMP



This compact, high efficiency diaphragm pump is designed for smooth fluid transfer in industrial environments. Its corrosion-resistant build and consistent output make it ideal for water based and chemical fluids under moderate pressure and temperature conditions.

FEATURES

- ◆ Operates with low air consumption for energy efficiency
- ◆ Built with corrosion-resistant and chemically compatible materials
- ◆ Suitable for water-based and light chemical fluids
- ◆ Compact and lightweight for easy installation and mobility
- ◆ Designed to maintain consistent flow under varying conditions

APPLICATIONS

- ◆ Pulsation-Free Transfer System
Specially designed for pulsation-free paint spray applications ensuring smooth finish.
Also used for transferring oil, paint, chemicals, and other industrial fluids efficiently.

ACCESSORIES



TECHNICAL SPECIFICATIONS

CATEGORY	DATA
Pressure ratio	1 : 1
Discharge per cycle (cc)	140
Recommended spray volume @40 cycles/min (lpm)	5.6
Max fluid temperature ambient condition	T4
T rating	135° C
Wetted part	304 stainless steel /PTFE/ Silicon
Maximum Inlet air pressure (bar)	6
Maximum output pressure @ 6 bar air inlet	6
Air consumption N-LPM	30
PORT SIZE	
Fluid inlet	3/4" BSP (F)
Fluid outlet	3/8" BSP (F)
Air inlet	1/4" BSP



VR Coatings Pvt.Ltd.

Registered Office:
J-138 MIDC,
Bhosari, Pune 411026
Maharashtra,INDIA

+91 98 2291 29 14
sales@vrcoatings.com
www.vrcoatings.com

