

LION

Hydraulic high-volume
fluid transfer pump



LION is a hydraulically driven, high-volume industrial fluid-transfer pump designed for continuous circulation and feeding duties. Its 4000 cc theoretical displacement and recommended delivery of 60 L/min at 15 cycles make it suitable for centralized coating and process-fluid handling systems.

FEATURES

- ◆ Hydraulic drive for stable, continuous industrial transfer duty
- ◆ 4000 cc theoretical hydraulic capacity per cycle
- ◆ Recommended delivery of 60 L/min at 15 cycles
- ◆ Maximum oil inlet pressure of 120 bar
- ◆ Heavy-duty wetted parts with chrome-plated and carbide components
- ◆ Floor-mounted construction for fixed industrial installations

APPLICATIONS

◆ Bulk Paint & Coating Transfer

High-volume movement of primers, topcoats and compatible coating materials between storage and process equipment.

◆ Central Paint-Kitchen Circulation

Suitable for continuous circulation and feeding in centralized paint supply installations.

◆ Production-Line Fluid Feeding

Feeds compatible process fluids to dispensing, coating or finishing stations where steady volume is required.

◆ Tank / Drum Unloading

Supports transfer from bulk containers into day tanks, circulation loops or downstream process equipment.

TECHNICAL SPECIFICATIONS

TYPE	SPECIFICATION
Pressure Ratio	0.14:1
Hydraulic Motor Type (mm)	D66 (Ø66)
Hydraulic Capacity / Cycle (Theoretical)	4000 cc
Dimension (D x H) mm	Ø 500 x 1600 HEIGHT
Recommended Spray Volume @ 15 Cycles (L/Min)	60 L/Min
Oil Consumption @ 1 Cycle	0.59 L/Cycle
Oil Flow Rate at 10 Bar & @ 15 Cycles	8.85 L/Min
Maximum Oil Inlet Pressure (Pressure Safety Set)	120 Bar
Maximum Fluid Outlet Pressure @ 120 Bar Oil Inlet	16.8 Bar
Maximum Fluid Temp	(II 2G Ex h IIB T4 Gb)
Wetted Parts	Carbon Steel Chrome Plated Cylinder & Piston, Tungsten Carbide Seat. PTFE seal rings.
Weight	~ 132 kg (net weight, std pump)



VR Coatings Pvt.Ltd.

Registered Office:
J-138 MIDC,
Bhosari, Pune 411026
Maharashtra,INDIA



+91 98 2291 29 14



sales@vrcoatings.com



www.vrcoatings.com

