

VALVES



COLOUR CHANGE VALVE (DOUBLE DISC)

Suitable for colour change application in airless and air-assisted airless systems.
Fast easy colour changing

VALVE SEAT ID	CCV 250	2MM
	CCV 400	2MM
FULLY STAINLESS STEEL	Suitable for water based materials, Compact Easy to maintain and service Fast efficient valve action	
MAXIMUM WORKING PRESSURE	CCV 250	250 BAR
	CCV 400	400 BAR
INLET/CIRCULATION PORT	1/4" BSP(F)	
WETTED PARTS	304, STAINLESS STEEL, PTFE, VITON	
VALVE SEATS & BALL	TUNGSTEN CARBIDE	
CONTROL SYSTEM	PLC-BASED ELECTRO-PNEUMATIC OR COMPLETE PNEUMATIC CONTROL	




COLOUR CHANGE VALVE (SINGLE DISC)

VALVE SEAT ID	2 MM
FULLY STAINLESS STEEL	SUITABLE FOR WATER BASED MATERIALS, COMPACT EASY TO MAINTAIN AND SERVICE FAST EFFICIENT VALVE ACTION
MAXIMUM WORKING PRESSURE	300 BAR
INLET/CIRCULATION PORT	1/4" BSP (F)
WETTED PARTS	304 STAINLESS STEEL/TUNGSTEN PTFE /VITON/ CARBIDE BODY
VALVE SEATS & BALL	TUNGSTEN CARBIDE
CONTROL SYSTEM	PLC-BASED ELECTRO-PNEUMATIC OR COMPLETE PNEUMATIC CONTROL



VALVES



COLOUR CHANGE VALVE (LOW PRESSURE)

- ◆ Suitable for colour change application in air assisted spray systems.
- ◆ Basic Module consists of three valves, two for colour and one for solvent valve.
- ◆ Add on module consists of two colour valves.
- ◆ Any number of colours possible.
- ◆ Fast easy colour changing.



RESULTANT FLUID PATH	EQUIVALENT TO 4 MM HOLE (12.56 MM ²)
FULLY STAINLESS STEEL	SUITABLE FOR WATER BASED MATERIALS COMPACT EASY TO MAINTAIN, AND SERVICE, FAST EFFICIENT VALVE ACTION.
MAXIMUM WORKING PRESSURE	40 BAR
INLET/CIRCULATION PORTS	1/4" BSP (F)
WETTED PARTS	304 STAINLESS STEEL, PTFE, DELRIN
CONTROL SYSTEM	PLC-BASED ELECTRO-PNEUMATIC OR COMPLETE PNEUMATIC CONTROL



AUTOMATIC FEEDING (ON/OFF) VALVE 3.0MM, 6.5MM

MAXIMUM WORKING PRESSURE	500 BAR, (FOR 3 MM), 225 BAR (FOR 6.5 MM) 240 BAR (FOR 10MM)
OUTLET HOLE SIZE	3.0 MM, 6.5 MM, (10MM)
SWITCHING AIR INLET PRESSURE	UP TO 8 BAR (DOUBLE ACTING)
INLET/CIRCULATION PORTS	1/4" BSP(F) FOR 3 MM, 3/8" BSP(F) FOR 6.5 MM, 1/2 BSP(F) FOR 10MM
OUTLET PORT	3/8" BSP(F) SWIVEL, 1/2" BSP(F) SWIVEL
WETTED PARTS	304 STAINLESS STEEL, TUNGSTEN CARBIDE VALVE, PTFE
CONTROL SYSTEM	PLC-BASED ELECTRO-PNEUMATIC OR COMPLETE PNEUMATIC CONTROL



VR Coatings Pvt.Ltd.

Registered Office:
J-138 MIDC,
Bhosari, Pune 411026
Maharashtra, INDIA

☎ +91 98 2291 29 14
✉ sales@vrcoatings.com
🌐 www.vrcoatings.com

