Everllence

Connectivity Information PrimeServ Assist

This document gives information about the technical requirements for the customer`s side of the connection to Everllence CEON.

Connection Device (DELL Edge Gateway 3002)

Interface:
Fast Ethernet (RJ-45) mit PoE

Transmission physics:
Max. 100m per segment, twisted pair

Transmission speed:
10/100MBit/s

Power supply:
9 - 32 VDC

bruno.peradelli@gnv.it
10/10/2025 at 09:50 UTC

Network Availability of Customer Digital Infrastructure:

- A static or DHCP provided Internet Address with access to the Contractor Everllence CEON Cloud is required in order to provide Service Delivery.
- Continuous connectivity to communications gateway installed on customer network needs to be provided to the following destination domains/IP:
  - For CEON access **TCP Port 443** for
    - **assethub.mya.io** — **35.156.61.78 / 35.156.77.222 / 35.157.233.80**
    - **upgrades.mya.io** — **35.156.61.78 / 35.156.77.222 / 35.157.233.80**
    - **assethub.manceon.io** — **35.156.61.78 / 35.156.77.222 / 35.157.233.80**
  - For time syncronization open **UDP Port 123** for
    - **ntp.ubuntu.com**
    - **ntp.manceon.io** — **35.156.61.78 / 35.156.77.222 / 35.157.233.80**

We recommend to set firewall whitelist rules with the domain names listed above.
If not possible please use IPs.

Please forward this checklist to your IT Department / Internet provider.