

C interfaces to GALAHAD HASH

Jari Fowkes and Nick Gould STFC Rutherford Appleton Laboratory Sun Apr 2 2023

1 GALAHAD C package gltr	1
1.1 Introduction	1
1.1.1 Purpose	1
1.1.2 Authors	1
1.1.3 Originally released	1
1.1.4 Terminology	2
1.1.5 Method	2
1.1.6 Reference	2
1.1.7 Call order	2
2 File Index	3
2.1 File List	3
3 File Documentation	5
3.1 galahad_gltr.h File Reference	5
3.1.1 Data Structure Documentation	5
3.1.1.1 struct gltr_control_type	5
3.1.1.2 struct gltr_inform_type	6
3.1.2 Function Documentation	7
3.1.2.1 gltr_initialize()	7
3.1.2.2 gltr_read_specfile()	7
3.1.2.3 gltr_import_control()	8
3.1.2.4 gltr_solve_problem()	8
3.1.2.5 gltr_information()	9
3.1.2.6 gltr_terminate()	10
4 Example Documentation	11
4.1 gltrt c	11

Chapter 1

GALAHAD C package hash

1.1 Introduction

1.1.1 Purpose

Set up, insert into, remove from and search a chained scatter table (Williams, CACM 2, 21-24, 1959).

Currently, only the control and inform parameters are exposed; these are provided and used by other GALAHAD packages with C interfaces.

1.1.2 Authors

N. I. M. Gould, STFC-Rutherford Appleton Laboratory, England.

C interface, additionally J. Fowkes, STFC-Rutherford Appleton Laboratory.

Julia interface, additionally A. Montoison and D. Orban, Polytechnique Montréal.

1.1.3 Originally released

December 1990, C interface January 2022.

GALAHAD 4.0 C interfaces to GALAHAD HASH

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:	
galahad_hash.h	??

4 File Index

GALAHAD 4.0 C interfaces to GALAHAD HASH

Chapter 3

File Documentation

3.1 galahad_hash.h File Reference

```
#include <stdbool.h>
#include <stdint.h>
#include "galahad_precision.h"
#include "galahad_cfunctions.h"
```

Data Structures

- struct hash_control_type
- struct hash_inform_type

3.1.1 Data Structure Documentation

3.1.1.1 struct hash_control_type

Data Fields

int	error	error and warning diagnostics occur on stream error
int	out	general output occurs on stream out
int	print_level	the level of output required. Possible values are:
		• \leq 0 no output, $• \geq$ 1 debugging
bool	space_critical	if space_critical true, every effort will be made to use as little space as possible. This may result in longer computation time
bool	deallocate_error_fatal	if deallocate_error_fatal is true, any array/pointer deallocation error will terminate execution. Otherwise, computation will continue
char	prefix[31]	all output lines will be prefixed by prefix(2:LEN(TRIM(prefix))-1) where prefix contains the required string enclosed in quotes, e.g. "string" or 'string'

6 File Documentation

3.1.1.2 struct hash_inform_type

Data Fields

int	status	return status. 0 is a successful call
int	alloc_status	the status of the last attempted allocation/deallocation
char	bad_alloc[81]	the name of the array for which an allocation/deallocation error ocurred

GALAHAD 4.0 C interfaces to GALAHAD HASH