



C interfaces to GALAHAD FIT

Jari Fowkes and Nick Gould
STFC Rutherford Appleton Laboratory
Sun Apr 16 2023

1 GALAHAD C package fdc	1
1.1 Introduction	1
1.1.1 Purpose	1
1.1.2 Authors	1
1.1.3 Originally released	1
1.1.4 Method	1
1.1.5 Call order	2
1.1.6 Array indexing	2
2 File Index	3
2.1 File List	3
3 File Documentation	5
3.1 galahad_fdc.h File Reference	5
3.1.1 Data Structure Documentation	5
3.1.1.1 struct fdc_control_type	5
3.1.1.2 struct fdc_time_type	6
3.1.1.3 struct fdc_inform_type	6
3.1.2 Function Documentation	7
3.1.2.1 fdc_initialize()	7
3.1.2.2 fdc_read_specfile()	7
3.1.2.3 fdc_find_dependent_rows()	8
3.1.2.4 fdc_terminate()	9
4 Example Documentation	13
4.1 fdct.c	13
4.2 fdctf.c	14

Chapter 1

GALAHAD C package fit

1.1 Introduction

1.1.1 Purpose

Fit polynomials to function and derivative data.

Currently, only the control and inform parameters are exposed; these are provided and used by other GALAHAD packages with C interfaces.

1.1.2 Authors

N. I. M. Gould and D. P. Robinson, STFC-Rutherford Appleton Laboratory, England.

C interface, additionally J. Fowkes, STFC-Rutherford Appleton Laboratory.

Julia interface, additionally A. Montoison and D. Orban, Polytechnique Montréal.

1.1.3 Originally released

March 2010, C interface January 2022.

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

galahad_fit.h	??
-------------------------------	-------	----

Chapter 3

File Documentation

3.1 galahad_fit.h File Reference

```
#include <stdbool.h>
#include <stdint.h>
#include "galahad_precision.h"
#include "galahad_cfunctions.h"
```

Data Structures

- struct [fit_control_type](#)
- struct [fit_inform_type](#)

3.1.1 Data Structure Documentation

3.1.1.1 struct fit_control_type

control derived type as a C struct

Data Fields

bool	f_indexing	use C or Fortran sparse matrix indexing
int	error	error and warning diagnostics occur on stream error
int	out	general output occurs on stream out
int	print_level	the level of output required is specified by print_level
bool	space_critical	if space_critical is true, every effort will be made to use as little space as possible. This may result in longer computation times
bool	deallocate_error_fatal	if deallocate_error_fatal is true, any array/pointer deallocation error will terminate execution. Otherwise, computation will continue
char	prefix[31]	all output lines will be prefixed by .prefix(2:LEN(TRIM(.prefix))-1) where .prefix contains the required string enclosed in quotes, e.g. "string" or 'string'

3.1.1.2 struct fit_inform_type

inform derived type as a C struct

Data Fields

int	status	return status. Possible values are: <ul style="list-style-type: none">• 0 Normal termination with the required fit• -1 An allocation error occurred; the status is given in the component .alloc_status• -2 A deallocation error occurred; the status is given in the component alloc_status• -3 the restriction $n \geq 1$ has been violated
int	alloc_status	the status of the last attempted allocation/deallocation
char	bad_alloc[81]	the name of the array for which an allocation/deallocation error occurred