C10 DevOps and cost

Git integration, deployment pipelines and capacity monitoring.

C10-L1 Git integration for Fabric workspaces

One workspace per developer on its own branch, pull requests into main, and a data reload plan, because Git holds definitions, not data.

What Git integration stores for a lakehouse	Metadata only: name, shortcuts, OneLake security roles. Not tables or files.
Commit vs Update	Commit exports workspace changes to Git. Update imports Git changes and overwrites the workspace version.
Who connects a workspace to Git?	Admin only. Members and Contributors commit and update. Viewers see no Git information.
Recommended development process	One workspace per developer on its own branch. Pull requests into main.

C10-L2 Deployment pipelines, dev to test to production

Stage-specific settings belong in deployment rules. Compare before you deploy. Reload data after, because deployments copy items, not data.

Deployment pipeline stages	2 to 10 stages, default Development, Test, Production. One workspace per stage.
What a deployment copies	Item content and metadata. Not data: refresh models and reload tables after.
Deployment rule types	Data source, parameter, default lakehouse. Defined in the target stage on the item.
Deploying over an existing item	Content is overwritten. ID, URL and permissions stay the same.

C10-L3 Capacity, smoothing and throttling

Know which of your jobs are background, run them off-peak, protect production with surge protection, and read the Metrics app before you resize.

Smoothing windows	Interactive: 5 to 64 minutes. Background: 24 hours. Timepoints are 30 seconds, 2,880 a day.
Throttling stages	Up to 10 min: none. 10 to 60: 20 s interactive delay. 60 min to 24 h: interactive rejection. Over 24 h: all rejected.
Surge protection	Capacity level: earlier background rejection. Workspace level: cap a workspace's CU share over 24 hours, except Mission Critical.
Capacity Metrics app	Installed by a capacity admin. Health page for throttling. Compute page for 14 days of usage.

C10-L4 Sizing a capacity, from trial to the right F SKU

Measure a real peak on a trial, compare it with each SKU's 30-second budget plus headroom, check the F64 licence floor, then reserve only once the load is steady.

Capacity units of an F SKU	The number in its name: F2 has 2, F64 has 64. Trial capacity has 64.

Budget per 30-second window	CUs times 30. An F64 has 1,920 CU-seconds per window.
The F64 licence floor	Below F64, every Power BI viewer needs Pro or PPU. From F64, free-licence users with a viewer role can view.
Sizing method	Trial, read the peak in the Metrics app, pick the smallest SKU covering peak plus headroom, scale and check.