Phase 1, days 1 to 30: Orient

EY: Talent Data Strategy

E1 UK GDPR and special category data in HR

E1-L1 Personal data, special category data and the two-part test

Classify each attribute by what it reveals. Keep the special categories and the protected characteristics as two separate fields, and treat inferences as data.

The nine special categories	Racial or ethnic origin, political opinions, religious or philosophical beliefs, trade union membership, genetic, biometric (to identify), health, sex life, sexual orientation.
Is an inferred special category special category data?	Yes. A model that infers health or ethnicity processes special category data.
Age and sex	Protected characteristics under the Equality Act 2010. Not special categories.
The two-part test	An Article 6 lawful basis for all personal data, plus an Article 9 condition for special category data.

E1-L2 A lawful basis for each use of talent data

Give each purpose its own lawful basis, avoid consent for workers, record a legitimate interests assessment for each use of legitimate interests, and keep only the fields each purpose needs.

The seven lawful bases	Consent, contract, legal obligation, vital interests, public task, legitimate interests, and recognised legitimate interests since 5 February 2026.
Consent for employee data	Rarely appropriate. The power imbalance makes it hard to give freely. Use another basis.
Legitimate interests assessment	Purpose, necessity, balancing, recorded before processing starts.
Purpose limitation	A basis covers the purposes you specified. A new purpose, such as an attrition model, needs its own check.
Recognised legitimate interests	Article 6(1)(ea), from 5 February 2026. Only the purposes in Annex 1, with no balancing test.

E1-L3 Article 9 conditions, policy documents and DPIA screening in HR

Pair each Article 9 condition with its Schedule 1 condition and an appropriate policy document, keep monitoring data away from individual decisions, and screen every new use for a DPIA.

Employment condition in the UK	Article 9(2)(b) plus Schedule 1, Part 1, paragraph 1 of the DPA 2018, with an appropriate policy document.
Diversity monitoring	Article 9(2)(g) plus Schedule 1 paragraph 8, equality of opportunity or treatment. Never for decisions about one person.
Appropriate policy document	Names the Schedule 1 condition, how you meet the principles, and retention and erasure. One APD can cover several purposes.

When a DPIA is mandatory	Before high-risk processing, always for large-scale special category data and extensive profiling with significant effects. Consult the ICO if high risk remains.

E1-L4 Writing the DPIA for a people model

Cover the four parts of Article 35(7). Name each harm, rate it, put fairness figures in the risk section, record measures and residual risk, and consult the ICO if a high risk remains.

Article 35(7): four required parts of a DPIA	Description and purposes, necessity and proportionality, risks to people, and the measures that address them.
ICO template risk scales	Likelihood: remote, possible, probable. Severity: minimal, significant, severe. Overall: low, medium, high.
Where fairness goes in a DPIA	In the risk section, with flag rates per group, the ratio and the threshold for action.
High residual risk	Consult the ICO before processing starts.

E1-L5 Personal data in each medallion layer

Keep raw identifiers in bronze for a few people, pseudonymise with a keyed hash in silver, suppress small groups in gold, and record each choice. Pseudonymised data is still personal data.

Pseudonymisation, UK GDPR Article 4(5)	Data no longer attributable to a person without additional information that is kept separately and protected.
Is pseudonymised data personal data?	Yes. You hold the key. It lowers the risk; the law still applies.
Why a keyed hash?	A plain hash of a known-format ID is matched by hashing every possible value. HMAC with a secret key prevents that.
Personal data per layer	Bronze raw for a named few, silver pseudonymised, gold aggregated with small groups suppressed.

E2 DAMA-DMBOK applied to talent data

E2-L1 The DAMA wheel, eleven knowledge areas around governance

Name the knowledge area before you name the fix. Governance at the hub assigns an owner to each area, so problems reach the person who can solve them.

DAMA wheel	Data governance at the hub, ten knowledge areas around it. DMBOK2, revised in 2024.
DMBOK2 definition of data governance	The exercise of authority, control and shared decision-making (planning, monitoring and enforcement) over the management of data assets.
Reference data, master data, metadata	Reference: lists of codes. Master: the agreed record of a core entity. Metadata: data about data.
First move on any data problem	Name the knowledge area, then its owner, then the fix.

E2-L2 A maturity baseline you can defend

Score a grid of knowledge areas by talent domain, in whole levels, with evidence for each score, and report the weakest area per domain.

A common 0 to 5 maturity scale	0 none, 1 initial, 2 repeatable, 3 defined, 4 managed, 5 optimised. Agree and version the names with stakeholders.
The baseline grid	Knowledge areas by talent domain: workforce, recruitment, learning, performance, mobility, skills.
Summarise a domain by	Its weakest area and score. A mean hides gaps.
A defensible score	A whole level with cited evidence: a document, a metric or a log.

E2-L3 Governance at the hub, decision rights, policies and escalation

Separate deciding from doing. Name a decider for each kind of decision, write rules as policy, standard and procedure, and log each decision with its reason.

Governance against management	Governance decides and oversees. Management does the work.
Decision rights to name first	Definitions, access to sensitive fields, quality thresholds, and new uses of data.
Policy, standard, procedure	Policy: what and why. Standard: measurable. Procedure: how. Each changes at its own pace.
Escalation path	Data steward, data owner, governance council. Log every decision with its reason.

E2-L4 People master data, match rules and survivorship

Match in bands, with only deterministic keys merging automatically. Choose each field's value by a written rule, never let a blank win, and keep the cross-reference.

Deterministic or probabilistic matching	Deterministic: exact keys, easy to explain, misses typos. Probabilistic: similarity score, catches more, makes false matches.
Match bands	Merge above a high score, keep apart below a low one, and send the middle band to a data steward.
Common survivorship rules	Source priority, most recent, most complete. A blank never overwrites a value.
Why keep a cross-reference?	Later deliveries find their person by source ID, and a false merge can be undone.

E2-L5 A RACI and a business glossary for talent data

Give every activity exactly one A and at least one R, name roles rather than people, and keep each glossary term with a rule, an owner, a steward, a system of record and a versioned status.

RACI letters	R does the work, A owns and signs off (exactly one), C is asked before, I is told after.
Two RACI failures	Two accountable roles, so each waits or approves their own; no accountable role, so nobody signs off.
Glossary entry fields	Term, definition, calculation rule, owner, steward, system of record, related terms, status with version and date.
Where to start a glossary	The 15 terms used most in people reports, not the whole vocabulary.

C0 Start here: foundations for Fabric

C0-L1 Data platform vocabulary, files, tables, lakes and warehouses

Keep data once, in a typed table format such as Delta, and let each engine read it, instead of exporting copies to untyped files.

CSV, Parquet and Delta	CSV: text, no types. Parquet: columnar, typed, compressed. Delta: Parquet files plus a transaction log with versions.
Lake, warehouse, lakehouse	Lake: files, structure on read. Warehouse: typed tables for SQL. Lakehouse: open tables in a lake, read by Spark and SQL.
ELT and medallion stages	Load raw first, transform inside the platform: bronze (as received), silver (clean), gold (aggregated).
Fabric's names for these	OneLake is the one lake (GA). Lakehouse tables are Delta (GA). The SQL analytics endpoint queries them with T-SQL (GA).

C0-L2 Power BI basics, reports, semantic models and measures

Put ratios in measures that divide totals, and let filter context decide what each total covers.

```
Weighted reach % = DIVIDE ( SUM ( fact[reach] ), SUM ( fact[base] ) )
```

Data, semantic model, report	Data sits in source tables. The model describes tables, relationships and measures. Reports hold visuals that query the model.
Calculated column against measure	A column is worked out per row and stored. A measure is worked out when a visual asks, in that visual's filter context.
Ratios in Power BI	A measure dividing totals: DIVIDE (SUM (reach), SUM (base)). Never average per-row percentages.
Import, DirectQuery, Direct Lake	Import copies and refreshes. DirectQuery queries the source each time. Direct Lake (GA) reads OneLake Delta tables directly.

C0-L3 Two engines, one table, Spark notebooks and the SQL analytics endpoint

One Delta table, two engines: write and transform with Spark, query with T-SQL on the SQL analytics endpoint.

```python
from pyspark.sql import functions as F

df = spark.read.table("respondents")
totals = df.filter(F.col("final_weight") > 0).groupBy("region").agg(F.sum("final_weight").alias("total"))
totals.show()
```

```sql
SELECT region, SUM(final_weight) AS total
FROM dbo.respondents
WHERE final_weight > 0
GROUP BY region;
```

Two engines over one lakehouse table	Spark in notebooks reads and writes. The SQL analytics endpoint queries with T-SQL and is read-only for table data.
Append rows to a lakehouse table from Spark	df.write.mode("append").saveAsTable("respondents"). mode("overwrite") replaces the rows.

Spark transformations against actions	filter, groupBy, agg, select describe a new DataFrame. show, count, collect run the plan.
Where to put T-SQL writes	In a Warehouse. The lakehouse's SQL analytics endpoint does not write table data.

C1 Fabric architecture

C1-L1 Tenant, capacity, workspace and item

The capacity decides who can view, how much runs at once and what it costs. Separate environments into workspaces, and give production its own capacity.

Fabric hierarchy	Tenant, capacity, workspace, item.
What F64 means	An F SKU with 64 capacity units. F SKUs run from F2 to F2048.
Free-licence viewers of Power BI content	Need an F64 or larger (or P) capacity. Smaller F SKUs need Pro, PPU or trial licences for viewers.
Pausing a capacity	Stops compute billing from then on, bills remaining smoothed and overage usage at once, and stops its items.

C1-L2 OneLake, one lake per tenant

One lake, one copy, many engines. Address data by GUID in anything automated.

```
https://onelake.dfs.fabric.microsoft.com/<workspace>/<item>.<itemtype>/<path>
abfss://<workspace>@onelake.dfs.fabric.microsoft.com/<item>.<itemtype>/<path>
```

How many OneLakes per tenant?	Exactly one. You cannot create or delete OneLakes.
OneLake table formats	Delta Parquet or Iceberg, open formats every Fabric engine reads.
OneLake path by name	abfss://<workspace>@onelake.dfs.fabric.microsoft.com/<item>.<itemtype>/Tables/<table>.
Why GUIDs in automation	They survive renames, avoid special-character problems in abfs URIs, and drop the item type.

C1-L3 Workspace roles, granted to groups

Roles go to groups, write access in production goes to automation, and people read.

Fabric workspace roles	Admin, Member, Contributor, Viewer.
Admin-only rights	Update or delete the workspace, manage admins, connect Git, create a workspace identity.
Viewer and lakehouse data	Reads with T-SQL (ReadData). Not through Spark or OneLake APIs (ReadAll starts at Contributor).
Who writes to production?	An automation identity as Contributor. People get Viewer, through groups.

C2 Lakehouse, Warehouse and SQL analytics endpoint

C2-L1 Lakehouse Tables and Files, and schemas

Raw files in Files, Delta tables in Tables, and schema-qualified names in shared code.

Lakehouse Tables vs Files	Tables: managed Delta tables, visible to SQL and Direct Lake. Files: raw and non-Delta data.
Non-Delta folder under Tables	Shown in the Unidentified area, not queryable.
Lakehouse schemas	On by default for new lakehouses. dbo is the fixed default schema.
Spark four-part name	workspace.lakehouse.schema.table. A bare name means dbo in the default lakehouse.

C2-L2 Warehouse T-SQL, and where it differs from SQL Server

Map the types, declare keys as NOT ENFORCED hints, and check uniqueness yourself after every load.

Primary keys in Fabric Warehouse	Only PRIMARY KEY NONCLUSTERED ... NOT ENFORCED. Duplicates are not blocked.
nvarchar, money, datetime in Fabric Warehouse	Not supported. Use varchar, decimal, datetime2.
MERGE and TRUNCATE in Fabric Warehouse	Both supported. MERGE is generally available.
Triggers in Fabric Warehouse	Not supported. Put the logic in the loading procedure.

C2-L3 Lakehouse, Warehouse or SQL analytics endpoint

The data and the logic are the same. The item type decides whether the procedure runs at all, and whether a failure leaves the tables consistent.

Lakehouse, Warehouse or endpoint: the deciding question	Who writes the data, and in which language? Spark writes to a lakehouse, T-SQL writes to a warehouse.
What can you do on the SQL analytics endpoint?	SELECT and create views, functions and procedures. No INSERT, UPDATE or DELETE on table data.
When do you need a Warehouse over a Lakehouse?	T-SQL writes, stored procedure loads, and multi-table transactions.
Read a lakehouse table from a warehouse in the same workspace	Use a three-part name: lakehouse.schema.table. No copy.
A new lakehouse table is missing from the endpoint	Metadata sync lag. Usually under a minute. Refresh or retry before dependent steps.

C3 Unifying datasets

C3-L1 OneLake shortcuts, and the delete that goes through

Shortcuts save copies. Treat every path under a shortcut as someone else's data.

What a shortcut is	A folder that points to data in OneLake or external storage, without copying it.

Delete the shortcut vs delete inside it	Deleting the shortcut keeps the data. Deleting files inside it deletes them in the target, if you can write there.
Shortcut as a table	Create it under Tables, pointing at Delta data.
External shortcut caching	OneLake caches read files for 1 to 28 days to cut egress.

C3-L2 Mirroring operational databases into OneLake

Mirroring replicates operational databases for free compute and generous storage, within per-source limits. Reconcile the table list after setup.

Shortcut or mirroring?	Shortcut for open-format data in storage. Mirroring for databases and catalogs, replicated when proprietary.
Mirroring cost	Replication compute is free. Storage is free up to 1 TB per CU. Queries use capacity.
Azure SQL Database mirroring limits	Up to 1,000 tables. Primary keys on datetime2(7), datetimeoffset(7) or time(7) block a table.
After setting up a mirror	Reconcile table lists and row counts with the source.

C3-L3 Mirroring Azure Databricks Unity Catalog into Fabric

Mirroring Unity Catalog copies no data and no permissions. Decide what is shareable, scope the connection, and rebuild access rules in Fabric.

What mirroring Unity Catalog moves	Only catalog metadata. Data is read in place through shortcuts.
Unity Catalog tables that do not mirror	Tables with row filters or column masks, federated, Delta Sharing and streaming tables, views and materialized views.
Unity Catalog permissions in Fabric	Not carried over. Rebuild access with Fabric's permission model.
Which identity reads mirrored data?	The connection's credential, for all queries. Scope it tightly.

C5 Spark notebooks in Fabric

C5-L1 From Databricks notebooks to Fabric notebooks

Replace dbutils with notebookutils, secrets with Key Vault, inline installs with environments, and pass real timeouts to child notebooks.

Fabric replacement for dbutils	notebookutils (formerly mssparkutils).
Secrets in Fabric notebooks	notebookutils.credentials.getSecret(vault_url, name), from Azure Key Vault.
notebookutils.notebook.run default timeout	90 seconds. Pass timeout_seconds.
%pip in pipeline runs	Turned off by default. Use an environment.

C5-L2 Environments, resource profiles and V-Order

Pin libraries in a Full mode environment, keep the writeHeavy default for ingestion, and turn V-Order on for read-heavy gold tables.

Environment publishing modes	Quick: installs at session start (adds minutes). Full: reproducible snapshot, recommended for pipelines.
V-Order in new workspaces	Off by default (writeHeavy profile). Write cost around 15%, faster reads.
Turn V-Order on for one table	TBLPROPERTIES("delta.parquet.vorder.enabled" = "true").
spark.sql.parquet.vorder.enable	Removed in Runtime 1.3 and later. Use spark.sql.parquet.vorder.default or table and writer options.

C5-L3 Delta tables shared between Databricks and Fabric

Open format, but not every feature for every reader. Design shared gold tables for the weakest reader that needs them.

Delta interoperability rule	Every reader must support every feature the writer put in the table.
TIMESTAMP_NTZ in Fabric	Spark yes. SQL analytics endpoint and Direct Lake no.
Runtime 2.0 default table protocol	Reader 3, writer 7, deletion vectors on. Python notebooks cannot read deletion vectors.
Check a table's features	DESCRIBE DETAIL: minReaderVersion, minWriterVersion, table features.

C10 DevOps and cost

C10-L1 Git integration for Fabric workspaces

One workspace per developer on its own branch, pull requests into main, and a data reload plan, because Git holds definitions, not data.

What Git integration stores for a lakehouse	Metadata only: name, shortcuts, OneLake security roles. Not tables or files.
Commit vs Update	Commit exports workspace changes to Git. Update imports Git changes and overwrites the workspace version.
Who connects a workspace to Git?	Admin only. Members and Contributors commit and update. Viewers see no Git information.
Recommended development process	One workspace per developer on its own branch. Pull requests into main.

C10-L2 Deployment pipelines, dev to test to production

Stage-specific settings belong in deployment rules. Compare before you deploy. Reload data after, because deployments copy items, not data.

Deployment pipeline stages	2 to 10 stages, default Development, Test, Production. One workspace per stage.
What a deployment copies	Item content and metadata. Not data: refresh models and reload tables after.
Deployment rule types	Data source, parameter, default lakehouse. Defined in the target stage on the item.
Deploying over an existing item	Content is overwritten. ID, URL and permissions stay the same.

C10-L3 Capacity, smoothing and throttling

Know which of your jobs are background, run them off-peak, protect production with surge protection, and read the Metrics app before you resize.

Smoothing windows	Interactive: 5 to 64 minutes. Background: 24 hours. Timepoints are 30 seconds, 2,880 a day.
Throttling stages	Up to 10 min: none. 10 to 60: 20 s interactive delay. 60 min to 24 h: interactive rejection. Over 24 h: all rejected.
Surge protection	Capacity level: earlier background rejection. Workspace level: cap a workspace's CU share over 24 hours, except Mission Critical.
Capacity Metrics app	Installed by a capacity admin. Health page for throttling. Compute page for 14 days of usage.

C10-L4 Sizing a capacity, from trial to the right F SKU

Measure a real peak on a trial, compare it with each SKU's 30-second budget plus headroom, check the F64 licence floor, then reserve only once the load is steady.

Capacity units of an F SKU	The number in its name: F2 has 2, F64 has 64. Trial capacity has 64.
Budget per 30-second window	CUs times 30. An F64 has 1,920 CU-seconds per window.
The F64 licence floor	Below F64, every Power BI viewer needs Pro or PPU. From F64, free-licence users with a viewer role can view.
Sizing method	Trial, read the peak in the Metrics app, pick the smallest SKU covering peak plus headroom, scale and check.

A4 Unity Catalog

A4-L1 The three-level namespace, one catalog per environment

The strong version reads exactly the table its config names, whatever the session's current catalog is.

```
research_prod.research_silver.nat_respondents
```

```
def table_name(catalog: str, layer: str, tracker: str) -> str:
    suffix = {"bronze": "raw", "silver": "respondents", "gold": "metrics"}[layer]
    return f"{catalog}.research_{layer}.{tracker}_{suffix}"
```

Unity Catalog name format	catalog.schema.table, for example research_prod.research_silver.nat_respondents.
What does each level hold in this project?	Catalog: environment. Schema: layer or governance. Table: tracker at a grain.
Why never write a two-part table name in pipeline code?	It resolves against the session's current catalog, which varies by cluster, notebook and job.
Where do table names come from?	One function built from config, such as table_name(catalog, layer, tracker).

A4-L2 Grant to groups, grant the least, grant at the right level

Three rules: groups not users, schemas not tables, SELECT for people and MODIFY for pipelines.

```
GRANT USE CATALOG ON CATALOG research_prod TO `research_analysts`;
GRANT USE SCHEMA, SELECT ON SCHEMA research_prod.research_gold TO
  `research_analysts`;
SHOW GRANTS ON SCHEMA research_prod.research_gold;
```

Privileges needed to read a table	USE CATALOG on the catalog, USE SCHEMA on the schema, SELECT on the table or schema.
Why grant SELECT on the schema rather than the table?	Schema grants are inherited by every current and future table in it.
Who gets MODIFY on production silver and gold?	The pipeline service principal. People get SELECT.
Why never grant to a user account?	User grants outlive the reason for them. Group membership is managed in one place.

A4-L3 Row filters and column masks in Unity Catalog

The strong script runs on Databricks, names groups instead of people, and uses three-part names throughout.

```
CREATE FUNCTION research_prod.research_governance.respondent_filter(tracker_id
  STRING)
RETURN is_account_group_member('research_approved_analysts') OR tracker_id = 'TRK-
  PUBLIC';

ALTER TABLE research_prod.research_silver.nat_respondents
SET ROW FILTER research_prod.research_governance.respondent_filter ON (tracker_id);
```

```
CREATE FUNCTION research_prod.research_governance.mask_postcode(postcode STRING)
RETURN CASE WHEN is_account_group_member('pii_readers') THEN postcode ELSE '***' END;

ALTER TABLE research_prod.research_silver.nat_respondents
ALTER COLUMN postcode SET MASK research_prod.research_governance.mask_postcode;
```

Row filter in Databricks	A SQL UDF returning BOOLEAN, bound with ALTER TABLE t SET ROW FILTER f ON (col).
Column mask in Databricks	A SQL UDF taking the column value, bound with ALTER TABLE t ALTER COLUMN c SET MASK f.
is_account_group_member or is_member?	is_account_group_member: Unity Catalog groups are account-level. is_member checks workspace groups.
What is CREATE ROW ACCESS POLICY?	Snowflake syntax. Databricks rejects it. Reference defect 4.