D5 Errors typical of AI-generated code

Invented APIs, deprecated calls, missing edge cases, self-confirming tests.

D5-L1 Invented functions, parameters and syntax

Look up every function, parameter and statement for your exact version, and run it on small data before it reaches a pipeline.

CREATE ROW ACCESS POLICY	Snowflake syntax. Databricks: SQL UDF plus ALTER TABLE ... SET ROW FILTER.
F.col('a').isnotnull()	Unknown attribute becomes a struct field lookup, then 'Column' object is not callable. The method is isNotNull.
Three ways to confirm an API exists	Official docs for your version, hasattr or help() in a notebook, inspect.signature for parameters.
The costly invented-API case	Code that runs: a real parameter with a different meaning, or a function from a newer version.

D5-L2 Deprecated APIs and version mismatches

Assume suggested code targets some other version. Check deprecations for yours, turn warnings into test failures, and compare versions numerically.

Chained assignment in pandas 3	df['a'][i] = x never updates df (Copy-on-Write). Use df.loc[i, 'a'] = x.
pandas 3 removals	DataFrame.append (use pd.concat) and applymap (use DataFrame.map).
input_file_name() on DBR 17.3 LTS	Not supported. Use _metadata.file_path.
Comparing version strings	Never as text: '3.10' < '3.9'. Compare integer tuples or use packaging.version.

D5-L3 Five review checks for AI-written code

Review AI code for edge cases, self-confirming tests, secrets, needless structure and, in DAX, filters removed too widely.

```
def test_share():
    assert share(3, 4) == 3 / 4   # repeats the code
```

Five review checks for AI code	Edge cases, self-confirming tests, secrets, over-engineering, DAX filter context.
Self-confirming test	Expected value computed with the code's own formula. Use hand-worked values instead.
Where secrets live	Secret scopes or Key Vault, read at run time. Never in code or prompts.
ALL(fact_table) in a share measure	Removes every filter, including wave and region slicers. Use ALL on the one dimension you mean.