

clEnqueueWriteImage

Enqueues a command to write from a 2D or 3D image object to host memory.

```
cl_int clEnqueueWriteImage (cl_command_queue command_queue,
                             cl_mem image,
                             cl_bool blocking_write,
                             const size_t origin[3],
                             const size_t region[3],
                             size_t input_row_pitch,
                             size_t input_slice_pitch,
                             const void * ptr,
                             cl_uint num_events_in_wait_list,
                             const cl_event *event_wait_list,
                             cl_event *event)
```

Parameters

command_queue

Refers to the command-queue in which the write command will be queued. *command_queue* and *image* must be created with the same OpenCL context.

image

Refers to a valid 2D or 3D image object.

blocking_write

Indicates if the write operation is *blocking* or *non-blocking*.

If *blocking_write* is CL_TRUE the OpenCL implementation copies the data referred to by *ptr* and enqueues the write command in the command-queue. The memory pointed to by *ptr* can be reused by the application after the **clEnqueueWriteImage** call returns.

If *blocking_write* is CL_FALSE the OpenCL implementation will use *ptr* to perform a nonblocking write. As the write is non-blocking the implementation can return immediately. The memory pointed to by *ptr* cannot be reused by the application after the call returns. The *event* argument returns an event object which can be used to query the execution status of the write command. When the write command has completed, the memory pointed to by *ptr* can then be reused by the application.

origin

Defines the (x, y, z) offset in pixels in the image from where to write or read. If *image* is a 2D image object, the z value given by *origin*[2] must be 0.

region

Defines the (*width*, *height*, *depth*) in pixels of the 2D or 3D rectangle being write or written. If *image* is a 2D image object, the *depth* value given by *region*[2] must be 1.

input_row_pitch

The length of each row in bytes. This value must be greater than or equal to the element size in bytes * *width*. If *input_row_pitch* is set to 0, the appropriate row pitch is calculated based on the size of each element in bytes multiplied by *width*.

input_slice_pitch

Size in bytes of the 2D slice of the 3D region of a 3D image being written. This must be 0 if *image* is a 2D image. This value must be greater than or equal to *row_pitch* * *height*. If *input_slice_pitch* is set to 0, the appropriate slice pitch is calculated based on the *row_pitch* * *height*.

ptr

The pointer to a buffer in host memory where image data is to be written to.

event_wait_list , *num_events_in_wait_list*

Specify events that need to complete before this particular command can be executed. If *event_wait_list* is NULL, then this particular command does not wait on any event to complete. If *event_wait_list* is NULL, *num_events_in_wait_list* must be 0. If *event_wait_list* is not NULL, the list of events pointed to by *event_wait_list* must be valid and *num_events_in_wait_list* must be greater than 0. The events specified in *event_wait_list* act as synchronization points. The context associated with events in *event_wait_list* and *command_queue* must be the same.

event

Returns an event object that identifies this particular write command and can be used to query or queue a wait for this particular command to complete. *event* can be NULL in which case it will not be possible for the application to query the status of this command or queue a wait for this command to complete.

Notes

Calling **clEnqueueWriteImage** to update the latest bits in a region of the image object with the *ptr* argument value set to *host_ptr* + (*origin*[2] * *image slice pitch* + *origin*[1] * *image row pitch* + *origin*[0] * *bytes per pixel*), where *host_ptr* is a pointer to the memory region specified when the image object being written is created with CL_MEM_USE_HOST_PTR, must meet the following requirements in order to avoid undefined behavior:

- The host memory region being written contains the latest bits when the

enqueued write command begins execution.

- The *input_row_pitch* and *input_slice_pitch* argument values in **clEnqueueWriteImage** must be set to the image row pitch and slice pitch.
- The image object is not mapped.
- The image object is not used by any command-queue until the write command has finished execution.

Errors

clEnqueueWriteImage return CL_SUCCESS if the function is executed successfully. Otherwise, it returns one of the following errors.

- CL_INVALID_COMMAND_QUEUE if *command_queue* is not a valid command-queue.
- CL_INVALID_CONTEXT if the context associated with *command_queue* and *image* are not the same or if the context associated with *command_queue* and events in *event_wait_list* are not the same.
- CL_INVALID_MEM_OBJECT if *image* is not a valid image object.
- CL_INVALID_VALUE if the region being write or written specified by *origin* and *region* is out of bounds or if *ptr* is a NULL value.
- CL_INVALID_VALUE if *image* is a 2D image object and *origin*[2] is not equal to 0 or *region*[2] is not equal to 1 or *slice_pitch* is not equal to 0.
- CL_INVALID_EVENT_WAIT_LIST if *event_wait_list* is NULL and *num_events_in_wait_list* greater than 0, or *event_wait_list* is not NULL and *num_events_in_wait_list* is 0, or if event objects in *event_wait_list* are not valid events.
- CL_MEM_OBJECT_ALLOCATION_FAILURE if there is a failure to allocate memory for data store associated with *image*.
- CL_OUT_OF_HOST_MEMORY if there is a failure to allocate resources required by the OpenCL implementation on the host.

Specification

 [OpenCL Specification](#)

Also see

[clEnqueueReadImage](#), [clEnqueueCopyImage](#)



Copyright © 2007-2009 The Khronos Group Inc. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and/or associated documentation files (the "Materials"), to deal in the Materials without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Materials, and to permit persons to whom the Materials are furnished to do so, subject to the condition that this copyright notice and permission notice shall be included in all copies or substantial portions of the Materials.