clCreateImage2D

Creates a 2D image object.

Parameters

context

A valid OpenCL context on which the image object is to be created.

flags

A bit-field that is used to specify allocation and usage information about the image memory object being created and is described in the table List of supported *cl_mem_flags* values for clCreateBuffer.

image_format

A pointer to a structure that describes format properties of the image to be allocated. See cl_image_format for a detailed description of the image format descriptor.

image_width , image_height

The width and height of the image in pixels. These must be values greater than or equal to 1.

image_row_pitch

The scan-line pitch in bytes. This must be 0 if <code>host_ptr</code> is NULL and can be either 0 or greater than or equal to <code>image_width</code> * size of element in bytes if <code>host_ptr</code> is not NULL. If <code>host_ptr</code> is not NULL and <code>image_row_pitch</code> is equal to 0, <code>image_row_pitch</code> is calculated as <code>image_width</code> * size of element in bytes. If <code>image_row_pitch</code> is not 0, it must be a multiple of the image element size in bytes.

host_ptr

A pointer to the image data that may already be allocated by the application. The size of the buffer that *host_ptr* points to must be greater than or equal to *image_row_pitch* * *image_height*. The size of each element in bytes must be a power of 2. The image data specified by *host_ptr* is

stored as a linear sequence of adjacent scanlines. Each scanline is stored as a linear sequence of image elements.

errcode_ret

Will return an appropriate error code. If *errcode_ret* is NULL, no error code is returned.

Errors

clCreatel mage2D returns a valid non-zero image object created and the errcode_ret is set to CL_SUCCESS if the image object is created successfully. Otherwise, it returns a NULL value with one of the following error values returned in errcode_ret:

- CL_INVALID_CONTEXT if *context* is not a valid context.
- CL_INVALID_VALUE if values specified in *flags* are not valid.
- CL_INVALID_IMAGE_FORMAT_DESCRIPTOR if values specified in image_format are not valid or if image_format is NULL.
- CL_INVALID_IMAGE_SIZE if *image_width* or *image_height* are 0 or if they exceed values specified in CL_DEVICE_IMAGE2D_MAX_WIDTH or CL_DEVICE_IMAGE2D_MAX_HEIGHT respectively for all devices in context or if values specified by image_row_pitch do not follow rules described in the argument description above.
- CL_INVALID_HOST_PTR if *host_ptr* is NULL and CL_MEM_USE_HOST_PTR or CL_MEM_COPY_HOST_PTR are set in *flags* or if *host_ptr* is not NULL but CL_MEM_COPY_HOST_PTR or CL_MEM_USE_HOST_PTR are not set in *flags*.
- CL_IMAGE_FORMAT_NOT_SUPPORTED if the *image_format* is not supported.
- CL_MEM_OBJECT_ALLOCATION_FAILURE if there is a failure to allocate memory for image object.
- CL_INVALID_OPERATION if there are no devices in *context* that support images (i.e. CL_DEVICE_IMAGE_SUPPORT (specified in the table of OpenCL Device Queries for clGetDeviceInfo) is CL_FALSE).
- CL_OUT_OF_HOST_MEMORY if there is a failure to allocate resources required by the OpenCL implementation on the host.

Specification

DenCL Specification

Also see

3 중 2 2015-02-21 오후 5:15

clCreateImage3D



Copyright © 2007-2009 The Khronos Group Inc. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and/or associated documentation files (the "Materials"), to deal in the Materials without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Materials, and to permit persons to whom the Materials are furnished to do so, subject to the condition that this copyright notice and permission notice shall be included in all copies or substantial portions of the Materials.

3 중 3 2015-02-21 오후 5:15