

Bootstrap: Code

Inline

Wrap inline snippets of code with `<code>`.

For example, `<section>` should be wrapped as inline.

For example, `<code>{"<section>"}` should be wrapped as inline.

User input

Use the `<kbd>` to indicate input that is typically entered via keyboard.

To switch directories, type `cd` followed by the name of the directory.

To edit settings, press `ctrl + ,`

```
<div>To switch directories, type <code>cd</code> followed by the name of the directory.</div>  
<div>To edit settings, press <code>ctrl + ,</code></div>
```

Basic block

Use `<pre>` for multiple lines of code. Be sure to escape any angle brackets in the code for proper rendering.

```
<p>Sample text here...</p>
```

```
<pre>{"<p>Sample text here...</p>"}
```

You may optionally add the `.pre-scrollable` class, which will set a max-height of 350px and provide a y-axis scrollbar.

Variables

For indicating variables use the `<var>` tag.

$y = mx + b$

```
<var>y</var> = <var>m</var><var>x</var> + <var>b</var>
```

Sample output

For indicating blocks sample output from a program use the `<samp>` tag.

```
This text is meant to be treated as sample output from a computer program.
```

```
<samp>This text is meant to be treated as sample output from a computer program.</samp>
```

© 2014 SketchPixy Creative - v3.0.0