

2.3 R Scripts

Put reusable functions in a .R file and `source()` them so you are not copy-pasting.

1. A script is code you keep

A **script** is a file of R code. Comments are fine. There is no YAML header and no formatted prose. The usual extension is `.R`.

Create one with **File** → **New File** → **R Script**. Type:

```
mean(c(2, 3, 4, 5))
```

Ctrl+Enter (Windows) or **Cmd+Enter** (Mac) sends the current line, or the selection, to the console. The **Run** button does the same.

Save project scripts in an `R/` folder, as in note 1.3. If the file holds one function, name the file after the function (`geo_mean.R`). If it holds several helpers, use a short collective name (`my_utils.R`).

A script is the right place for a function you will call from more than one Quarto document. Copy-paste means every fix has to be repeated.

2. Write the function once

Suppose several writeups need a geometric mean. Put the function in `R/geo_mean.R`:

```
#' Geometric mean of a positive numeric vector
#'
#' Uses log(), mean(), and exp().
#'
#' @param x A vector of positive numbers.
#'
#' @return A single numeric value.
#'
#' @examples
#' geo_mean(c(1, 6, 2, 5))
geo_mean <- function(x) {
  stopifnot(is.numeric(x))
  x |>
    log() |>
    mean() |>
    exp()
}
```

If you prefer `%>%`, load `magrittr` or `tidyverse` in the script (or in the file that sources it) before you call `geo_mean()`.

3. `source()` makes the function available

`source()` runs a script in the current session. After that, the functions it defined are objects you can call.

Use a **relative** path from the project, the same rule as note 1.3:

```
source("R/geo_mean.R")

geo_mean(c(1, 6, 2, 5))
```

From a Quarto file in `analysis/`, the relative path might be `../R/geo_mean.R`. `here::here("R", "geo_mean.R")` is another reliable option once you are in an RStudio project.

If the script uses `%>%` or `ggplot()`, those packages must be loaded in the session. Either put `library(...)` at the top of the script, or load the packages in the document before `source()`. Packages are the durable way to manage those dependencies. DATA 413/613 is the course that builds them.

4. Practice

Write a function that takes a numeric vector and returns `TRUE` where the value is between 0.1 and 0.5, inclusive of the endpoints if you like, and `FALSE` otherwise.

1. Save it in `R/` under a name that matches the function.
2. In a Quarto document (or an R script) in another folder, `source()` that file with a relative path.
3. Call it on `c(0, 0.2, 0.4, 0.7)`.