

如果图片不显示，请 [git clone](#)到本地进行查看

git clone [git@github.com:wanghuan2054/geektime.git](https://github.com:wanghuan2054/geektime.git)

Hive作业

目录：

- Hive 建表

- 题目1

- 解法1（不考虑数据倾斜）

- SQL

- 运行结果

- 解法2（考虑数据倾斜）

- SQL

- 题目2

- SQL

- 运行结果

- 题目3(选做)

- 写法1

- SQL

- 运行结果

- 写法2

- SQL

- 运行结果

- GeekFileFormat实现

- POM文件

- GeekTextInputFormat核心代码（解密）

- GeekTextOutputFormat核心代码(加密)

- 上传数据和jar到hdfs

- Hive CLI 操作

- 创建Hive数据库

- add jar

- hive支持本地模式

- 验证解密是否成功

- 创建Hive表

- Load data

- 查看表（验证GeekTextInputFormat解密）

- Insert data

- 验证加密是否成功

- 创建Hive表

- Load data

- 查看表（验证GeekTextInputFormat加密）

- 同时验证加密解密是否成功

- 创建Hive表

- Load data

- 查看表（验证加密解密）

- 表Schema

- geektime_input

- geektime_output

- geektime_inoutput

Hive 建表

```

create table hive_sql_test1.t_user(
userid bigint,
sex String,
age int,
occupation String,
zipcode String
)
row format delimited fields terminated by ':';
load data local inpath '/home/hive/users.dat' overwrite into table
hive_sql_test1.t_user;

create table hive_sql_test1.t_movie
(
movieid bigint,
moviename string,
movietype string
)
row format delimited fields terminated by ':';

load data local inpath '/home/hive/movies.dat' overwrite into table
hive_sql_test1.t_movie;

create table hive_sql_test1.t_rating
(
userid bigint,
movieid bigint,
rate double,
times string
)
row format delimited fields terminated by ':';
load data local inpath '/home/hive/ratings.dat' overwrite into table
hive_sql_test1.t_rating;

```

题目1

简单：展示电影ID为2116这部电影各年龄段的平均影评分

解法1（不考虑数据倾斜）

不考虑数据倾斜问题

SQL

```

SELECT t.age , avg(t1.rate) AS AVGRATE from hive_sql_test1.t_user t
INNER JOIN hive_sql_test1.t_rating t1
ON (T.userid = T1.userid)
WHERE t1.movieid = 2116
GROUP BY T.age
ORDER BY T.age ;

```

运行结果

```
17
18 SELECT t.age , avg(t1.rate) AS AVGRATE from hive_sql_test1.t_user t
19 INNER JOIN hive_sql_test1.t_rating t1
20 ON (T.userid = T1.userid)
21 WHERE t1.movieid = 2116
22 GROUP BY T.age
23 ORDER BY T.age ;
```

```
INNER JOIN hive_sql_test1.t_rating t1
ON (T.userid = T1.userid)
WHERE t1.movieid = 2116
GROUP BY T.age
ORDER BY T.age
WARN :
INFO : Query ID = hive_20210802193400_7a0588fb-e253-4d2b-b889-7d1079bebb42
INFO : Total jobs = 2
INFO : Starting task [Stage-6:MAPREDLOCAL] in serial mode
INFO : Execution completed successfully
```

查询历史记录 保存的查询 结果 (7)

	t.age	avgrate
1	1	3.2941176470588234
2	18	3.3580246913580245
3	25	3.436548223350254
4	35	3.2278481012658227
5	45	2.8275862068965516
6	50	3.32
7	56	3.5

解法2（考虑数据倾斜）

考虑数据倾斜问题，假设2116这部电影评分记录集中在28-30这个年龄段,其它年龄段寥寥无几

解决数据倾斜的方法很多，本文列出我的一条思路

1. 首先按照age和occupation 或者 age 和zipcode 进行分组，对原先按照age分组所有age相同的数据会同时shuffle到一个reduce节点，按照新分组会将之前倾斜值的倾斜程度变为原来的 $1/N$ ， $N = (\text{occupation 或者 zipcode 值}) \% \text{reducer 的值的不同个数}$
2. 将1的子查询结果（GROUP BY T.age ,t.zipcode 预聚合），之后再统一对age进行分组求avg，降低了之前一个节点处理所有数据量。

核心思路，分治思想，对任务进行拆分，先多字段分组求和，后将中间聚合结果统一求avg。

SQL

```
SELECT X.age as age , avg(X.sumrate) as avgrate FROM
(
SELECT t.age , t.zipcode , sum(t1.rate) AS sumrate from hive_sql_test1.t_user t
INNER JOIN hive_sql_test1.t_rating t1
ON (T.userid = T1.userid)
WHERE t1.movieid = 2116
GROUP BY T.age ,t.zipcode
) X
GROUP BY X.age
ORDER BY X.age ;
```

题目2

中等：找出男性评分最高且评分次数超过50次的10部电影，展示电影名，平均影评分和评分次数

SQL

```
SELECT t.sex AS sex,
       t2.moviename AS name,
       avg(t1.rate) AS avgrate,
       count(*) AS total
FROM hive_sql_test1.t_user t
INNER JOIN hive_sql_test1.t_rating t1 ON (T.userid = T1.userid)
INNER JOIN hive_sql_test1.t_movie t2 on(t1.movieid = t2.movieid)
WHERE t.sex = 'M'
GROUP BY T.sex,
         t2.moviename
HAVING count(*) > 50
ORDER BY avgrate DESC
LIMIT 10 ;
```

运行结果

```
16 SELECT t.sex AS sex,
17       t2.moviename AS name,
18       avg(t1.rate) AS avgrate,
19       count(*) AS total
20 FROM hive_sql_test1.t_user t
21 INNER JOIN hive_sql_test1.t_rating t1 ON (T.userid = T1.userid)
22 INNER JOIN hive_sql_test1.t_movie t2 on(t1.movieid = t2.movieid)
23 WHERE t.sex = 'M'
24 GROUP BY T.sex,
25         t2.moviename
26 HAVING count(*) > 50
27 ORDER BY avgrate DESC
28 LIMIT 10 ;
```

INFO : Query ID = hive_20210802210200_6a5ef37f-c199-47eb-b61b-285c323e1fc7
INFO : Total jobs = 2
INFO : Starting task [Stage-9:MAPREDLOCAL] in serial mode

[job_1626505659980_0552](#)

[job_1626505659980_0553](#)

查询历史记录

保存的查询

结果 (10)

	sex	name	avgrate	total
1	M	Sanjuro (1962)	4.639344262295082	61
2	M	Godfather, The (1972)	4.583333333333333	1740
3	M	Seven Samurai (The Magnificent Seven) (Shichinin no samurai) (1954)	4.576628352490421	522
4	M	Shawshank Redemption, The (1994)	4.560625	1600
5	M	Raiders of the Lost Ark (1981)	4.520597322348094	1942
6	M	Usual Suspects, The (1995)	4.518248175182482	1370
7	M	Star Wars: Episode IV - A New Hope (1977)	4.495307167235495	2344
8	M	Schindler's List (1993)	4.49141503848431	1689
9	M	Paths of Glory (1957)	4.485148514851486	202
10	M	When a Woman Loves, She Loves (1992)	4.478260869565218	644

题目3(选做)

困难：找出影评次数最多的女士所给出最高分的10部电影的的平均影评分，展示电影名和平均影评分（可使用多行SQL）

写法1

嵌套子查询

SQL

```
SELECT t3.moviename,
       avg(t2.rate) AS avgrate
FROM (SELECT a.movieid , a.rate
      FROM (SELECT t.userid,
                   count(*) AS total
            FROM hive_sql_test1.t_user t
            INNER JOIN hive_sql_test1.t_rating t1 ON (T.userid = T1.userid)
            WHERE t.sex = 'F'
            GROUP BY T.userid
            ORDER BY total DESC
            LIMIT 1) x
      inner join hive_sql_test1.t_rating a on (x.userid = a.userid)
      ORDER BY a.rate DESC
      LIMIT 10) t1
INNER JOIN hive_sql_test1.t_rating t2 on(t1.movieid = t2.movieid)
INNER JOIN hive_sql_test1.t_movie t3 on(t2.movieid = t3.movieid)
GROUP BY t2.movieid , t3.moviename
ORDER BY avgrate DESC ;
```

运行结果

```
1 SELECT t3.moviename,
2       avg(t2.rate) AS avgrate
3 FROM (SELECT a.movieid , a.rate
4       FROM (SELECT t.userid,
5                count(*) AS total
6             FROM hive_sql_test1.t_user t
7             INNER JOIN hive_sql_test1.t_rating t1 ON (T.userid = T1.userid)
8             WHERE t.sex = 'F'
9             GROUP BY T.userid
10            ORDER BY total DESC
11            LIMIT 1) x
12      inner join hive_sql_test1.t_rating a on (x.userid = a.userid)
13      ORDER BY a.rate DESC
14      LIMIT 10) t1
15 INNER JOIN hive_sql_test1.t_rating t2 on(t1.movieid = t2.movieid)
16 INNER JOIN hive_sql_test1.t_movie t3 on(t2.movieid = t3.movieid)
17 GROUP BY t2.movieid , t3.moviename
18 ORDER BY avgrate DESC ;
```

INFO : Query ID = hive_20210803174349_f3dca635-db83-4a2f-b5b8-94ee55cd035b

INFO : Total jobs = 12

INFO : Starting task [Stage-26:MAPREDLOCAL] in serial mode

查询历史记录

保存的查询

结果 (10)

	t3.moviename	avgrate
1	Rear Window (1954)	4.476190476190476
2	City Lights (1931)	4.387453874538745
3	His Girl Friday (1940)	4.249370277078086
4	Hands on a Hard Body (1996)	4.163043478260869
5	Annie Hall (1977)	4.14167916041979
6	Crumb (1994)	4.063136456211812
7	Blazing Saddles (1974)	4.047363717605005

```

10 ORDER BY total DESC
11 LIMIT 1) x
12 inner join hive_sql_test1.t_rating a on (x.userid = a.userid)
13 ORDER BY a.rate DESC
14 LIMIT 10) t1
15 INNER JOIN hive_sql_test1.t_rating t2 on(t1.movieid = t2.movieid)
16 INNER JOIN hive_sql_test1.t_movie t3 on(t2.movieid = t3.movieid)
17 GROUP BY t2.movieid , t3.moviename
18 ORDER BY avgrate DESC ;

```

```

INFO : Query ID = hive_20210803174349_f3dca635-db83-4a2f-b5b8-94ee55cd035b
INFO : Total jobs = 12
INFO : Starting task [Stage-26:MAPREDLOCAL] in serial mode

```

job_1626505659980_1535

job_1626505659980_1545

查询历史记录

保存的查询

结果 (10)

	t3.moviename	avgrate
1	Rear Window (1954)	4.476190476190476
2	City Lights (1931)	4.387453874538745
3	His Girl Friday (1940)	4.249370277078086
4	Hands on a Hard Body (1996)	4.163043478260869
5	Annie Hall (1977)	4.14167916041979
6	Crumb (1994)	4.063136456211812
7	Blazing Saddles (1974)	4.047363717605005
8	White Christmas (1954)	3.8265682656826567
9	Topsy-Turvy (1999)	3.7039473684210527
10	Metropolitan (1990)	3.6464646464646466

写法2

WITH AS

SQL

```

-- 找出影评次数最多的女士
WITH Rating_CNT AS
(
SELECT t.userid,
       count(*) AS total
FROM   hive_sql_test1.t_user t
INNER JOIN hive_sql_test1.t_rating t1 ON (T.userid = T1.userid)
WHERE  t.sex = 'F'
GROUP BY T.userid
ORDER BY total DESC
LIMIT 1),
-- 找出该女士评分最高的10部电影
TOPMOVIES AS
(
SELECT a.movieid , a.rate
FROM   Rating_CNT x
inner join hive_sql_test1.t_rating a on (x.userid = a.userid)
ORDER BY a.rate DESC
LIMIT 10)

-- select t2.* from TOPMOVIES t2;

-- 求这10部电影的 average 影评评分，展示电影名和 average 影评评分
SELECT t3.moviename,
       avg(t2.rate) AS avgrate
FROM   TOPMOVIES t1

```

```

INNER JOIN hive_sql_test1.t_rating t2 on(t1.movieid = t2.movieid)
INNER JOIN hive_sql_test1.t_movie t3 on(t2.movieid = t3.movieid)
GROUP BY t2.movieid , t3.moviename
ORDER BY avgrate DESC ;

```

运行结果

```

1 -- 找出影评次数最多的女士
2 WITH Rating_CNT AS
3 (SELECT t.userid,
4      | count(*) AS total
5   FROM hive_sql_test1.t_user t
6   INNER JOIN hive_sql_test1.t_rating t1 ON (T.userid = T1.userid)
7   WHERE t.sex = 'F'
8   GROUP BY T.userid
9   ORDER BY total DESC
10  LIMIT 1),
11 -- 找出该女士评分最高的10部电影
12 TOPMOVIES AS
13 (SELECT a.movieid , a.rate
14   FROM Rating_CNT x
15   inner join hive_sql_test1.t_rating a on (x.userid = a.userid)
16   ORDER BY a.rate DESC
17   LIMIT 10)
18 -- 求这10部电影的 average 评分，展示电影名和 average 评分
19 SELECT t3.moviename,
20      | avg(t2.rate) AS avgrate
21 FROM TOPMOVIES t1
22 INNER JOIN hive_sql_test1.t_rating t2 on(t1.movieid = t2.movieid)
23 INNER JOIN hive_sql_test1.t_movie t3 on(t2.movieid = t3.movieid)
24 GROUP BY t2.movieid , t3.moviename
25 ORDER BY avgrate DESC ;

```

```

WARN :
INFO : Query ID = hive_20210803173125_58042bd0-2d80-40f4-942e-a5b47e2856d1
INFO : Total jobs = 12

```

查询历史记录 保存的查询 结果 (10)

	t3.moviename	avgrate
1	Rear Window (1954)	4.476190476190476
2	City Lights (1931)	4.387453874538745
3	His Girl Friday (1940)	4.249370277078086
4	Hands on a Hard Body (1996)	4.163043478260869

```

18 求这10部电影的 average 评分，展示电影名和 average 评分
19 SELECT t3.moviename,
20        avg(t2.rate) AS avgrate
21 FROM TOPMOVIES t1
22 INNER JOIN hive_sql_test1.t_rating t2 on(t1.movieid = t2.movieid)
23 INNER JOIN hive_sql_test1.t_movie t3 on(t2.movieid = t3.movieid)
24 GROUP BY t2.movieid , t3.moviename
25 ORDER BY avgrate DESC ;

```

```

WARN :
INFO : Query ID = hive_20210803173125_58042bd0-2d80-40f4-942e-a5b47e2856d1
INFO : Total jobs = 12

```

job_1626505659980_1498

job_1626505659980_1499

查询历史记录

保存的查询

结果 (10)

	t3.moviename	avgrate
1	Rear Window (1954)	4.476190476190476
2	City Lights (1931)	4.387453874538745
3	His Girl Friday (1940)	4.249370277078086
4	Hands on a Hard Body (1996)	4.163043478260869
5	Annie Hall (1977)	4.14167916041979
6	Crumb (1994)	4.063136456211812
7	Blazing Saddles (1974)	4.047363717605005
8	White Christmas (1954)	3.8265682656826567
9	Topsy-Turvy (1999)	3.7039473684210527
10	Metropolitan (1990)	3.6464646464646466

GeekFileFormat实现

项目源码位置: <https://github.com/wanghuan2054/geektime/tree/master/0801HiveSQL>

POM文件

```

<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <groupId>org.example</groupId>
  <artifactId>HiveCustomFormat</artifactId>
  <version>1.0</version>

  <properties>
    <maven.compiler.source>8</maven.compiler.source>
    <maven.compiler.target>8</maven.compiler.target>
    <java.version>1.8</java.version>
    <hadoop.version>3.1.3</hadoop.version>
    <hive.version>3.1.2</hive.version>
  </properties>
  <dependencies>
  <dependency>
    <groupId>org.apache.hadoop</groupId>
    <artifactId>hadoop-client</artifactId>

```



```

        <version>${hadoop.version}</version>
    </dependency>
    <dependency>
        <groupId>org.apache.hadoop</groupId>
        <artifactId>hadoop-common</artifactId>
        <version>${hadoop.version}</version>
    </dependency>
    <dependency>
        <groupId>org.apache.hive</groupId>
        <artifactId>hive-exec</artifactId>
        <version>${hive.version}</version>
    </dependency>
</dependencies>
</project>

```

GeekTextInputFormat核心代码（解密）

```

@Override
    public boolean next(LongWritable key, Text value) throws IOException {
        while(reader.next(key, text)) {
            String strReplace =
text.toString().toLowerCase().replaceAll("ge{2,256}k", "");
            Text txtReplace = new Text();
            txtReplace.set(strReplace);
            value.set(txtReplace.getBytes(), 0, txtReplace.getLength());
            return true;
        }
        return false;
    }

```

GeekTextOutputFormat核心代码(加密)

```

@Override
    public void write(Writable w) throws IOException {
        // Get input data
        Text tmpText = ((Text) w);
        StringBuilder sb = new StringBuilder();
        String str = tmpText.toString();
        String[] words = str.toString().toLowerCase().split("\\s+");
        // 生成一个 min-max 之间的随机整数
        int min = 2;
        int max = 256;
        int randomNum = getRandomNum(min, max);
        int validWordCnt = 0;
        boolean flag = true;
        for (String word: words) {
            // 如果是有效单词， 统计数+1， 方便后面生成gee...k， 生成中间e的个数使用
            if(checkValidWord(word)){
                validWordCnt++;
            }
            // 随机数个单词标记
            randomNum--;
            // 行首单词不加空格
            if (flag){

```

```

        flag = false ;
        sb.append(word) ;
    }
    else {
        // 非行首单词输出空格+单词
        sb.append(" " + word) ;
    }
    // 输出指定生成随机数个单词后，进行插入操作
    if (0 == randomNum){
        // 生成指定min-max区间的随机整数
        randomNum = getRandomNum(min,max) ;
        // 利用之前产生的有效单词数，生成gee...K
        String insertword = generateGeek(validwordCnt);
        sb.append(" " + insertword);
        // 插入单词之后，有效单词总数从新开始计数
        validwordCnt = 0 ;
    }
}
String strReplace = sb.toString();
Text output = new Text();
output.set(strReplace);
text.set(output.getBytes(), 0, output.getLength());
writer.write(text);
}
public static int getRandomNum(int min , int max){
    return (int) (Math.random()*(max-min)+min) ;
}
// 产生中间连续N个e
public static String generateGeek(int eCnt){
    String prefix = "g" ;
    String loopStr = "e" ;
    String suffix = "k" ;
    StringBuilder sb = new StringBuilder(prefix) ;
    for (int i = 0; i < eCnt; i++) {
        sb.append(loopStr) ;
    }
    return sb.append(suffix).toString();
}

// 检测是否为有效字符，非gee...k单词
public static boolean checkValidWord(String word){
    boolean res = true;

    String tmp = word;
    tmp = tmp.replaceAll("\\p{P}", "");
    if (word.length() != tmp.length()) {
        res = false;
    }
    // 定义模式匹配
    Pattern pattern = Pattern.compile("ge{2,256}k");
    Matcher matcher = pattern.matcher(word) ;
    // matches 进行全局匹配 与给定的字符串进行全匹配
    // 测试word 中包含geek，返回false
    res = !matcher.matches();
    return res;
}

```

上传数据和jar到hdfs

登录到jikehadoop01节点

#上传jar

```
[student@jikehadoop01 ~]$ hadoop fs -put  
/home/student/wanghuan/HiveCustomFormat-1.0.jar /user/student/wanghuan/
```

```
[student@jikehadoop01 ~]$ hadoop fs -ls /user/student/wanghuan
```

Found 3 items

```
-rw-r--r--  3 student student      18479 2021-08-05 00:36  
/user/student/wanghuan/HiveCustomFormat-1.0.jar  
-rw-r--r--  3 student student       2110 2021-07-11 22:54  
/user/student/wanghuan/phone_data.txt  
-rw-r--r--  3 student student       8870 2021-07-11 22:58  
/user/student/wanghuan/wanghuanmr-1.0-SNAPSHOT.jar
```

#上传数据文件

```
[student@jikehadoop01 ~]$ hadoop fs -put /home/student/wanghuan/geek.txt  
/user/student/wanghuan/
```

```
[student@jikehadoop01 ~]$ hadoop fs -ls /user/student/wanghuan/
```

Found 4 items

```
-rw-r--r--  3 student student      18479 2021-08-05 00:36  
/user/student/wanghuan/HiveCustomFormat-1.0.jar  
-rw-r--r--  3 student student       730 2021-08-05 00:41  
/user/student/wanghuan/geek.txt  
-rw-r--r--  3 student student       2110 2021-07-11 22:54  
/user/student/wanghuan/phone_data.txt  
-rw-r--r--  3 student student       8870 2021-07-11 22:58  
/user/student/wanghuan/wanghuanmr-1.0-SNAPSHOT.jar
```

Hive CLI 操作

登录到 Alibaba Cloud Elastic Compute Service

创建Hive数据库

```
hive> create database wanghuan ;  
OK  
Time taken: 0.077 seconds
```

add jar

```
hive>add jar hdfs:///user/student/wanghuan/HiveCustomFormat-1.0.jar;  
Added [/tmp/e80feb11-9d66-4d37-a662-2c90e106a810_resources/HiveCustomFormat-  
1.0.jar] to class path  
Added resources: [hdfs:///user/student/wanghuan/HiveCustomFormat-1.0.jar]
```

hive支持本地模式

```
# hive的Job交给yarn执行太慢，hive支持本地模式  
set hive.exec.mode.local.auto=true;
```

验证解密是否成功

创建Hive表

```
# 切换数据库
hive> use wanghuan ;
OK
Time taken: 0.029 seconds
# 创建表
create table IF NOT EXISTS geektime_input (
    content string
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY '\n' LINES TERMINATED BY '\n'
stored as
INPUTFORMAT 'hive.inoutformat.GeekTextInputFormat'
OUTPUTFORMAT 'org.apache.hadoop.hive.q1.io.HiveIgnoreKeyTextOutputFormat' ;

hive> create table IF NOT EXISTS geektime_input (
    > content string
    > )
    > ROW FORMAT DELIMITED FIELDS TERMINATED BY '\n' LINES TERMINATED BY '\n'
    > stored as
    > INPUTFORMAT 'hive.inoutformat.GeekTextInputFormat'
    > OUTPUTFORMAT 'org.apache.hadoop.hive.q1.io.HiveIgnoreKeyTextOutputFormat'
;
OK
Time taken: 0.24 seconds
```

Load data

```
# 本地加载
load data local inpath '/home/student/wanghuan/geek.txt' overwrite into table
geektime_input;
# hdfs 加载
load data inpath '/user/student/wanghuan/geek.txt' overwrite into table
geektime_input;
```

查看表 (验证GeekTextInputFormat解密)

例如: This notebook can be geeeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeek database.
解密为: This notebook can be used to install gek on all worker nodes, run data generation, and create the TPCDS database.

```
hive> show tables ;
OK
geektime_input
Time taken: 0.084 seconds, Fetched: 1 row(s)
hive> select * from geektime_input ;
OK
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
```

```
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
Time taken: 0.233 seconds, Fetched: 5 row(s)
```

Insert data

```
hive> insert into geektime_input (content) values("This notebook can be geeek
used to geek install gek on all geeek worker nodes, run data generation, and
create the TPCDS geeeeeeeek database.");
Query ID = student_20210805004916_1da574e6-8bd7-4652-ad9f-b10f6b9e6307

# 查看刚才插入的数据，被成功解密显示
hive> select * from geektime_input ;
OK
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
wang huan can be kafka to flink gek on all hudi nodes, spark data generation,
and hadoop the nihao database.
wang huan can be kafka to flink gek on all hudi nodes, spark data generation,
and hadoop the nihao database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
this notebook can be used to install gek on all worker nodes, run data
generation, and create the tpcds database.
Time taken: 0.042 seconds, Fetched: 9 row(s)
```

验证加密是否成功

创建Hive表

```
# 切换数据库
hive> use wanghuan ;
OK
Time taken: 0.029 seconds
# 创建表
create table IF NOT EXISTS geektime_output (
    content string
)
ROW FORMAT DELIMITED
    FIELDS TERMINATED BY '\n'
    LINES TERMINATED BY '\n'
stored as
INPUTFORMAT 'org.apache.hadoop.mapred.TextInputFormat'
```

```

OUTPUTFORMAT 'hive.inoutformat.GeekTextOutputFormat' ;

hive> create table IF NOT EXISTS geektime_output (
  >   content string
  > )
  > ROW FORMAT DELIMITED
  >   FIELDS TERMINATED BY '\n'
  >   LINES TERMINATED BY '\n'
  > stored as
  > INPUTFORMAT 'org.apache.hadoop.mapred.TextInputFormat'
  > OUTPUTFORMAT 'hive.inoutformat.GeekTextOutputFormat' ;

OK
Time taken: 0.104 seconds

```

Load data

```

# 本地加载
load data local inpath '/home/student/wanghuan/geek.txt' overwrite into table
geektime_output;
# hdfs 加载
load data inpath '/user/student/wanghuan/geek.txt' overwrite into table
geektime_output;

```

查看表 (验证GeekTextInputFormat加密)

例如: This notebook can be used to install gek on all worker nodes, run data generation, and create the TPCDS database.

加密为: This notebook can be geeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeeek database.

```

hive> show tables;
OK
geektime_input
geektime_output
Time taken: 0.037 seconds, Fetched: 2 row(s)

```

旧数据没有加密

```

hive> select * from geektime_output ;
OK

```

This notebook can be geeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeeek database.

This notebook can be geeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeeek database.

This notebook can be geeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeeek database.

This notebook can be geeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeeek database.

This notebook can be geeek used to geek install gek on all geeek worker nodes, run data generation, and create the TPCDS geeeeeeeeek database.

```

Time taken: 0.046 seconds, Fetched: 5 row(s)

```

插入新数据

```

hive> insert into geektime_output (content) values("This notebook can be used to
install gek on all worker nodes, run data generation, and create the TPCDS
database.");

```

```
# 查看新数据是否加密
hive> select * from geektime_output ;
OK
this notebook geek can be geek used to install gek geeek on all geek worker
nodes, run geek data generation, and create the geeeeeek tpcds database.
This notebook can be geeek used to geek install gek on all geeek worker nodes,
run data generation, and create the TPCDS geeeeeeeeek database.
This notebook can be geeek used to geek install gek on all geeek worker nodes,
run data generation, and create the TPCDS geeeeeeeeek database.
This notebook can be geeek used to geek install gek on all geeek worker nodes,
run data generation, and create the TPCDS geeeeeeeeek database.
This notebook can be geeek used to geek install gek on all geeek worker nodes,
run data generation, and create the TPCDS geeeeeeeeek database.
This notebook can be geeek used to geek install gek on all geeek worker nodes,
run data generation, and create the TPCDS geeeeeeeeek database.
```

同时验证加密解密是否成功

创建Hive表

```
# 切换数据库
hive> use wanghuan ;
OK
Time taken: 0.029 seconds
# 创建表
create table IF NOT EXISTS geektime_inoutput (
    content string
)
ROW FORMAT DELIMITED
    FIELDS TERMINATED BY '\n'
    LINES TERMINATED BY '\n'
stored as
INPUTFORMAT 'hive.inoutformat.GeekTextInputFormat'
OUTPUTFORMAT 'hive.inoutformat.GeekTextOutputFormat' ;

hive> create table IF NOT EXISTS geektime_inoutput (
    > content string
    > )
    > ROW FORMAT DELIMITED
    > FIELDS TERMINATED BY '\n'
    > LINES TERMINATED BY '\n'
    > stored as
    > INPUTFORMAT 'hive.inoutformat.GeekTextInputFormat'
    > OUTPUTFORMAT 'hive.inoutformat.GeekTextOutputFormat' ;
OK
Time taken: 0.094 seconds
```

Load data

表Schema

geektime_input

InputFormat: hive.inoutformat.GeekTextInputFormat
OutputFormat: org.apache.hadoop.hive.ql.io.HiveIgnoreKeyTextOutputFormat

```
hive> desc formatted geektime_input ;
OK
# col_name          data_type          comment

content            string

# Detailed Table Information
Database:           wanghuan
OwnerType:          USER
Owner:              student
CreateTime:         Thu Aug 05 00:39:46 CST 2021
LastAccessTime:     UNKNOWN
Retention:          0
Location:
hdfs://jikehadoop01:8020/user/hive/warehouse/wanghuan.db/geektime_input
Table Type:         MANAGED_TABLE
Table Parameters:
    numFiles         6
    numRows          0
    rawDataSize      0
    totalSize        1445
    transient_lastDdlTime 1628096654

# Storage Information
SerDe Library:      org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe
InputFormat:        hive.inoutformat.GeekTextInputFormat
OutputFormat:
org.apache.hadoop.hive.ql.io.HiveIgnoreKeyTextOutputFormat
Compressed:         No
Num Buckets:        -1
Bucket Columns:     []
Sort Columns:       []
Storage Desc Params:
    field.delim      \n
    line.delim       \n
    serialization.format \n
Time taken: 0.064 seconds, Fetched: 32 row(s)
```

geektime_output

InputFormat: org.apache.hadoop.mapred.TextInputFormat
OutputFormat: hive.inoutformat.GeekTextOutputFormat

```
hive> desc formatted geektime_output ;
OK
# col_name          data_type          comment

content            string
```

```

# Detailed Table Information
Database:                wanghuan
OwnerType:               USER
Owner:                   student
CreateTime:              Thu Aug 05 00:53:27 CST 2021
LastAccessTime:         UNKNOWN
Retention:               0
Location:
hdfs://jikehadoop01:8020/user/hive/warehouse/wanghuan.db/geektime_output
Table Type:              MANAGED_TABLE
Table Parameters:
    numFiles              4
    numRows               0
    rawDataSize           0
    totalSize             1200
    transient_lastDdlTime 1628097015

# Storage Information
SerDe Library:           org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe
InputFormat:             org.apache.hadoop.mapred.TextInputFormat
OutputFormat:            hive.inoutformat.GeekTextOutputFormat
Compressed:              No
Num Buckets:             -1
Bucket Columns:          []
Sort Columns:            []
Storage Desc Params:
    field.delim           \n
    line.delim            \n
    serialization.format  \n
Time taken: 0.047 seconds, Fetched: 32 row(s)

```

geektime_inoutput

```

InputFormat:    hive.inoutformat.GeekTextInputFormat
OutputFormat:   hive.inoutformat.GeekTextOutputFormat

```

```

hive> desc formatted geektime_inoutput ;
OK
# col_name          data_type          comment

content            string

# Detailed Table Information
Database:                wanghuan
OwnerType:               USER
Owner:                   student
CreateTime:              Thu Aug 05 01:06:45 CST 2021
LastAccessTime:         UNKNOWN
Retention:               0
Location:
hdfs://jikehadoop01:8020/user/hive/warehouse/wanghuan.db/geektime_inoutput
Table Type:              MANAGED_TABLE
Table Parameters:
    numFiles              3
    numRows               0
    rawDataSize           0
    totalSize             1029

```

transient_lastDdlTime 1628097087

Storage Information

SerDe Library: org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe
InputFormat: hive.inoutformat.GeekTextInputFormat
OutputFormat: hive.inoutformat.GeekTextOutputFormat
Compressed: No
Num Buckets: -1
Bucket Columns: []
Sort Columns: []

Storage Desc Params:

field.delim \n
line.delim \n
serialization.format \n

Time taken: 0.049 seconds, Fetched: 32 row(s)