

Precision Portable DC Load Testing — Engineered for the Field

L-10T Portable Load Bank

WHY THE L-10T?

Field service and battery testing made simple. This compact unit delivers precise resistive load for 12V, 24V, 36V, and 48V DC motive batteries and power supplies in a lightweight portable package. Perfect for commissioning, maintenance, and troubleshooting DC systems.

KEY BENEFITS

- Four load steps at 12/24V (combinable to 15 loads)
- Three load steps at 36/48V (combinable to 7 loads)
- Total capacity: 190A @12V · 380A @24V · 270A @36V · 360A @48V
- Integrated metering: 0–50V voltmeter, 0–400A ammeter
- Air-cooled and completely self-contained
- Compact & lightweight: 22" × 8" × 11", 40 lbs
- Carrying case included for easy transport
- Thermal protection for safety · Plug test pins for test leads
- Power indicator light

SPECIFICATIONS

- Continuous Duty Rated – Designed for field servicing and extended testing of DC batteries and power supplies
- Dimensions: 22" L × 8" W × 11" H
- Weight: 40 lbs
- Meters: 0–50V voltmeter, 0–400A ammeter
- Air-cooled, self-contained design



L-10T Portable Load Bank

IDEAL FOR

- Field servicing of motive batteries
- Testing DC power supplies (12–48V)
- Battery capacity & performance validation
- Forklift and industrial battery testing
- Material handling maintenance
- Troubleshooting & commissioning

FEATURES

- Plug test pins for connecting test leads
- Power indicator light
- Thermal protection with safety interlocks
- Rugged carrying case included

Load Step	12VDC	24VDC	36VDC	48VDC
1	15A	30A	45A	60A
2	25A	50A	75A	100A
3	50A	100A	150A	200A
4	100A	200A	—	—
TOTAL AMPS	190A	380A	270A	360A

Table 1: L-10T Portable Load Bank - Technical Values