

Precision Portable AC Load Testing — Engineered for the Field

A69-80 Portable Load Bank

WHY THE A69-80?

Field service and generator testing made simple. This compact unit delivers 100 kW at 480VAC (80 kW at 208VAC) in a lightweight portable package. Perfect for commissioning, maintenance, and troubleshooting 3-phase and single-phase systems.

KEY BENEFITS

- 100 kW @ 480VAC / 80 kW @ 208VAC 3-Phase
- Also tests 240VAC 3-phase, 240VAC single-phase, and 120VAC single-phase
- Multiple load steps for precise testing
- Integrated metering: Voltmeter, Ammeter, Frequency
- Air-cooled with 120VAC control power
- Compact & lightweight: 22" × 8" × 21", 60 lbs
- Carrying case included for easy transport
- Thermal protection for safety
- Plug-and-play setup with included 10 ft cable
- Power indicator lights

SPECIFICATIONS

- Continuous Duty Rated – Designed for field servicing and extended testing of generators and inverters
- Dimensions: 22" L × 8" W × 21" H
- Weight: 60 lbs
- Meters: 0–150V voltmeter, 0–250A ammeter, 55–65 Hz frequency
- Air-cooled; 120VAC outlet required for fans and relays



A69-80 Portable Load Bank

IDEAL FOR

- Generator commissioning
- UPS and inverter testing
- Field service of 480V/208V systems
- Single-phase 120/240V verification
- Backup power validation
- 3-phase portable load testing

FEATURES

- Plug test pins for connecting test leads
- Receptacle for included 10 ft cable
- Power indicator lights
- Thermal protection
- Rugged carrying case included
- Completely self-contained — air-cooled

Voltage / Phase	NET kW	Load Steps
480VAC 3-Phase	100 kW	12.5, 12.5, 25, 25, 25 kW
208VAC 3-Phase	80 kW	10, 10, 20, 20, 20 kW
240VAC 3-Phase	—	Supported
240VAC Single Phase	—	Supported
120VAC Single Phase	—	Supported

Table 1: A69-80 Portable Load Bank - Technical Values