

Precision Portable DC Load Testing — Engineered for the Field

A42-500 Portable Load Bank

WHY THE A42-500?

Field service and battery testing made simple. This compact unit delivers a temporary resistive load for 24V, 36V, and 48V DC batteries and power supplies in a lightweight portable package. Load adjustable from 0–500A at 24VDC and 48VDC (0–375A at 36VDC).

KEY BENEFITS

- 24V / 36V / 48V DC support
- 0–500A at 24VDC and 48VDC
- 0–375A at 36VDC
- 100A, 100A, 200A fixed steps plus 0–100A adjustable step
- Integrated metering: 0–75V voltmeter, 0–500A ammeter
- Air-cooled and completely self-contained
- Compact & lightweight: 22" × 8" × 11", 49 lbs
- Carrying case included for easy transport
- Thermal protection for safety
- Plug test pins for test leads
- Power indicator light

SPECIFICATIONS

- Continuous Duty Rated – Designed for field servicing and extended testing of 24/36/48V DC batteries and power supplies
- Dimensions: 22" L × 8" W × 11" H
- Weight: 49 lbs
- Meters: 0–75V voltmeter, 0–500A ammeter
- Air-cooled, self-contained design



A42-500 Portable Load Bank

IDEAL FOR

- Field servicing of 24/36/48V motive batteries
- Testing DC power supplies (24–48V)
- Battery capacity & performance validation
- Forklift and industrial battery testing
- Material handling equipment maintenance
- DC system troubleshooting & commissioning

FEATURES

- 100A, 100A, and 200A fixed steps plus 0–100A adjustable
- Plug test pins for connecting test leads
- Power indicator light
- Thermal protection
- Rugged carrying case included
- Completely self-contained — no external cooling required

Load Step	24VDC	36VDC	48VDC
Adjustable	0–100A	—	0–100A
Fixed	100A	—	100A
Fixed	100A	—	100A
Fixed	200A	—	200A
TOTAL AMPS	500A	375A	500A

Table 1: A42-500 Portable Load Bank - Technical Values