

Precision Portable AC Load Testing — Engineered for the Field

57 kW Portable Load Bank

WHY THE A57?

Field service and generator testing made simple. This compact unit delivers 57 kW at 480V (45 kW at 208V) in a lightweight portable package. Perfect for commissioning, maintenance, and troubleshooting 3-phase and single-phase systems.

KEY BENEFITS

- 57 kW @ 480VAC / 45 kW @ 208VAC 3-Phase
- 25kW 240VAC / 6 kW @ 120Vac 1-Phase
- Multiple load steps for precise testing
- Integrated metering: Voltmeter, Ammeter, Frequency
- Air-cooled with 120VAC control power
- Compact & lightweight: 22" x 8" x 21", 60 lbs
- Carrying case with integrated casters for easy transport
- Thermal protection for safety
- Plug-and-play setup with included 10 ft cable

SPECIFICATIONS

- Continuous Duty Rated – Designed for extended operation with standard air temperature and pressure, at nominal sea level
- Total airflow 1680 CFM (derate 3.5% per 1,000 ft above sea level)
- Meters: 0-600V, 0-150A, 55-65 Hz
- Accuracy: Voltmeter & Ammeter $\pm 1\%$, Frequency ± 0.1 Hz



A57 Portable Load Bank

IDEAL FOR

- Generator commissioning
- UPS and inverter testing
- Field service of 480V/208V systems
- Single-phase 120/240V verification
- Backup power validation
- Revenue meter qualification

FEATURES

- Power indicator lights
- Quick-connect test leads
- Thermal overload protection with auto-shutdown

Voltage / Phase	NET kW	Load Steps	ΔT @ 1680 CFM
480VAC / 240VAC 3-Phase	57 kW	1, 2, 2.5, 10, 12.5, 25 kW	107.2°F (59.6°C)
208VAC 3-Phase	45 kW	0.8, 1.6, 1.6, 4, 8, 9.7, 19.3 kW	84.6°F (47.0°C)
240VAC Single Phase	25 kW	0.5, 1, 1, 2.5, 5, 6.25, 12.5 kW	47.0°F (26.1°C)
120VAC Single Phase	6 kW	0.13, 0.25, 0.25, 0.63, 1.25, 1.5, 3 kW	11.3°F (6.3°C)

Table 1: A57 Portable Load Bank - Technical Values