Value Transformation

David Mann

@MannD | Labs.HeirloomSoftware.com

Operators

- concatMap
- concatMapTo
- defaultIfEmpty
- endWith
- startWith
- exhaustMap

- expand
- map
- mapTo
- scan
- mergeScan
- pluck

- reduce
- switchMap/flatMap
- mergeMapTo
- switchMapTo
- materialize
- dematerialize

concatMap

Map values to provided function/Observable

Emits all values

Sequential



concatMapTo

Source as signal

Subscribe when notified

Emit combined results



defaultIfEmpty

Default Value



endWith

Append values



startWith

Prepend values



exhaustMap

Map values to generated Observables

Emit results



expand

Apply function source values

recursive



```
expand(x => {return x < 5 ? of(x + 1) : empty() ;})
```



map

Pass all values through a function



mapTo

Convert every value to same constant



scan

Emit cumulative results



mergeScan

Emit cumulative results

Plus other values



mergeScan((acc, val) => of('a', 'b', acc + val), 0)

pluck

Pull values from objects



reduce

Emit final cumulative result



switchMap/flatMap

Subscribe to internal Observable when source emits

Cancel previous subscription



mergeMapTo

Emit inner Observable for each source value



switchMapTo

Emit inner Observable for each source value

Cancel previous subscription



materialize

Replace emissions with Notifications



{ kind: 'N', value: *<value>*, error: undefined, hasValue: true }
{ kind: 'C', value: undefined, error: undefined, hasValue:false}
{ kind: ‘E', value: undefined, error: *<error contents>*, hasValue:false}

dematerialize

Replace Notifications with standard emissions



{ kind: 'N', value: *<value>*, error: undefined, hasValue: true }
{ kind: 'C', value: undefined, error: undefined, hasValue:false}
{ kind: ‘E', value: undefined, error: *<error contents>*, hasValue:false}