Assignment for ACL

Create a directory /tmp/canteen
create a users sample in the system
provide ACL access to this user with rwx permission
provide ACL access to the group "sysadmin" with rwx permissions
Change the permssios for user from rwx to r-x only
Delete all the ACL permissions from the directory

Answer:

```
[root@localhost ~]# mkdir /tmp/canteen
[root@localhost ~]# useradd sample
[root@localhost ~]# setfacl -m u:sample:rwx /tmp/canteen
[root@localhost ~]# setfacl -m g:sysadmin:rwx /tmp/canteen
[root@localhost ~]# getfacl /tmp/canteen
getfacl: Removing leading '/' from absolute path names
# file: tmp/canteen
# owner: root
# group: root
user::rwx
user:sample:rwx
group::r-x
group:sysadmin:rwx
mask::rwx
other::r-x

[root@localhost ~]# setfacl -m u:sample:r-x /tmp/canteen
[root@localhost ~]# getfacl /tmp/canteen
getfacl: Removing leading '/' from absolute path names
# file: tmp/canteen
# owner: root
# group: root
user::rwx
user:sample:r-x
group::r-x
group:sysadmin:rwx
mask::rwx
other::r-x

[root@localhost ~]# setfacl -b /tmp/canteen
[root@localhost ~]# getfacl /tmp/canteen
getfacl: Removing leading '/' from absolute path names
# file: tmp/canteen
# owner: root
# group: root
user::rwx
group::r-x
other::r-x

[root@localhost ~]#
```