NovaTech Systems — NovaFlow Product Documentation

NovaTech Systems • Internal Knowledge Base Document

Field	Value
Document ID	NT-PROD-001
Version	2.2
Effective date	2026-08-15
Owner department	Product — NovaFlow
Last updated	2026-08-15
Status	Active

Purpose and scope

Product and operational reference for NovaFlow workflows, roles, APIs, common failures, and troubleshooting.

All names, systems, processes, dates, limits, and examples in this document are fictional and exist only for the NovaTech Systems RAG knowledge-base exercise.

1. Product Overview

NovaFlow is NovaTech's workflow automation platform for enterprise business processes. It allows authorized users to model workflows, define conditions, invoke actions, connect approved integrations, and observe execution results.

2. Workflow Model

A NovaFlow workflow follows the conceptual sequence: Trigger → Conditions → Actions → Completion.

Element	Description	Example
Trigger	Starts a workflow	New ticket created; scheduled event; approved API event
Conditions	Determines whether and how the workflow proceeds	Priority is P1; amount exceeds configured threshold
Actions	Performs one or more operations	Send notification; update record; call approved integration
Completion	Records successful completion or terminal failure	Workflow completed; action failed and execution marked failed

3. Main Features

- Visual workflow creation and editing.
- Conditional routing and branching.
- Reusable actions and approved integrations.
- Execution history and operational visibility.
- Role-based access to workflow configuration.

- API access for approved automation scenarios.

4. User Roles

Role	Typical capability
Workflow Administrator	Manage workspace-level configuration and access.
Workflow Builder	Create and modify workflows within assigned scope.
Workflow Operator	Run, inspect, or manage executions where authorized.
Viewer	View workflows and execution information without changing configuration.

5. API Overview

NovaFlow APIs use authenticated requests and authorization controls. API consumers should treat tokens and integration credentials as secrets and follow NT-SEC-001. Exact endpoint details, rate limits, and unreleased capabilities are intentionally not specified in this knowledge base.

6. Common Errors

Error category	Meaning	Recommended action
Invalid trigger configuration	Trigger cannot be activated as configured	Validate required fields and event source permissions.
Condition evaluation failure	A workflow condition could not be evaluated	Inspect input schema and execution logs.
Action timeout	An action did not complete within its allowed time	Check downstream dependency health and retry policy.
Integration authorization failure	Connected service rejected the request	Verify authorization state and required permissions.

7. Troubleshooting

1. Open the affected workflow and identify the failed execution.
2. Check the trigger payload and condition evaluation result.
3. Identify the first failed action rather than only the final error.
4. Inspect integration or downstream service status where authorized.
5. Retry only when the action is safe to repeat and the workflow’s idempotency behavior is understood.
6. Escalate recurring platform failures to the NovaFlow team or SRE.

8. FAQ

Question	Answer
What is a workflow?	A configured sequence of trigger, conditions, actions, and completion behavior.
Can every user edit workflows?	No. Editing depends on the user’s assigned NovaFlow role and workspace permissions.
Where should secrets be stored?	In approved secrets-management controls; never in source code or workflow descriptions.
What if an integration authorization expires?	Reauthorize through the approved integration flow and verify the required permissions.

9. Related Documents

- NT-SEC-001 — Security Policy
- NT-TECH-001 — NovaID Documentation
- NT-SRE-001 — Incident Management Runbook
- NT-ENG-001 — Engineering Handbook