

STM32CubeMX Assignment2.ioc*: STM32F103C8Tx

File Window Help

Home > STM32F103C8Tx > Assignment2.ioc - Pinout & Configuration > GENERATE CODE

Pinout & Configuration | Clock Configuration | Project Manager | Tools

Software Packs | Pinout

Categories: A-Z

- System Core >
- Analog >
- Timers >
- Connectivity >
- Computing >
- Middleware and Software Packs >

TIM3 Mode and Configuration

Mode

Slave Mode: Disable

Trigger Source: Disable

☒ Internal Clock

Channel1: Disable

Channel2: Disable

Configuration

Reset Configuration

NVIC Settings | DMA Settings

Parameter Settings | User Constants

Configure the below parameters:

Search (Ctrl+F)

Counter Settings

Prescaler (PSC - 16 bit... 7199

Counter Mode: Up

Counter Period (AutoR... 4999

Internal Clock Division ... No Division

auto-reload preload: Disable

Trigger Output (TRGO) Param...

Pinout view | System view

Pinout view

System view

STM32F103C8Tx LQFP48

Pinout diagram showing the chip and its connections.

Windows taskbar: 24°C صافى غالىتا

STM32CubeMX Assignment2.ioc*: STM32F103C8Tx

File Window Help

Home > STM32F103C8Tx > Assignment2.ioc - Pinout & Configuration > GENERATE CODE

Pinout & Configuration | Clock Configuration | Project Manager | Tools

Software Packs | Pinout

Categories: A-Z

- System Core >
- Analog >
- Timers >
- Connectivity >
- Computing >
- Middleware and Software Packs >

TIM3 Mode and Configuration

Mode

Slave Mode: Disable

Trigger Source: Disable

☒ Internal Clock

Channel1: Disable

Channel2: Disable

Channel3: Disable

Channel4: Disable

Combined Channels: Disable

Configuration

Reset Configuration

NVIC Settings | DMA Settings

Parameter Settings | User Constants

NVIC Interrupt Table: Enabled | Preemption Priority: 0 | Sub Priority: 0

TIM3 global interrupt: ☒ 0 0

Pinout view | System view

Pinout view

System view

STM32F103C8Tx LQFP48

Pinout diagram showing the chip and its connections.

Windows taskbar: 24°C صافى غالىتا

