

WEEK 8 Skill OSSP

1. Create Week 8 workspace

```
ashborn@DESKTOP-I4G5Q4N:~$ mkdir week8_s
ashborn@DESKTOP-I4G5Q4N:~$ cd ~/week8_s
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ pwd
/home/ashborn/week8_s
```

2. Environment Variable Expansion

```
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ nano env_expand.c
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ gcc env_expand.c -o env_expand
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./env_expand
Enter variable reference: $USER
USER = ashborn
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./env_expand
Enter variable reference: $HOME
HOME = /home/ashborn
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./env_expand
Enter variable reference: $ABCXYZ
ABCXYZ = <undefined>
```

3. Replace the previous program and Compile

```
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ nano env_expand.c
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ gcc env_expand.c -o env_expand
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./env_expand
Enter variable reference: $USER
Original token : $USER
Expanded token : ashborn
```

4. Test Nested Variable Expansion

```

ashborn@DESKTOP-I4G5Q4N:~/week8_s$ export NAME="OSSP"
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ export GREETING='$NAME'
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ echo $GREETING
$NAME
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./env_expand
Enter variable reference: $GREETING
Original token : $GREETING
Expanded token : $NAME
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./env_expand
Enter variable reference: $NAME
Original token : $NAME
Expanded token : OSSP

```

5. Built-in Command Dispatch

```

ashborn@DESKTOP-I4G5Q4N:~/week8_s$ nano builtin.c
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ gcc builtin.c -o builtin
ashborn@DESKTOP-I4G5Q4N:~/week8_s$ ./builtin
mini-shell> pwd
/home/ashborn/week8_s
mini-shell> hello
Invalid command: hello
mini-shell> pwd
/home/ashborn/week8_s
mini-shell> _

```

6. Test Exit Built-in

```

mini-shell> exit
Exiting shell...
ashborn@DESKTOP-I4G5Q4N:~/week8_s$

```

Summary:

Implemented environment variable expansion during command parsing in Ubuntu. The program detected \$VAR references, expanded their values using environment variables, handled undefined variables, updated tokens, and demonstrated nested variable expansion.

Implemented built-in command dispatch using a dispatch table. Built-in commands such as `pwd` and `exit` were executed within the shell, invalid commands were detected, and shell state was maintained and tested successfully.