

Oracle 11g - SQL

Other Schema Objects – Views

Objectives

After completing this lesson, you should be able to do the following:

- Create simple and complex views
- Retrieve data from views
- Create, maintain, and use sequences
- Create and maintain indexes
- Types of Indexes: Normal (B-Tree), BITMAP, Partitioned & Function-based Index
- Impact on Dropping of Index
- When to Drop of Index, If necessary
- Create private and public synonyms

Database Objects

Object	Description
View	Logically represents subsets of data from one or more tables
Sequence	Generates numeric values
Index	Improves the performance of some queries
Synonym	Gives alternative names to objects

What Is a View?


EMPLOYEES table

	EMPLOYEE_ID	FIRST_NAME	LAST_NAME	EMAIL	PHONE_NUMBER	HIRE_DATE	JOB_ID	SALARY
1	100	Steven	King	SKING	515.123.4567	17-JUN-87	AD_PRES	24000
2	101	Neena	Kochhar	NKOCHHAR	515.123.4568	21-SEP-89	AD_VP	17000
3	102	Lex	De Haan	LDEHAAN	515.123.4569	13-JAN-93	AD_VP	17000
4	103	Alexander	Hunold	AHUNOLD	590.423.4567	03-JAN-90	IT_PROG	9000
5	104	Bruce	Ernst	BERNST	590.423.4568	21-MAY-91	IT_PROG	6000
6	107	Diana	Lorentz	DLORENTZ	590.423.5567	07-FEB-99	IT_PROG	4200
7	124	Kevin	Mourgos	KMOURGOS	650.121.2004	16-NOV-99	ST_MAN	5800
8	141	Trenna				17-OCT-95	ST_CLERK	3500
9	142	Curtis				29-JAN-97	ST_CLERK	3100
10	143	Randall				15-MAR-98	ST_CLERK	2600
11	144	Peter	Vargas	PVARGAS	650.121.2004	09-JUL-98	ST_CLERK	2500
12	149	Eleni	Zlotkey	EZLOTKEY	011.44.1344.429018	29-JAN-00	SA_MAN	10500
13	174	Ellen	Abel	EABEL	011.44.1644.429267	11-MAY-96	SA_REP	11000
14	176	Jonathon	Taylor	JTAYLOR	011.44.1644.429265	24-MAR-98	SA_REP	8600
15	178	Kimberely	Grant	KGRANT	011.44.1644.429263	24-MAY-99	SA_REP	7000
16	200	Jennifer	Whalen	JWHALEN	515.123.4444	17-SEP-87	AD_ASST	4400
17	201	Michael	Hartstein	MHARTSTE	515.123.5555	17-FEB-96	MK_MAN	13000
18	202	Pat	Fay	PFAY	603.123.6666	17-AUG-97	MK_REP	6000
19	205	Shelley	Higgins	SHIGGINS	515.123.8080	07-JUN-94	AC_MGR	12000
20	206	William	Gietz	WGIEZT	515.123.8181	07-JUN-94	AC_ACCOUNT	8300

Advantages of Views

To restrict
data access

To make complex
queries easy



To provide data
independence

To present different
views of the same
data

Simple Views and Complex Views

Feature	Simple Views	Complex Views
Number of tables	One	One or more
Contain functions	No	Yes
Contain groups of data	No	Yes
DML operations through a view	Yes	Not always

Creating a View

- You embed a subquery in the CREATE VIEW

```
CREATE [OR REPLACE] [FORCE|NOFORCE] VIEW view  
  [(alias[, alias]...)]  
  AS subquery  
[WITH CHECK OPTION [CONSTRAINT constraint]]  
[WITH READ ONLY [CONSTRAINT constraint]];
```

- The subquery can contain complex SELECT syntax.

Creating a View

- Create the EMPVU80 view, which contains details of employees in department 80:

```
CREATE VIEW empvu80
AS SELECT employee_id, last_name, salary
FROM employees
WHERE department_id = 80;
CREATE VIEW succeeded.
```

- Describe the structure of the view by using the DESCRIBE command:

```
DESCRIBE empvu80
```


Creating a View

- Create a view by using column aliases in the subquery:

```
CREATE VIEW    salvu50
  AS SELECT    employee_id ID_NUMBER, last_name NAME,
              salary*12 ANN_SALARY
              FROM      employees
              WHERE      department_id = 50;
CREATE VIEW succeeded.
```

- Select the columns from this view by the given alias names:

Retrieving Data from a View

```
SELECT *  
FROM salvu50;
```

	ID_NUMBER	NAME	ANN_SALARY
1	124	Mourgos	69600
2	141	Rajs	42000
3	142	Davies	37200
4	143	Matos	31200
5	144	Vargas	30000

Modifying a View

- Modify the EMPVU80 view by using a CREATE OR REPLACE VIEW clause. Add an alias for each column name:

```
CREATE OR REPLACE VIEW empvu80
(id_number, name, sal, department_id)
AS SELECT  employee_id, first_name || ' '
           || last_name, salary, department_id
FROM      employees
WHERE     department_id = 80;
CREATE VIEW succeeded.
```



- Column aliases in the CREATE OR REPLACE VIEW clause are listed in the same order as the columns in the subquery.

Creating a Complex View

Create a complex view that contains group functions to display values from two tables:

```
CREATE OR REPLACE VIEW dept_sum_vu
  (name, minsal, maxsal, avgsal)
AS SELECT    d.department_name, MIN(e.salary),
             MAX(e.salary),AVG(e.salary)
  FROM      employees e JOIN departments d
  ON        (e.department_id = d.department_id)
  GROUP BY  d.department_name;
CREATE VIEW succeeded.
```

Rules for Performing DML Operations on a View

- You can usually perform DML operations on simple views. 
- You cannot remove a row if the view contains the following:
 - o Group functions
 - o A `GROUP BY` clause
 - o The `DISTINCT` keyword
 - o The pseudocolumn `ROWNUM` keyword

Rules for Performing DML Operations on a View

You cannot modify data in a view if it contains:

- Group functions
- A `GROUP BY` clause
- The `DISTINCT` keyword
- The pseudocolumn `ROWNUM` keyword
- Columns defined by expressions

Rules for Performing DML Operations on a View

You cannot add data through a view if the view includes:

- Group functions
- A `GROUP BY` clause
- The `DISTINCT` keyword
- The pseudocolumn `ROWNUM` keyword
- Columns defined by expressions
- `NOT NULL` columns in the base tables that are not selected by the view

Using the WITH CHECK OPTION Clause

- You can ensure that DML operations performed on the view stay in the domain of the view by using the WITH CHECK OPTION clause:

```
CREATE OR REPLACE VIEW empvu20
AS SELECT      *
   FROM        employees
   WHERE       department_id = 20
   WITH CHECK OPTION CONSTRAINT empvu20_ck ;
CREATE VIEW succeeded.
```

- Any attempt to change the department number for any row in the view fails because it violates the WITH CHECK OPTION constraint.

Denying DML Operations

- You can ensure that no DML operations occur by adding the `WITH READ ONLY` option to your view definition.
- Any attempt to perform a DML operation on any row in the view results in an Oracle server error.



Denying DML Operations

```
CREATE OR REPLACE VIEW empvu10  
    (employee_number, employee_name, job_title)  
AS SELECT      employee_id, last_name, job_id  
    FROM        employees  
    WHERE       department_id = 10  
    WITH READ ONLY ;  
CREATE VIEW succeeded.
```

Removing a View

You can remove a view without losing data because a view is based on underlying tables in the database.

```
DROP VIEW view;
```

```
DROP VIEW empvu80;  
DROP VIEW empvu80 succeeded.
```